

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1403-2

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	EXHAUST EMISSION USEFUL LIFE (miles)			INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)			
2007	7GMXT06.2382	LDT: 6001-8500# GVW, 3751- 5750# ALVW	"LEV II" Low Emission Vehicle (LEV II LEV)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2		
				120 K	150K		,	Unleaded)		
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE FAMILY (EVAF) DISPLACEMENT (L)							
1	2TWC, 2	HO2S(2), SFI, OBD(F)		7GMXR0178820						
•		*	7GMXR0223840							
•		*	6, 6.2							
•		*								

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1403-1 dated January 19, 2006.

Executed at El Monte, California on this

Allen Lyons, Chief

Mobile Source Operations Division

day of February 2006.

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

										applicable t	o losting	yasum y	J IESI IUU	4.1
		@ RAF=* RAF = *	NMOG or			=non-CH4 c	rganic gas;	NMHC=non-	CH4 hydrocarbor	n; CO=carboi	monoxide; N	Ox=oxides o	f nitrogen;	
CERT STD NMOG NM		NMHC CERT	NMHC STD											
0.054	0.055	[g/mi]	[g/mi]	[g/mi]	CERT	[g/mi] STD	CERT	x [g/mi] STD	HCH	O [mg/mi]	PM [g/mi])x [g/mi]
45	@ 50K	0.058	*	0.075	1.8	3.4	0.02	0.05		15.	CERT	STD	CERT	STD
	@ UL	0.058	*	0.090	1.8	4.2	0.02	0.07		18.	•		0.01 0. 01	0.07
0) 50°F & 4K	0.125	*	0.150	2.6	3.4	0.03	0.05		30.		•	*	*
CO [@ 20°F	[g/mi] & 50K		1.4	NMHC+No (comp	Ox [g/mi] osite)	CO [g (comp		NMHC- [g/mi] [CO [g/mi] [US06]		IC+NOx] [SC03]	CO [[g/mi] :03]
0En=		4.4		CERT	STD	CERT	STD	CERT	STD	CERT STD	CERT	STD	CERT	STD
STD	6.2		1000 miles	*	*	*	*	0.06	0.40	2.5 10.5	0.12	0.31	2.2	3.5
310	12.5	SFTP	@ * miles	•	*	*		*		•		*	*	•
Evaporative Family		3-Days Diu (grams	lurnal + Hot Soak ns/test) @ UL		oak 2-Days Diurnal + Hot Soak (grams/test) @ UL		t Soak JL	Running Loss (grams/mile) @ UL		Re	On-Board Refueling Vapor Recovery (grams/gallon) @ UL			
		CERT	S.	D CERT		S	STD		STD			STD		
7GMXR0176820		0.48	0.	90	0 0.35		15	0.00	0.05		0.03		0.20	
7GMXR0223840		0.59	0.	90	0.36	0.36 1.15		0.00	0.05		0.09		0.20	
*		*	,		•	1				* *		*		
	=												1	

* = not applicable; UL=useful life; PC=passenger car, LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2007 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
CADILLAC	ESCALADE EXT AWD	7GMXR0223840	1	6.2	*	*	SFTP	Full
CADILLAC	ESCALADE 2WD	7GMXR0176820	1	6.2	*	*	SFTP	Full
CADILLAC	ESCALADE AWD	7GMXR0176820	1	6.2	*	*	SFTP	Full
CADILLAC	ESCALADE ESV AWD	7GMXR0223840	1	6.2	*	*	SFTP	Full
GMC	K1500 YUKON DENALI AWD	7GMXR0176820	1	6.2	*	*	SFTP	Full
GMC	K1500 YUKON XL AWD	7GMXR0223840	1	6.2	*	ŵ	SFTP	Full
CHEVROLET	K1500 SILVERADO CLASSIC 4WD	7GMXR0176820	1	6	*	*	SFTP	Full
CHEVROLET	C1500 SILVERADO CLASSIC 2WD	7GMXR0176820	1	6	*	*	SFTP	Full
GMC	K1500 SIERRA CLASSIC 4WD	7GMXR0176820	1	6	*	*	SFTP	Full
GMC	C1500 SIERRA CLASSIC 2WD	7GMXR0176820	1	6	*	*	SFTP	Full
GMC	K1500 SIERRA CLASSIC AWD	7GMXR0176820	1	6	*	*	SFTP	Full