Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	STANDAR (LEV=low emis transitional LE	T EMISSION D CATEGORY slon vehicle; TLEV V; ULEV=ultra LEV super ULEV)		FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
2008		8GMXT06.0392		2   L	DT: >6000# GVW, 3750-5750# ALVW	LE	V II LEV	120K / 150K	Gasoline (Tier 2 Unleaded) plus Battery- Assist					
No.		PORA ILY (E		No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEM		= not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TV WU= warm-up cat. O2S/HO2S=oxygen sensor/heated 0						
1	8GMXR0176822			1	2TWC, 2HO2S(2),	SFI, OBD (F)	AFS/NAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFi= multiport fuel injection/sequential MFI							
2	•		2	+										
3	•		3	•		TBI= throttle body injection TC/SC=turbo /super charger   CAC=charge air cooler OBD (F) / (P)=full /partial on-board								
4		•		4	*		diagnostic prefix 2=parallel (2) suffix=series							
EVAF No.		ECS ENGINE No. SIZE (L)					S SUBJECT TO SFTP DS ARE UNDERLINED ABBREVIATIONS:							
1	1 6.0			Chevrolet: C1500 Tahoe Hybrid 2WD, K1500 Tahoe Hybrid 4WD; GMC: C1500 Yukon Hybrid 2WD, K1500 Yukon Hybrid 4WD										
*		-	*											
*	• •		1-	•										
*		* * * * * * * * * * * * * * * * * * * *			*									

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/ml]			NMOG @ RAF= * CH4 RAF = *			NMOG or	nitrogen	HCHO=fo	rmaidehyde	РМ≕раг	ticulate	matter	H4 hydrocal RAF=reactive dispensed]	ity adjustme	nt factor	2/3 D [a/test	]=2/3 dav	
CER	tT	STD	NMOG		NMHC	NMHC STD	mg=millig	am mi	r⊓lle K=1	000 miles	FEC	dearees F	ahrenheit	SFTP=supp				
0.04	7	0.050	CERT		CERT	[g/mi]	CO [g/ml]		NOx [g/mi]			HCHO [mg/ml]		PM [g/mi]		Hwy NOx [g/mi]		
		0.000	[g/mi]	1	[g/mi]	19,,,,,,1	CERT	STD	CERT	STI	D	CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.04		*	0.075	0.6	3.4	0.02	0,0	5	*	15	•	*	0.01	0.07	
		@ UL	0.05	2	•	0.090	0.6	4.2	0.02	0.0	7	•	18	*	0.01	0.01	0.09	
	@ 50	°F & 4K	0.06	)	*	0.150	1.0	3.4	0.03	0.0	5	*	*	*	•	*	*	
	CO [g/mi] @ 20°F &		.V) or 501	< (⊤ler	/, ULEV, 1, TLEV)	NMHC+NC (compo			g/mi] posite)	NMH( [g/mi]	+NOx [US06		CO [g/mi] [US06]		IC+NOx		[g/mi] C03]	
50	K	SFTP 2	= @ VL (	Tier 1,	TLEV)	CERT	\$TD	CERT	STD	CERT	ST	CE	RT ST	CERT	STD	CERT	STD	
CERT	1.3	- 20	24.3	SFT	ΓP @ 4K	*	*	*	•	0.03	0.4	0 0	.9 10.	5 0.02	0.31	0,8	3.5	
STD	12,5			SFT	TP@UL	*	•	•	•	*	*		• •	*	•	•	•	
@ UL	F	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2 EVAPO				PORA	RATIVE FAMILY 3 EVAF				PORATIVE FAMILY 4		
W 0L	3-D	2-0	) F	₹L	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORVI	R 3-D	2-D	RL	ORVR	
CERT	0.62	0.4	3 0.	.00	0.01	*		•	*	*	+	*	• -	·	+	•	•	
STD	0.90	1.1	5 0.	05	0.20	•	•		•	•		*	•	*	*	•	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_1944\_ day of October 2007.

🕰 Annette Hebert, Chief

Mobile Source Operations Division