TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0612 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

*			•	_				- LOXUS GO 40011				
1	j	1	3.5	- 1	Lexus GS 450h							
No.		No.	SIZE (I		VEHICLE MAKES & MODELS	HICLES SUBJI ANDARDS ARI	ECT TO SFTP UNDERLINED	ABBREVIATIONS:				
3 EVAF	=	ECS ENGINE			LIP/IIIA P			TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
2							•	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AiR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
1	8TY	YXR0160E12			2WU-TWC, 2TV	NC, 2AF	S, 2HO2S,DGI,					
No.	FAN	APORA MILY (E	VAF)	No	EMISSION CONTROL	MS (ECS)	* = not applicable	14*** Warming Car. Ozornozo-ozyteki sensorneaten UZS				
2008		8TYXV03.5CC4		4	Passenger Car		Emiss (LE\	uper-Ultra Low ion Vehicle /II SULEV)	120K / 150K	Gasoline plus Battery-Assist		
MODI YEA		TEST GROUP			VEHICLE TYPE {PC=passenger car; LDT=light- truck; MDV=medium-duty vehi- tvW=loaded vehicle weight LVW=adjusted LVW)	STANDAF (LEV=low emi transitional L SULEV	ST EMISSION RD CATEGORY ssion vehicle; TLEV= EV; ULEV=ultra LEV; =super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

	NMOG FLEET NMOG @ R AVERAGE [g/mi] CH4 RAF			RAF=*	NMOG or	muoden	nunu-ro	mruaioemvo	an PM≕nai	TICIII2TO IY	natter W	OFFERDACTI	rbon CO=c	ant frates	2/2 D (-144	1-919 da		
CER	T	STD	CERT CERT [g/mi] [g/mi]		NMHC STD	dlurnal+h mg=millig	OL-SOAK K	r (8ւայ)=տ	ınning loss 1000 miles	OKYK	g/gallon (lispensed Tranhait	=on-board r	refueling var	OF RECOVERY	g=gram		
0.03	0	0.040				[g/m1]	CO [g/mi]		NOx [g/mi]		, F	ICHO [n	ng/mi]	PM [SFTP≂supplemental fe PM [g/mi]		Hwy NOx [g/mi]	
- market	OZ SZINISKI Z						CERT	STD	CERT	T ST	D C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K		*	*	•		† *	•	٠.		•	*	•	*	•	•	
	1/4	@ UL	0,0	800	*	0.010	0.1	1.0	0.01	0.0	2	•	4		0.01	0.01	0.03	
# Pub	@ 50	°F & 4K		•	•	*		•	*	•	1	•	•		•	*	•	
@ 20	"F &	SFTP 1 = @ 4K (SULEV, ULEV LEV) or 50K (Tier 1, TLEV SFTP 2 = @ UL (Tier 1, TLEV)		er 1, TLEV)				[g/mi] NMHC+N posite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
50	K	SFTP 2	= (Q) (JL (Tier 1	I, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T ST	D CER	T STD	CERT	STD	
CERT	1,6				SFTP 1	•	٠	*	•	0.02	0.14	0.8	8.0	0.02	0.20	0.01	2.7	
STD	10.0				SFTP 2	•	*	٠	•		*	*	*	-	•		•	
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2 EVAPO					PORATI	RATIVE FAMILY 3 EVAPORATIVE FAMILY 4					LY 4	
	3-D	2-0	_	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR	
CERT	0.41	0.4	5	0.01	0.03	1	•	•	•	•	*	*	-	4		*	•	
STD	0.50	0.6	5	0.05	0.20		•	*	*	*	•	•	•	*	*	•		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______ day of September 2007.

Annette Hebert, Chief

Mobile Source Operations Division