

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW; GVW=gross vehicle weight)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas)
2008	8VVXB03.2U2N	PC and LDT ≤ 6,000 pounds GVW (PC; LDT 3,751 – 5,750 pounds LVW)	LEV II ULEV	120K / 150K	Gasoline
No.	EVAPORATIVE FAMILY (EVAF)	No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS)	* = not applicable	
1	8VVXR0130EB6	1	2TWC(2), SFI, 2HO2S, 2HAFS, OBD (P)	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler DOR=direct O3 reduction OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series	
2	8VVXR0130ET3	2	*		
3	*	3	*		
EVAF No.	ECS No.	ENGINE SIZE (L)	VEHICLE MAKES & MODELS	VEHICLES SUBJECT TO SFTP STANDARDS ARE UNDERLINED	ABBREVIATIONS:
1	1	3.2		<u>Volvo: (PC) S80 3.2, S80 3.2 AWD, V70 3.2, XC70 3.2 AWD</u>	
2	1	3.2		<u>Volvo: (LDT 3,751 – 5,750 LVW) XC90 3.2, XC90 3.2 AWD</u>	
*	*	*			
*	*	*			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.


NMOG FLEET AVERAGE STD [g/mi]		NMOG @ RAF= * CH4 RAF= *		NMOG or NMHC STD [g/mi]	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal/hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensand]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
PC/LDT1	LDT2	NMOG CERT [g/mi]	NMHC CERT [g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]			
0.040	0.050				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
	@ 50K	0.019	*	0.040	0.2	1.7	0.04	0.05	*	8	*	*	0.01	0.07		
	@ UL	0.025	*	0.055	0.3	2.1	0.06	0.07	*	11	*	0.01	0.01	0.09		
	@ 50°F & 4K	0.059	*	0.080	0.3	1.7	0.03	0.05	*	16	*	*	*	*		
CO [g/mi] @ 20°F & 50K	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
CERT 1.4		SFTP 1	*	*	*	*	0.04	0.14	0.1	8.0	0.07	0.20	0.3	2.7		
STD 10.0		SFTP 2	*	*	*	*	*	*	*	*	*	*	*	*		
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.40	0.39	0.01	0.02	0.34	0.38	0.01	0.01	*	*	*	*	*	*	*	*
STD	0.50	0.65	0.05	0.20	0.65	0.85	0.05	0.20	*	*	*	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That at the request of the manufacturer, LDT models in this test group with a GVW over 6,000 pounds are certified to and shall be required to comply with, the evaporative emission standards applicable to LDT under 6,000 pounds GVW. At the request of the manufacturer, LDT models in this test group with a LVW 3751 to 5750 pounds are certified to, and shall be required to comply with, the passenger car SFTP standards.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 28 day of June 2007.


Annette Hebert, Chief
Mobile Source Operations Division