

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE				MI	VEHICLE TYPE PC=passenger car; LDT=light-duty truck; pV=medium-duty vehicle; ALVW=adjuste aded vehicle weight; LVW=loaded vehicl weight; GVW=gross VW)	ST (L	XHAUST EMISSION ANDARD CATEGOREV=low emission vehicl TLEV= transitional LEV; V=ultra LEV; SULEV=st ULEV)	RY le; ;	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
201	2 CME	CMBXJ03.5U2B		PC LDT: 6001-8500# GVW, 3751-5750# ALVW			LEV II ULEV		120K / 150K	Flexible Fuel: Ethanol (E85)/Gasoline (Tier 2 Unleaded)				
No.	EVAPORATIVE FAMILY (EVAF)		N	lo.	SPECIAL FEATURES & EMISSION CONTROL SYSTEM	S (ECS)	* = not applicable	WU=w	TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TW WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U/SCR-N= selective catalytic reduction-urea/ammonia;					
1	CMBXR0165LNF			1	2TWC, 2HO2S(2),	DFI, OBD(NH3OC=SCR-U/SCR-N ammonia slip catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; AFS/HAFS=air-fuel ratio sensor / heated AFS; NOXS= NOX sensor; RDOS=reductant quality sensor; EGR=exhaust gas recirculation; EGRC=cooled EGR; AIR=secondary air injection; PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)/(B)= full/partial/both on-boa diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2)							
2	CMBXR0170LNF			2	And the second s									
3	*			3	· · · · · · · · · · · · · · · · · · ·									
4	*			4	2. * D. *									
5	*	*				11.3								
6	*	*		6			suffix=series;							
EVA No.				1611	MAKES & MODELS STAN	IDARDS A	JECT TO SFTP RE <u>UNDERLINED</u>	ABBREVIATIONS:						
1	1	3.			MERCEDES BENZ: C350, E350 COUPE, E350 CONVERTIBLE, E350 COUPE 4MATIC									
2	1	3.		MERCEDES BENZ: (LDT 3,751-5,750# ALVW) ML 350 4MATIC										
					AND THE CONTRACT OF THE CONTRA									
*	* *													
*	*	*			Part Andrews Programme (PART)		and the second second							

That the exhaust, the evaporative emission standards, and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

NMOG FLEET NMOG @ RAF= AVERAGE [g/mi] CH4 RAF = *					RAF= * F = *	NMOG or	diditial library in the Land i												
PC/LDT1 LDT2			NMOG CERT		NMHC	NMHC STD	mg=milligram mi=mile CO [g/mi]			K=1000 miles F		HCHO [mg/mi]			PM [g/mi]		Hwy NOx [g/mi]		
STD	_	STD		T i]	CERT [g/mi]	[g/mi]	CERT	STD	CERT			ERT	1		RT	STD	CERT	STD	
0.035	SUPPLEMENTAL PROPERTY OF	.043 @ 50K	0.011				0.7	1.7	0.02	0.05		0.4 (0.5)	8 (8)	*		*	0.02 (0.02)	0.07 (0.07)	
		@ UI 0.01		9		(0.075) 0.055 (0.090)	(0.7) 1.1 (1.1)	2.1 (2.1)	0.04	0.07	7 0	0.5	11 (11)	(*)		0.01 (0.01)	0.03 (0.03)	0.09 (0.09)	
	@ 50	°F & 4K	(0.03	(1)		*	*	*	*	*		*	*	*		*	*	*	
CO [g		SFTP 1 = @ 4K (SULEV, ULEV,			NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi [US06]	1	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
@ 20°F					1, TLEV)	CERT	STD	CERT	STD	CERT	STD		ERT S	TD (CERT	STD	CERT	STD	
CERT	3.0 (1.4)			SFT	P @ 4K	*		*		0.03	0.14	1	0.9 8	.0	0.03	0.20	0.4	2.7	
STD	10.0			SFT	P@UL	*	*	*	*	*	*		*	*	*	*	*	*	
	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3					EVAPORATIVE FAMILY 4				
@ UL	3-D	2-D		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	F	RL OR	VR	3-D	2-D	RL	ORVR	
CERT	0.43	*	0.	.000	0.004	0.52	*	0.01	0.06	*	*		* ,		*	*	*	*	
STD	0.50	0.65	0	.05	0.20	0.90	1.15	0.05	0.20	*	*		*: 1		*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of rebruary 20

Annette Hebert, Chief

Mobile Source Operations Division