BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0343

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR			EXHAUST EMISSION STANDARD CATEGORY	USEFUL LI	FE (miles)	FUEL TYPE		
0044	Passenger Car (PC)/LDT2:		"LEV II" Ultra Low Emission	EXH / ORVR	EVAP	Gasoline		
2014	EBMXJ02.0N20	<6000#GVW, 3751-5750#LVW	Vehicle (LEV II ULEV)	150K	150K	Gasonie		
No. ECS & SPECIAL FEATURES		EVAPORATIVE FAI	EVAPORATIVE FAMILY (EVAF)					
1	1 TWC, AFS,HO2S, DFI, TC, CAC, OBD(F)		EBMXR013	EBMXR0130N54				
*	*		*			2		
*		*	*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of March 2013.

Annette Hebert, Chief

Duren

Mobile Source Operations Division

EXECUTIVE ORDER A-008-0343

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=" AVERAGE [g/mi] CH4 RAF = "			HCHO=form	CH4=methane; NMOG=non-CH4 organic gas, NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of n HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+											
PC/LDT STD	LDT2 STD	NMOG CERT	NMHC	NMHC STD	hot-soak; R mi≃mile; K=	not-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure									
0.035	0.043	[g/mi]	CERT [g/mi]	[g/mi]	COI	g/mi]	NOx	[g/mi]	HCHO	[mg/mi]	PM (g/mi]	Hwy NO	x [g/mi]	
0.000	0.043	[g/m]	[[gmm]		CERT	STD	CERT	\$TD	CERT	STD	CERT	STD	CERT	STD	
2.5	@ 50K	0.011	*	0.040	1.1	1.7	0.02	0.05	*	8.	*	*	0.003	0.07	
	@ UL	0.014	*	0.055	1.3	2.1	0.02	0.07	*	11.	*	0.01	0.004	0.09	
@	50°F & 4K	0.009	*	0.080	0.4	1.7	0.02	0.05	*	16.	*	*	•	*	

.Co				Ox [g/mi] oosite)	CO [g/mi] osite)		+NOx [US06]	lns co [NMHÇ [g/mi]] 00 [S0]	g/mi] :03]
@ 2	0°F & 50K		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	1.1	SFTP @ 4000 miles	*	*	*	*	0.04	0.14	1.8	8.0	0.04	0.20	1.2	2.7
STD	10.0	SFTP @ * miles	*	* *	*	*	*	*	*	*	*	*	*	*

Evaporative Family	3-Days Diurn (grams/te	al + Hot Soak est) @ UL		ial + Hot Soak est) @ UL	Runnin (grams/m	ng Loss nile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
EBMXR0130N54	0.31	0.50	*	0.65	0.01	0.05	0.01	0.20	
*	*	*	*	•	•	*	*	*	
*	*	*	*	*	* .	*	*	+	
*	*	*	*	*	*	*	*	*	

* =not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT≤6000#GVWR,0-3750#LVW; LDT2=LDT≤6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-1000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF= Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=Wide range/linear/heated air-fuel ratio sensor; NOXS=NOx sensor; RDQS=reductant quality sensor; NH3S = Ammonia sensor; EGR=exhaust gas recirculation; EGRC=EGR cooler; AIR/AIRE=secondary air injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)(B)=full/partial/both on-board diagnostic; DOR=direct ozone reducing; HCT=Hydrocarbon Trap; BCAN=bleed carbon canister; prefix 2=parallei; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=tiquefied petroleum gas; E85="85%" Ethanol (*15%"gasoline) Fuel;

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBDII
вмw	328i Gran Turismo	EBMXR0130N54	1	2	PC	HCT	Full
BMW	328i SPORT WAGON	EBMXR0130N54	1	2	PC	нст	Full
BMW	X1 sDrive28i	EBMXR0130N54	1	2	PC	HCT	Full
BMW	320i	EBMXR0130N54	1	2	PC	HCT	Full
вмw	328i	EBMXR0130N54	1	2	PC	HCT	Full
вмw	528i	EBMXR0130N54	1	2	PC	HCT	Full
вмw	Z4 sDrive28i	EBMXR0130N54	1	2	PC	HCT	Full
BMW	328i xDrive SPORT WAGON	EBMXR0130N54	1	2	PC.	нст	Full
BMW	320i xDrive	EBMXR0130N54	1	2	PC	HCT	Full
BMW	328i xDrive	EBMXR0130N54	1	2	PC	HCT	Full
BMW	528i xDrive	EBMXR0130N54	1	2	PC	HCT	Full
BMW	X1 xDrive28i	EBMXR0130N54	1	2	PC	нст	Full
BMW	X3 xDrive28i	EBMXR0130N54	1	2	LDT2	HCT	Full