HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0614

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

			TEST O	GROUP INFO	RMATION				
MODEL YEAR	TEST GRO	UP VEHIC	LE CLASS(ES)		FUEL CATEGORY DEDICATED SINGLE FUEL VEHICLE		GASOLINE		
2015	FHNXV01.51	IH2	PC	DEDI					
	USEFUL LIF	E (miles)	VEHICLE E	MISSION CA	TEGORY	INTERI	M / INTERME	EDIATE IN-USE STD	
EXH/0	DRVR	EVAP	FTP		SFTP	FTF		SFTP	
150	000	150000	LEV3 ULEV125	LEV	3 COMPOSITE	*		NMOG+NOx	
SPECIAL	FEATURES &	EXHAUST EMISSION O	ONTROL SYSTEMS		OBD STATUS	Name and Address of the Address of t	ENGIN	NE DISPLACEMENT (L)	
1	WU-TWC,	TWC, WR-HO2S, HO2	S, EGR, DFI	FULL	ALL MOI	DELS			
*		*	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	PARTIAL			1.5		
*		•		PARTIAL W	ITH .				
		E	VAPORATIVE & REFUEL	ING (EVAP/O	RVR) FAMILY INFOR	MATION	4 May 4 88 10 10 10 10 10 10 10 10 10 10 10 10 10		
	EVAP / OR	VR FAMILY	EVAPOR	RATIVE STD	CATEGORY	EVAP E	MISSION ST	TD VEHICLE CLASS	
	FHNXR	0086VFA		LEV 2			P	C	
		*		*				•	
		•		*	•			*	
			EMISSION	N CREDIT IN	FORMATION				
	ALLOWANCE ST GROUP	AT PZEV ALLOWANCE FOR T GROUP	EST ALLOWANCE FOR GROUP		IMOG CREDIT FOR N-PZEV ZERO-EVAP	NMOG CREDI	T FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS	
	*				N.	N		N	
			NMOG AND FL	EET AVERA	GE INFORMATION				
NMOG RAF	CH4 RAF	NMOG/NMHC RATIO	HCHO/NMHC RATIO		MOG+NOX FLEET PC+LDT1 (0-3750 LVV			EET STD LDT2 (3751 LVW- GVWR) + MDPV	
*	*	1.1	0.05		0.100			0.119	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx Fleet Average" as applicable (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

@ Air Resources Board

HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0614

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(iii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(iii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwit

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of February 2014.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0614

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

EXHAUST E	MISSION S	TANDARDS A	AND CERT	FIFICATION	LEVELS (F	TP, HWFET	50 °F,	20 °F)	

	FUEL TYPE	PM=particulate hot-soak; RL [matter; RAF=rg/mi]=running lo	eactivity adjustr	nent factor; 2/3	D [g/test]=2/3 da =on-board refue	ay diurnal+	,		pen; HCHO=form mi=mile; K=10	,
	, , , , , , , , , , , , , , , , , , , ,		iOx (g/mi)	CO (HCHO	(mg/mi)	PM (g/mi)	HWY NMOG	+NOx (g/mi)
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
50°F @ 4K	GASOLINE - LEV3 E10	0.0312	0.250	0.34	2.1	0.1	16	*	*	*	*
FTP @ UL	GASOLINE - LEV3 E10	0.0359	0.125	0.34	2.1	0.1	4	*	0.01	0.0016	0.125
20°F @ 50K	GASOLINE - COLD CO	*	*	0.69	10.0	*	*	*	*	*	*

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		US06 / UC (LA92)						SC03				COMPOSITE				
	FUEL TYPE	FUEL TYPE NMOG+NOx (g/mi)		co (g/mi) PM (mg/mi)		NMOG+NOx (g/mi)		CO (g/mi)		NMOG+NOx (g/mi)		CO (g/mi)			
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	BIN	CERT	STD
@ UL	GASOLINE - LEV3 E10	*	*	*	*	*	*	*	*	*	*	0.0299	0.140	0.100	0.47	4.2

WHOLE VEHICLE EVAPORATIVE/ORVR EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE	WHOLE VEHICLE EV. 3-DAYS DIURNAL + HOT SOAK (g/test) @ UL			/APORATIVE TESTING 2-DAYS DIURNAL + HOT SOAK (g/test) @ UL			RUNNIN (g/mi)	G LOSS @ UL	ON-BOARD F VAPOR RE (g/gailon	COVERY
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD	CERT	STD
FHNXR0086VFA	GASOLINE - CARB	0. 257	0.50	*	0.518	0.65	*	0.000	0.05	*	*
FHNXR0086VFA	GASOLINE – TIER 2 UNLEADED	*	*	*	*	*	*	*	*	0.033	0.20
*	*	*	*	*	*	. *	*	*	*	*	*

FUEL ONLY & CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			FUEL ONLY EVAP					
EVAPORATIVE FAMILY	FUEL TYPE	3-DAYS DIURN/ (g/test	AL + HOT SOAK) @ UL	2-DAYS DIURN/ (g/test		CANISTER BLEED (g/test)		
		CERT	STD	CERT	STD	CERT	STD	
*	*	*	*	*	*	*	*	
*	*	*	*	*	*	*	*	
*	*	* *		*	*	*	*	

*=not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT <6000#GVWR,0-3750#LVW; LDT2=LDT <6000#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-10000#GVWR; MDV5=MDV 10001-14000#GVWR; MDPV=medium-duty passenger vehicle; ECS= emission control system; CERT= certification; STD= standard; FEL= family emission limit; LVW=loaded vehicle weight; ALVW=adjusted LVV; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; PZEV=partial allowance zero-emission vehicle; AT PZEV=advanced technology PZEV; TZEV=transitional zero-emission vehicle; TWC/OC3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF=diesel particulate filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=wide rage/linear/heated air-fuel ratio sensor; NOXS= NOx sensor; RDQS=reductant quality sensor; NH3S = ammonia sensor; EGR=exhaust gas recirculation; EGRC=EGR cooler; AIR/AIRE=secondary air injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI= sequential/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; FIP/\$=full/partial/partial with fines on-board diagnostic; DOR=direct ozone reducing; HCT=hydrocarbon trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" ethanol ("15%"gasoline) fuel; E10="10%" ethanol ("90%"gasoline) fuel; A=automatic transmission; M=manual transmission; OT=other transmission; CV=continuously variable transmission;

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
HONDA	FIT	PC	1.5	CV1, CV7, M6	FHNXR0086VFA	1	FULL	*