

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER D-546
Relating to Exemptions under Section 27156
of the Vehicle Code

BOSAL MEXICO SA DECV
"THREE-WAY PLUS OXIDATION CATALYTIC CONVERTER SERIES O6000/R6000"

WHEREAS, Vehicle Code Sections 27156 and 38391, and Title 13, California Code of Regulations (hereafter "CCR") Section 2222(h), authorize the California Air Resources Board (ARB) and its Executive Officer to exempt new aftermarket catalytic converters from the prohibitions of Vehicle Code Section 27156.

WHEREAS, Bosal Mexico SA DECV (Bosal Mexico) of Acceso 1, 126 Fracc., Ind. La Montana, Queretero, QRO Mexico CP 76150, has applied to the ARB for exemption from the prohibitions in Vehicle Code Sections 27156 and 38391 to market their new aftermarket series O6000/R6000 three-way plus oxidation catalytic converter (TWC + OC) for the following application, except for vehicles equipped with an on-board diagnostic II (OBD-II) system:

Converter Type	Series Number	Converter Use	Max. Eng. Size	Max. Veh. Test Wt.
TWC + OC	O6000 (Oval)	TWC + OC	5.9L (360 CID)	6,000 lbs. (GVWR = 7,140 lbs.)
	R6000 (Round)	TWC + OC		
	O6000 (Oval)	TWC		
	R6000 (Round)	TWC		

WHEREAS, pursuant to the authority vested in the Executive Officer by Health and Safety Code Section 39515 and in the Chief, Mobile Source Operations Division by Health and Safety Code Section 39516 and Executive Order G-02-003, the ARB finds that the above aftermarket catalytic converter complies with the California Vehicle Code Section 27156 and Title 13, California Code of Regulations, Section 2222(h). Emission performance of the catalytic converter was based on durability bench-aging by DMC-2 Division of OMG Corporation using the ARB-modified RAT-A bench-aging cycle for a duration of 50 hours, in lieu of the AMA driving cycle (Reference Appendix IV, Title 40, part 86, Code of Federal Regulations (June 28, 1977)).

WHEREAS, emissions tests conducted at Motorola AIEG laboratory, Dearborn, Michigan, using a 1990 5.9L Dodge Ram Van, and a 1994 5.9L Dodge Pickup 2500 showed the following conversion efficiencies which meet the minimum requirements for new aftermarket catalytic converters:

Catalyst Application Type

<u>Pollution Component</u>	<u>TWC + OC</u>	<u>TWC</u>
HC: Min. Requirement	70%	70
Bosal's series O6000/R6000	76.6	78.9
CO: Min. Requirement	70	70
Bosal's series O6000/R6000	74.9	77.4
NOx: Min. Requirement	50	60
Bosal's series O6000/R6000	61.4	78.3

IT IS HEREBY RESOLVED that the above catalytic converter is exempt from the prohibitions in Vehicle Code Section 27156 for installation on the approved vehicle applications subject to the following conditions:

1. No changes are permitted to the catalytic converter as described in the application for exemption. Any changes to the catalytic converter or any of its components, and other factors addressed in this order must be evaluated and approved by the ARB prior to marketing in California.
2. Marketing of the catalytic converter using identifications other than those shown in the exemption application, and in this Executive Order, or marketing of the catalytic converter for application other than the ones shown in this Executive Order shall be prohibited unless prior approval is obtained from the ARB. Exemption of this product shall not be construed as an exemption to sell, offer for sale, or advertise any components of the catalytic converter as individual devices.
3. Any oral or written references to this Executive Order or its content by Bosal Mexico, its principals, agents, employees, distributors, dealers, or other representatives must include the disclaimer that the Executive Order or the exemption it provides is not an endorsement or approval of any emission reduction claims for the catalytic converter and is only a finding that the catalytic converter is exempt from the prohibitions of Vehicle Code Section 27156.
4. Bosal Mexico SA DECV's installation instructions for the new catalytic converter must conform to requirements in Paragraphs I and IX of California Evaluation Procedures for New Aftermarket Non-Original Equipment Catalytic Converters.
5. Upon installation, the catalytic converter must carry a manufacturer's warranty for 25,000 miles on the substrates and 50,000 miles or five years on the shell and end pipes.

Violation of any of the above conditions shall be grounds for revocation of this order. The order may be revoked only after ten day written notice of intention to revoke it, during which period the holder of the order may request in writing a hearing to contest the proposed revocation. If a hearing is requested, it shall be held within ten days of receipt of the request, and the order may not be revoked until a determination is made, after the hearing, that grounds for revocation exist.

Executed at El Monte, California, this 28th day of January 2003.



Allen Lyons, Chief
Mobile Source Operations Division