Juli

(Page 1 of 2)

### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER M-1-282 Relating to Certification of New Motorcycles

#### KAWASAKI HEAVY INDUSTRIES, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9:

IT IS ORDERED AND RESOLVED: That 2000 model-year Kawasaki Heavy Industries, Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

	Displacement		Exhaust Emission Control Systems
Engine Family	<u>Cubic Centimeters</u>	Class	& Special Features
YKAXC.676AAA	676	III	Pulsed Secondary Air Injection

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon St	tandards	Hydrocarbons	Carbon N	Monoxide
(Corporate Average)	(Designated)	(Certification)	(Standard)	(Certification)
Grams per	Grams per	Grams per	Grams per	
<u>Kilometer</u>	Kilometer	<u>Kilometer</u>	Kilometer	<u>Kilometer</u>
1.0	1.3	0.8	12	10

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 4 day of November 1999

R. B. Sammerfield, Chief

Mobile Source Operations Division

Page: 6
Issued: SEP 0 9 1999
Revised:

E.O.#: M-1-282

Engine Family: YKAXC.676AAA

## Motorcycle Model Summary Form

65. Model Designation	66. Worst Case	67. Disp. (cc)	68. Bore / Stroke (mm)	69. Basic Ignition Timing (degrees)	70 Power (kW)	71 Rated Speed (rpm)	72 Rated Torque (Nm)	73. Rated Speed (rpm)
EJ650-A2	Yes	676	72.0 X 83.0	10°/900 rpm	37	7000	56	5500
- 410								
								- 2

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76 Road Load (nt)	77 Total Vehicle Mass (kg)	78 Full Weight with All Factory Options (kg)	79. Trans. Type	80 N/V
EJ650-A2	340	336 ~ 345	143.6	212	265	M-5	37.99

Page: 1

Issued: SEP 0 9 1999

Revised:

E.O.#: M-1-282

### **Motorcycle Engine Family Information Form**

Manufacturer: KAWASAKI HEAVY INDUSTRIES, LTD. 0.1 Certification Contact Person, address, phone, and fax: Jeffrey D. Shetler / David Corey Kawasaki Motors Corp., USA. 9950 Jeronimo Road, Irvine. CA 92618-2084 Fax: 949-460-5602 Tel: 949-770-0400 Displacement: 676cm<sup>3</sup> 3. Model Year: 2000 Number of Cylinders: 2 4. Process Code: New (new, correction, revision, r/c, f/f. etc.) Cylinder Arrangement: Inline-2 12. Engine Family: YKAXC.676AAA 13. Cylinder Head Configuration: SOHC 50s Engine Code: 49s Engine Code: Calif. Engine Code: EJ650A-AC1 14. Type of Cooling: Air Combustion Cycle: 4 6. Emission Control System: EM+AFR PAIR 15. Method of Aspiration: Natural 16. 7. Calif. Designated Standard: 1.3 gm/km Fuel System: Carburetor Projected Annual Sales: Number of Catalytic Converters: NA 9. New Technology \_ Yes X No If yes, cite the correspondence or reference the submittal document: 19. Adjustable Parameters: Method Approved Adjustable Range Tamper Resistance Method Parameter(s) (or NA) (or NA) Carry over NA an aluminum cap is placed Air adjuster on over the adjusting screw. carburetor (Air/Fuel Ratio) 20. AECDs in the Emission Control Systems: Evaporative System Exhaust System AECDs In System: AECDs In System: PAIR Sealed loop EM and AIR with Canister

Application Processed by: Joseph, Jegede Date: 11/3/99
Reviewed by: Tolon Date: 11/3/90

Revised:

E. O. #: M-1-282

Engine Family: YKAXC.676AAA

## **Motorcycle Test Information Form**

27. Are you carrying over test results from a previously certified family? \_ Yes X No

a) If yes, indicate family name:

- b) Is the family being certified identical to the family from which the data is being carried over?
- 28. Model Designation of Test Vehicle: EJ650A
- 29. Test Information Number: 00-1
- 30. Vehicle ID: JKAEJEA13XA000015
- 31. Service Accumulation Duration: 15000 (km)
- 32. Maximum Rated Power: 37 kW @ 7000 RPM
- 33. Displacement: 676 cc
- 34. Certification Fuel: Indolene: 91-95 RON
- 35. Test Data Set: Test 1

- 36. Road Load: 143.6 nt at 65 kph
- 37. Inertia Mass: 340 kg
- 38. N/V: 37.99

**Emission Values** 

 EVAP. Bench Test Method Approved: Date: <u>2/23/1983</u>

Reference: 84ARB-03

- 40. Unscheduled Maintenance: Yes X No
- 41. If yes, Vehicle Log provided: NA

42. Exhaust Emission Deterioration Factors:

System Khometers	nc	CO
3513	0.85	10.3
6012	0.66	10.2
6042	0.49	7.8
12013	0.77	7.7
12043	0.66	7.3
15012	0.76	10.2
alues at 15000 km:	HC = 0.7196	CO = 8.3981
alues at 30000 km:	HC = 0.7737	CO = 7.0784
	3513 6012 6042 12013 12043 15012 alues at 15000 km:	3513 0.85 6012 0.66 6042 0.49 12013 0.77 12043 0.66 15012 0.76  alues at 15000 km: HC = 0.7196

Regular DF	X
Modified DF	
If different veh	icle
specify vehicle	ID

43. Emission Test Results:

Official Test Results		Test 1	Test 2	Test 3	Test 4
g/km	СО	10.2			
g/km	CO <sup>2</sup>	80.6			
g/km	HC	0.76			
g/test	Evap.	0.557			

	Deterioration Factors
(X)	1.000
(X)	1.075
(+)	0.036

44. Certification Levels:

g/km	СО	$\overline{(10)}$	
g/km	HC	0.8	
g/test	Evap.	0.557	

Revised:

E. O. #: M-1-282

Engine Family: YKAXC.676AAA

### **Evaporative Emission Information**

- 45. Evaporative Family: YKAXC17.0A07
- 46. Number of Evap. Canisters: \_1
- 47. Design Working Capacity: 17.0 g
- 48. Configuration: Sealed loop
- 49. Number of Storage Areas: 1
- 50. Fuel Reservoir Volume: 2.2 liters
- 51. Vent System Configuration: Sealed loop
- 52. Nominal Tank Capacity: 18 liters

- 53. Engine Displacement Class: III
- 54. Storage Medium Composition: Activated carbon
- 55. Evap. Canister Medium Volume: 400cm<sup>3</sup>
- 56. Evap. Family Sales: 600
- 57. Engine Code: EX305B-AC1••••Bench test
  EX500A-AC1••••Durability test
- 58. Evap. Emission Family Code: YKAXC17.0A07
- 59. Evap. Emission Family Group: CV32-001
- 60. **Overall Evap D.F.** = <u>0.036</u> •Evap certification level = 0.557 g/test

### Bench DF

- 61. Test Vehicle ID: JKAEXLB14DA002384
- 62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	1.219
2	15000	1.240
3		
4		
5		
6		
7		
Interpolated Va	alues at <u>15000</u> km: =	1.240
Extrapolated V	alues at 30000 km: =	1.2674

Regular DF:	X
Modified DF:	
If different vehices specify the vehices	

#### Vehicle DF

63. Test Vehicle ID: JKAEXVA10HA000005

Bench Test D.F. = 0.027

64. Test Results.

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3547	0.515
2	5127	0.592
3	5157	0.505
4	9836	0,469
5	9866	0.801
6	15013	0.521
7		

Interpolated Values at 15000 km: = 0.5874

Extrapolated Values at 30000 km: = 0.6314

Vehicle Test D.F. = 0.044