### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER M-1-298 Relating to Certification of New Motorcycles

### KAWASAKI HEAVY INDUSTRIES, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Kawasaki Heavy Industries, Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

| Engine Family | Displacement<br>Cubic Centimeters | Class | Exhaust Emission Control Systems<br>& Special Features   |
|---------------|-----------------------------------|-------|--|
| YKAXC1.47AAD  | 1470                              | III   | Sequential Multiport Fuel Injection<br>Pulsed Secondary Air Injection<br>Oxidation Catalytic Converter |

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

| Hydrocarbon St      | tandards     | Hydrocarbons    | Carbon M   | lonoxide         |
|---------------------|--------------|-----------------|------------|------------------|
| (Corporate Average) | (Designated) | (Certification) | (Standard) | (Certification)  |
| Grams per           | Grams per    | Grams per       | Grams per  | Grams per        |
| Kilometer           | Kilometer    | Kilometer       | Kilometer  | <u>Kilometer</u> |
| 1.4                 | 0.8          | 0.6             | 12         | 6                |

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 2155 day of June 1999.

R. B. Summerfield, Chief
Mobile Source Operations Division

Page: 6

Issued: JAN 1 4 2000

Revised:

Engine Family: <u>YKAXC1.47AAD</u> E. O. # : M-1-298

## **Motorcycle Model Summary Form**

| 65.<br>Model<br>Designation | 66.<br>Worst<br>Case | 67.<br>Disp.<br>(cc) | 68.<br>Bore<br>/<br>Stroke<br>(mm) | 69. Basic Ignition Timing (degrees) | 70<br>Power<br>(kW) | 71<br>Rated<br>Speed<br>(RPM) | 72<br>Rated<br>Torque<br>(Nm) | 73.<br>Rated<br>Speed<br>(RPM) |
|-----------------------------|----------------------|----------------------|------------------------------------|-------------------------------------|---------------------|-------------------------------|-------------------------------|--------------------------------|
| VN1500-J2                   | Yes                  | 1470                 | 102X90                             | 5°/950 rpm                          | 48.5                | 5000                          | 115                           | 2500                           |
| VN1500-L1                   | -                    | 1470                 | 102X90                             | 5°/950 rpm                          | 48.5                | 5000                          | 115                           | 2500                           |
| VN1500-N1                   | -                    | 1470                 | 102X90                             | 5°/950 rpm                          | 48.5                | 5000                          | 115                           | 2500                           |

New model added

| 65.<br>Model<br>Designation | 74.<br>EIM<br>(kg) | 75.<br>Loaded<br>Vehicle<br>Weight Range<br>(kg) | 76<br>Road<br>Load<br>(nt) | 77<br>Total<br>Vehicle<br>Mass<br>(kg) | 78 Full Weight with All Factory Options (kg) | 79.<br>Trans.<br>Type | 80<br>N/V |
|-----------------------------|--------------------|--|----------------------------|--|--|-----------------------|-----------|
| VN1500-J2                   | 460                | 456~465  | 166.0                      | 322                                    | 385  | M-5                   | 26.49     |
| VN1500-L1                   | 460                | 456~465  | 166.0                      | 359                                    | 385  | M-5                   | 26.49     |
| VN1500-N1                   | 460                | 456~465  | 166.0                      | 325                                    | 385  | M-5                   | 26.49     |

E.O.#: M-1-298 Section: 7: Page: 6 Issued: APR 3 0 1999

Revised:

Engine Family: YKAXC1.47AAD

## **Motorcycle Model Summary Form**

| Model<br>Designation | Worst<br>Case | Disp.<br>(cc) | Bore / Stroke (mm) | Basic Ignition Timing (degrees) | Power<br>(kW) | Rated<br>Speed<br>(RPM) | Rated<br>Torque<br>(Nm) | Rated<br>Speed<br>(RPM) |
|----------------------|---------------|---------------|--------------------|---------------------------------|---------------|-------------------------|-------------------------|-------------------------|
| VN1500-J2            | Yes           | 1470          | 102X90             | 5°/950 rpm                      | 48.5          | 5000                    | 115                     | 2500                    |
| VN1500-L1            | -             | 1470          | 102X90             | 5°/950 rpm                      | 48.5          | 5000                    | 115                     | 2500                    |

| 65.<br>Model<br>Designation | 74.<br>EIM<br>(kg) | 75.<br>Loaded<br>Vehicle<br>Weight Range<br>(kg) | 76<br>Road<br>Load<br>(nt) | 77<br>Total<br>Vehicle<br>Mass<br>(kg) | 78 Full Weight with All Factory Options (kg) | 79.<br>Trans.<br>Type | 80<br>N/V |
|-----------------------------|--------------------|--|----------------------------|--|--|-----------------------|-----------|
| VN1500-J2                   | 460                | 460  | 166.0                      | 322                                    | 385  | M-5                   | 26.49     |
| VN1500-L1                   | 460                | 460  | 166.0                      | 342                                    | 385  | M-5                   | 26.49     |
|                             |                    |  |                            |  |  |                       |           |

E. O. #: M-1-298

0

Section: 7: Page: 1 Issued: APR 3 0 1999

Revised:

## **Motorcycle Engine Family Information Form**

|              | Certification Con<br>Jeffrey D.Shetler                | tact Person, address, pho               | ne, and fax:  |                              |
|--------------|---|---|---|------------------------------|
|              | Kawasaki Motor.<br>9950 Jeronimo R<br>Tel: 949-770-04 | s Corp., USA.<br>load, Irvine. CA 92618 | -2084<br>949-460-5602                               |                              |
| 3.           | Model Year: _20                                       | 00                                      | 10. Displacement:                                   | 1470cm <sup>3</sup>          |
|              | Process Code:   | New_<br>ction, revision, r/c, f/f. etc  | 11. Number of Cyline                                | ders: 2                      |
|              |   |   |   | ment: <u>Vee-Twin</u>        |
| 5.           | 50s Engine C  |   | 13. Cylinder Head C                                 | Configuration: SOHC          |
|              | 49s Engine C<br>Calif. Engine                         |   | 14. Type of Cooling:                                | Liquid                       |
| 5.           | Emission Contro                                       | l System: SFI+PAIR+OC                   | 2 15. Combustion Cycl                               | e: <u>4</u>                  |
| 7.           | Calif. Designated                                     | i Standard: 0.8 gm/km                   | 16. Method of Aspira                                | ation: Natural               |
| 3.           | Projected Annua                                       |   | 17. Fuel System: Fu                                 | uel Injected                 |
|              |   | 4                                       |   | rtic Converters: 1           |
|              | Parameter(s)  | Adjustable Range                        | Tamper Resistance Method<br>(or NA)                 | Method Approved              |
|              |   |   | an aluminum cap is placed over the adjusting screw. | Carry over                   |
|              |   |   |   |                              |
| Air          | AECDs In the Emis                                     | ssion Control Systems:                  |   |                              |
| 0. <i>2</i>  | AECDs In the Emis                                     | ssion Control Systems:                  | Evaporative System                                  |                              |
| O. z         |   |   | Evaporative System AECDs In System:                 |                              |
| Air<br>20. Z | aust System   | SFI, PAIR and OC                        |   | Sealed loop<br>with Canister |

Application Processed by: Joseph Jegede Date: 6/18/99 Reviewed by: Sten Hold Date: 6/21/99

E.O. #: M-1-298

Section: 7: Page: 4
Issued: APR 3 0 1999

Revised:

Engine Family: YKAXC1.47AAD

### **Motorcycle Test Information Form**

- 27. Are you carrying over test results from a previously certified family? X Yes No
  - a) If yes, indicate family name: XKAXC1.47AAD
  - b) Is the family being certified identical to the family from which the data is being carried over? No
- 28. Model Designation of Test Vehicle: VN1500-J1
- 29. Test Information Number: 99-1
- 30. Vehicle ID: JKBVNAJ13XA000007
- 31. Service Accumulation Duration: \_\_\_\_15000 \_\_\_\_(km)
- 32. Maximum Rated Power: 48.5 kW @ 5000 RPM
- 33. Displacement: 1470 cc
- 34. Certification Fuel: Indolene: 95~99 RON
- 35. Test Data Set: Test 1

- 36. Road Load: 166.0 nt at 65 kph
- 37. Inertia Mass: 460 kg
- 38. N/V: \_26.49
- 39. EVAP. Bench Test Method Approved:

Date: 2/17/87

Reference: \_EO M-1-82

- 40. Unscheduled Maintenance: \_\_\_ Yes X No
- 41. If yes, Vehicle Log provided: NA

42. Exhaust Emission Deterioration Factors:

| Harris Hall Law Hill |                           | Emissi      | on Values          |   |
|----------------------|---------------------------|-------------|--------------------|---|
| Test Number          | System Kilometers         | HC          | CO                 |   |
| 1                    | 3514                      | 054         | 5.4                |   |
| 2                    | 6012                      | 0.49        | 5.4                |   |
| 3                    | 6102                      | 0.51        | 4.8                |   |
| 4                    | 12013                     | 0.49        | 5.4                |   |
| 5                    | 12103                     | 0.32        | 4.8                |   |
| 6                    | 15028                     | 0.57        | 5.7                |   |
| 7                    | 15058                     | 0.64        | 5.4                | - |
| 8                    | 15088                     | 0.61        | 5.5                | * |
| 9                    | 15117                     | 0.37        | 4.9                | * |
| Interpolated Va      | alues at <u>15000</u> km: | HC = 0.4652 | CO = <u>5.3533</u> |   |
| Extrapolated V       | alues at <u>30000</u> km: | HC = 0.4102 | CO = <u>5.6172</u> |   |

| Regular DF                          | X |
|-------------------------------------|---|
| Modified DF                         |   |
| If different veh<br>specify vehicle |   |

\*1. This emission test was performed in order to confirm the previous EPA's approval test data which was submitted in 1999 model year certification.

- \*2. This emission test was performed in order to confirm the unit aged Punched Metal Catalyst.
- \*3. This emission test was performed in order to confirm the aged Honeycomb Catalyst.
- 4. These emission test was performed by the letter 99ARB-11 dated of February 18, 1999.

43. Emission Test Results:

| Official Test<br>Results |                 | Test 1 | Test 2 | Test 3 | Test 4 |
|--------------------------|-----------------|--------|--------|--------|--------|
| g/km                     | со              | 5.7    |        |        | /      |
| g/km                     | CO <sub>2</sub> | 157.1  |        |        |        |
| g/km                     | HC              | . 0.57 |        |        |        |
| g/test                   | Evap.           | 1.104  |        |        |        |

|    | Deterioration |
|----|---------------|
|    | Factors       |
| X) | 1.049         |
|    |               |
| X) | 1.000         |

0.000

44. Certification Levels:

| g/km   | CO    | 6     | 770 |  |
|--------|-------|-------|-----|--|
| g/km   | HC    | 0.6   |     |  |
| g/test | Evap. | 1.104 |     |  |

E.O. #: M-1-298 Section: 7: Page: 5

Section: 7: Page: 5
Issued: APR 3 0 1999

Revised:

Engine Family: YKAXC1.47AAD

## **Evaporative Emission Information**

- 45. Evaporative Family: YKAXC17.0A01
- 46. Number of Evap. Canisters: \_\_\_1\_\_
- 47. Design Working Capacity: 17.0 g
- 48. Configuration: Sealed loop
- 49. Number of Storage Areas: \_\_1\_
- 50. Fuel Reservoir Volume: 8 liters
- 51. Vent System Configuration: Sealed loop
- 52. Nominal Tank Capacity: 16 liters

- 53. Engine Displacement Class: III
- 54. Storage Medium Composition: Activated carbon
- 55. Evap. Canister Medium Volume: 400cm<sup>3</sup>
- 56. Evap. Family Sales: 1600
- 57. Engine Code: VNT50J-AC1
- 58. Evap. Emission Family Code: YKAXC17.0A01
- 59. Evap. Emission Family Group: CVK36-001
- 60. Overall Evap D.F. = 0.000

  \*Evap certification level = 1.104 g/test

#### Bench DF

- 61. Test Vehicle ID: JKBVNAA14HA000003
- 62. Test Results:

| Test Number     | System Kilometers        | Evap. Emission Values (g/test) |
|-----------------|--------------------------|--------------------------------|
| 1               | 3500                     | 0.843                          |
| 2               | 15000                    | 0.752                          |
| 3               |                          |                                |
| 4               |                          |                                |
| 5               |                          |                                |
| . 6             |                          |                                |
| 7               |                          |                                |
| Interpolated Va | lues at <u>15000</u> km: | = _0.7520                      |
| Extrapolated V  | alues at 30000 km        | : = 0.6333                     |
| Bench Test D.F. | = _0.000                 |                                |

| Regular DF:         | X      |
|---------------------|--------|
| Modified DF:        |        |
| If different vehice | cle    |
| specify the vehic   | ele ID |

#### Vehicle DF

- 63. Test Vehicle ID: JKBVNAA14HA000003
- 64. Test Results.

| Test Number      | System Kilometers           | Evap. Emission Values (g/test) |
|------------------|-----------------------------|--------------------------------|
| 1                | 3514                        | 1.012                          |
| 2                | 5124                        | 1.163                          |
| 3                | 5154                        | 1.070                          |
| 4                | 10019                       | 0.711                          |
| 5                | 10049                       | 0.821                          |
| 6                | 15013                       | 1.104                          |
| 7                |                             |                                |
| Interpolated Va  | dues at 15000 km:           | = 0.9308                       |
| Extrapolated V   | alues at <u>30000</u> km: = | = 0.8008                       |
| Vehicle Test D.l | F. = 0.000                  |                                |