

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-405  
Relating to Certification of New Heavy-Duty Motor Vehicle Engines

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED. That the following General Motors Corporation 1988 model-year diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 8,500 pounds:

<u>Engine Family</u>	<u>Displacement</u> <u>Liters (Cubic Inches)</u>		<u>Exhaust Emission Control Systems</u> <u>(Special Features)</u>
JGM06.2DAB5	6.2	(379)	Engine Modification (Diesel Injection - Prechamber)
JGM08.2EAB9	8.2	(500)	Engine Modification (Diesel Injection - Direct) (Turbocharger)
JGM08.2DAB6	8.2	(500)	<del>Electronic Injection Control</del> <i>gce</i> Engine Modification <i>gce</i> (Turbocharger) (Diesel Injection - Direct)

Engine models and codes are listed on attachments.

The following are emission standards for these engine families:

<u>Hydrocarbons</u> <u>gm/bhp-hr</u>	<u>Carbon Monoxide</u> <u>gm/bhp-hr</u>	<u>Nitrogen Oxides</u> <u>gm/bhp-hr</u>	<u>Particulates</u> <u>gm/bhp-hr</u>
1.3	15.5	6.0	0.60

The following are the certification emission values for these engine families:

<u>Engine Family</u>	<u>Hydrocarbons gm/bhp-hr</u>	<u>Carbon Monoxide gm/bhp-hr</u>	<u>Nitrogen Oxides gm/bhp-hr</u>	<u>Particulates gm/bhp-hr</u>
JGMO8.2DAB5	0.4	2.2	3.2	0.54
JGMO8.2EAB9	0.5	2.2	5.5	0.45
JGMO8.2DAB6	0.9	2.9	5.3	0.52

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this 25<sup>th</sup> day of November, 1987.

  
K. D. Drachand, Chief  
Mobile Source Division

17-JGM06.2DAB5-3A

(For CARB Use Only)

(1988)

HHDD

AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

HEAVY-DUTY DIESEL ENGINES

Manufacturer: General Motors Corporation

Executive Order No.: A-6-405

Engine Family: JGM06.2DAB5

Exhaust Emission Control System: EM,(DIP)

Liter (CID): 6.2L (379)

ENG MODEL	FUEL INJECTION PUMP MFR PART NO.	INJECTOR MFR PART NO.	MAXIMUM RATED HP AT RPM	FUEL RATE mm <sup>3</sup> /STROKE (LBS/HR)	MAXIMUM RATED TORQUE AT RPM	FUEL RATE mm <sup>3</sup> /STROKE (LBS/HR)
6.2L	NA	1 General Motors 0430211054 14045223	155 @ 3600	48.5 (78.7)	265 @ 2000	52.0 (46.0)
6.2L	NA	2 General Motors 0430211054 14045223	145 @ 3600	45.5 (74.0)	245 @ 2000	47.0 (41.7)

ISSUED: 002

REV. NO.: 003

17-JGM08.2EAB9-5A

(For CARB Use Only)

(1988)

AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

MHDD

HEAVY-DUTY DIESEL ENGINES

Manufacturer: General Motors Corporation

Executive Order No.: A-6-405

Engine Family: JGM08.2EAB9  
Liter (CID): 8.2 (500)

Exhaust Emission Control System: EM,(TC),(DID)

ENG MODEL	FUEL INJECTION PUMP MFR PART NO.	INJECTOR MFR PART NO.	MAXIMUM RATED HP AT RPM	FUEL RATE mm <sup>3</sup> /STROKE (LBS/HR)	MAXIMUM RATED TORQUE AT RPM	FUEL RATE mm <sup>3</sup> /STROKE (LBS/HR)
V8.8.2T	NA	4T75 General Motors 5226960	225 @ 2800	77.1 (95.7)	495 @ 1700	80.8 (60.9)
V8.8.2T	NA	4C59 General Motors 5226880	180 @ 2800	58.9 (73.1)	406 @ 1500	62.6 (41.6)
V8.8.2T	NA	4T70 General Motors 5226965	210 @ 2800	71.9 (89.3)	468 @ 1700	74.5 (56.2)

ISSUED: 002

REV. NO.: 003

0313T

17-JGMO8.2DAB6-7A

(For CARB Use Only)

(1988)

AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

MHDD

HEAVY-DUTY DIESEL ENGINES

Manufacturer: General Motors Corporation

Executive Order No.: A-6-405

Engine Family: JGMO8.2DAB6  
Liter (CID): 8.2 (500)

Exhaust Emission Control System: EM, (DID)

ENG MODEL	FUEL INJECTION PUMP MFR PART NO.	INJECTOR MFR PART NO.	MAXIMUM RATED HP AT RPM	FUEL RATE mm <sup>3</sup> /STROKE (LBS/HR)	MAXIMUM RATED TORQUE AT RPM	FUEL RATE mm <sup>3</sup> /STROKE (LBS/HR)
V8.8.2	NA	4C59 General Motors 5226880	175 @ 2800	57.8 (71.8)	390 @ 1200	62.7 (33.4)
V8.8.2	NA	4C59 General Motors 5226880	170 @ 2600	59.0 (68.0)	390 @ 1200	62.7 (33.4)

ISSUED: 002

REV. NO.: 003

313T