State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-4-203-3

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1999 model-year Navistar International Transportation Corporation diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GYWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family		Displacement (Cubic Inches)	Exhaust Emission Control Systems and Special Features
XNVXHO7.3ACA	7.3	(444)	Turbocharger Charge Air Cooler Engine Control Module Oxidation Catalytic Converter

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
1.3	15.5	4.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
0.1	3.8	3.7	0.09

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- Any engine which employs a defeat device shall not be covered by this Executive Order.
- 2. Within 180 days following the issuance of Executive Order A-4-203, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this $\sqrt{3}$ day of May 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

LARGE ENGINE MODEL SUMMARY

	!	8.Fuel Rate: 9.Emission Control (ibs/hr)@peak torque Device Per SAE J1930
Process Code: New Submission	Zadi	7.ruei Rate: mm/stroke@peak torque
	Manufacturer Family Name:	6.Torque @ RPM (SEA Gross)
	Manufacturer F	(lbs/hr) @ peak HP (for diesels only)
-	7. 0. 0. 0.	mm/stroke @ peak HP (for diesel only)
Vanufacturer: Navistar E.O.#A-4-203-3	3ACA_	3.BHP@RPM (SAE Gross)
	EPA Engine Family: XNVXH07.3ACA	l.Engine Code 2.Engine Model
Manufacturer:	EPA Engine Fan	1.Engine Code

DI, ECM, TA, OC TC, CAC 55.8 508@1600 85.7 103.4 250@2700

A250