State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-325-23

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

GFI CONTROL SYSTEMS, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 2000 model-year GFI Control Systems, Inc. Otto-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Dual-Fuel Liquid Propane Gas (LPG) or Gasoline

Engine Family	Engine Displacement Liters (Cubic Inches)	Exhaust Emission Control Systems and Special Features
YG9XH06.88CP	6.8 (417)	Sequential Multiport Fuel Injection Dual Heated Oxygen Sensors Three Way Catalytic Converter

Engine models and codes are listed on attachments.

The certification exhaust emission standards for this engine family in grams per brake horsepower-hour are:

Total	Carbon	Nitrogen
<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides
1.9	37.1	4.0

The certification exhaust emission values for this engine family in grams per brake horsepower-hour are: (The values in parentheses are for gasoline.)

Total	Carbon	Nitrogen
<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides
0.3 (0.1)	4.1 (2.4)	1.3 (0.5)

4

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.)

BE IT FURTHER RESOLVED: That the listed engine models comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Sections 1965.)

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

لير Executed at El Monte, California this _____ day of January 2000.

R. B. Symmerfield, Chief Mobile Source Operations Division

Antiput Lington Color 2 Exponential Antiput Color 2 Exponentia Antiput Color 2 Exponential Antiput Color 2	tõ Database	Engl	<u>le Model Si</u>	Engine Model Summary Database		ne Family	Engine Family Y69 K HOG. 880P	880P	Executive	Executive Oder A. 325-23
BGC CT/TERMERFFITE VI GFF JI 0 429 M A C-0.0250 demensione II 0 001		Model		4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel H Ibs/hr) @ p (lor diesels	1 6.Tarque & RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rale: (Ibs/hr)@peak lorque	9.Emission Control Device Per SAE J1930	
	1	GFP	310 @ 4250	NA	NA	425@3250	444mm/stroke	119 tbs/hr	TWC/2HO2S/SFI	
	i								:	
					-					
					-					
									:	
					•					
									·	
										•••

ξ. . .

,

.