GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1328 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS 2	ECS & SPECIAL FEATURES 3
	6GMXH06.0583	6.0	Gasoline	Otto	HDO	2TWC, 2HO2S(2), SFI
2006	· · · · · · · · · · · · · · · · · · ·		ENGINE N	ODELS / CODES (ated power, in hp)	
NGINE (L)	 			LQ4 / 50 (30	0)	
6.0				*		
*	l			*		
*	1					
*					San war 40 CEP R6 ah	c=Title 40, Code of Federal Regulations, Section 86.abo

=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 =liter; hp=horsepower; kw=kilowatt;

liter; hp=horsepower; kw=kilowatt;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control; DGI=direct gasoline injection; GCARB=gaseous carburetor; self-air-exidized filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control; DGI=direct gasoline injection; GCARB=gaseous carburetor; self-air-exidized filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control; DGI=direct gasoline injection; GCARB=gaseous carburetor; self-air-exidized filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control; DGI=direct gasoline injection; GCARB=gaseous carburetor; self-air-exidized filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-ECS=emission control; DGI=direct gasoline injection; GCARB=gasoline injection; GCARB=gasoline injection; GCARB=gasoline injection; GCARB=gasoline injection; GCARB=g

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of facting. (For flexible, and dual-fueled engines, the CERT values in brackets [1] are those when tested on conventional test fuel. For multi-fueled of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	NMHC		NOx		NMHC+NOx		со		PM		нсно	
							FTP	EURO	FTP	EURO	FTP	EURO
	FTP	EURO	FTP	EURO	FTP	EURO	FIF	LUNC		 	*	
				•	*	*	37.1	•	*			
TD _				 		*	*	*	*	*	•	*
EL	*	*	`	*	0.8	<u> </u>				+		*
ERT	*	•	*	•	0.6	•	5.6		 	*		*
TE.	corams per hr	* ake horsepowe	er-hour; Fi	* P=Federal Tes	t Procedure;	EURO=Euro III	European Ste	eady-State Cycle	: NTE=Not-to	o-Exceed; STD	=standard or emi late matter; HC	ssion test cap; HO=formalde

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the Option 1 federal NMHC+NOx emission standard(s) listed above pursuant to 13 CCR 1956.1 or 13 CCR 1956.8.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

day of April 2005.

Allen Lyons, Chief

Mobile Source Operations Division

Deven