

BAYTECH CORPORATION

EXECUTIVE ORDER A-330-0191 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

YEAR	2008 8BYTH08.1C12		ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
2008					PROCEDURE	CLASS	TWC, SFI, 2HO2S					
			8.1	CING	Otto	HDO						
	'ENGINE'S IDLE NS CONTROL			AD	DITIONAL IDLE EN	IISSIONS CON	ITROL 5					
	N/A				N/A							
ENGINE (L	L)			ENGINE MO	DELS / CODES (ra	ted power, in I	np)					
8.1					GM 8.1L / 1 (2		<u></u>					
* =not applic	cable; GVWR=gross	vehicle w	eight rating; 13 CCR	xyz=Title 13, California Code	of Regulations, Sect	ion xyz; 40 CFR	86.abc=Title 40, Code of Federal Regulation	ons, Section 86.abc:				
	- HOLDEDONEL . KM-KI	OWAIL, III.	-nour,				86.abc=Title 40, Code of Federal Regulation	ons, Section 86.abc;				
CNG/LN	IG=compressed/lique	efied natur	al gas; LPG =liquefie	ed petroleum gas; E85=85% e	thanol fuel; MF ≃mult		86.abc=Title 40, Code of Federal Regulation bit fuel; DF=dual fuel; FF=flexible fuel;	ns, Section 86.abc;				
CNG/LN L/M/H H ECS=em	IG=compressed/lique IDD=light/medium/he nission control system	efied natur avy heavy	-nour, ral gas; LPG=liquefie r-duty diesel; UB=urt C=three-way/oxidizir	ed petroleum gas; E85 =85% e ban bus; HDO =heavy duty Of	ethanol fuel; MF=mult to;	i fuel a.k.a. BF=	bi fuel: DF=dual fuel: FF=flexible fuel:					
CNG/LN L/M/H H ECS=en	IG=compressed/lique IDD=light/medium/he nission control syster DPF=diesel particul	efied natur avy heavy n; TWC/C ate filter:	ral gas; LPG=liquefie /-duty diesel; UB=urt DC=three-way/oxidizin PTOX=periodic tran (ed petroleum gas; E85=85% e ban bus; HDO=heavo ng catalyst; NAC=NOx adsort nyidizer; HO25/O25=heate/	ethanol fuel; MF=mult to; otion catalyst; SCR-U	i fuel a.k.a. BF=	bi fuel: DF=dual fuel: FF=flexible fuel:	WU (prefix) =warm-				
CNG/LN CNG/LN L/M/H H CCS=en up catalyst: TBI=throttle super charge	IG=compressed/lique IDD=light/medium/he nission control syste DPF=diesel particul body fuel injection; er; CAC=charge air	efied natur avy heavy m; TWC/C ate filter; SFI/MFI=s cooler: E	ral gas; LPG=liquefie	ed petroleum gas; E85=85% e ban bus; HDO=heavy duty Ol ng catalyst; NAC=NOx adsor oxidizer; HO2S/O2S=heated/ uel injection; DGI=direct gass t cas recirculation / copled E67	ethanol fuel; MF=mult to; otion catalyst; SCR-U otion catalyst; SCR-U line injection; GCAP	i fuel a.k.a. BF= I/SCR-N=select S/AFS=heated/a	bi fuel; DF=dual fuel; FF=flexible fuel; ive calalytic reduction – urea / ammonia; ir-fuel-ratio sensor (a.k.a., universal or linear	WU (prefix) =warm- oxygen sensor);				
CNG/LN CNG/LN L/M/H H ECS=em up catalyst; FBI=throttle super charge control mode	IG=compressed/liquidipple/liqu	efied natur avy heavy m; TWC/C ate filter; SFI/MFI=s cooler; E dification;	-noun, al gas; LPG=liquefie /-duty diesel; UB=urt DC=three-way/oxidizin PTOX=periodic trap or sequential/multi port f GR / EGR-C=exhaus 2 (prefix)=parallel;	ed petroleum gas; E85=85% e ban bus; HDO=heavy duty Ol ng catalyst; NAC=NOx adsor oxidizer; HO2S/O2S=heated/ uel injection; DGI=direct gast t gas recirculation / cooled E0 (2) (suffit)=in series;	ethanol fuel; MF=mult to; otion catalyst; SCR-U oxygen sensor; HAF; oline injection; GCAR R; PAIR/AIR=pulsec	i fuel a.k.a. BF= I / SCR-N=select 5/AFS=heated/a B=gaseous carb l/secondary air in	bi fuel: DF=dual fuel; FF=flexible fuel; ive catalytic reduction – urea / ammonia; ir-fuel-ratio sensor (a.k.a., universal or linear uretor; IDI/DD=indirect/direct dieset injectio ojection; SPL=smoke puff limiter; ECM/PCh	WU (prefix) =warm- roxygen sensor); nr; TC/SC=turbo/ M=engine/powertrain				
CNG/LN CNG/LN	In Cappine : Manifer : Man	efied natur avy heavy n; TWC/C ate filter; SFI/MFI=s cooler; E dification; m (cer 13	al gas; LPG=liquefie -duty diesel; UB=url DC=three-way/oxidizin PTOX=periodic trap is sequential/multi port f GR / EGR-C=exhaus 2 (prefix)=parallel; (CCR 1956 8/a/bi/k	ad petroleum gas; E85=85% s ban bus; HDO=heavy duly Ol ng catalyst; NAC=NOx adsor oxidizer; HO25/O25=heated/ idel injection; OGI=direct gas t gas recirculation / cooled E0 (2) (suffix)=in series; Vd. 30n=30 oftr NOx (per 13	ethanol fuel; MF=mult to; to; totion catalyst; SCR-U bxygen sensor; HA-U biline injection; GCAR iR; PAIR/AIR=pulsed	i fuel a.k.a. BF= / SCR-N=select /AFS=heated/a B=gaseous carb /secondary air in	bi fuel; DF=dual fuel; FF=flexible fuel; ive calalytic reduction – urea / ammonia; ir-fuel-ratio sensor (a.k.a., universal or linear	WU (prefix) =warm- roxygen sensor); n; TC/SC=turbo/ /I=engine/powertrain				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	*	*	*	*	•	+	14.4	*	0.01	*	0.01	*
FEL	0.23	*	0.32	*	0.55	*	*	*	*	*	*	*
CERT	0.20	*	0.27	*	0.47	*	5,4	*	0.003	*	0.002	*
NTE	*		*		*		*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure: EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [OTTO engines] and the incorporated 40CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of April 2008.

Annette Hebert, Chief
Mobile Source Operations Division