

BAYTECH CORPORATION

EXECUTIVE ORDER A-330-0214 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

ENGINE FAMI	Y ENGINE	FUEL TYPE 1	STANDARDS & TEST	SERVICE	ECS & SPECIAL FEATURES 3	DIAGNOSTIC 6				
		LPG	Otto	CLASS THDO	2TWC, SFI, 2HO2S	N/A				
RY ENGINE'S IDLE SIONS CONTROL 5 ADDITIONAL IDLE EMISSIONS CONTROL 5										
N/A N/A										
ENGINE MODELS / CODES (rated power, in hp)										
	GM 8.1L / 1 (332)									
horsepower; kw=kik G=compressed/lique DD=light/medium/hea ission control system DPF=diesel particula DDF=diesel particula body fuel injection; \$ ar; CAC=charge air of	watt, hr=hour; fied natural gas; LPG=lique vy heavy-duty diesel; UB=i ; TWC/OC=three-way/oxidi te filter: PTOX=periodic traj iFI/MFI=sequental/mutti pooler; EGR / EGR-C=exha	fied petroleum gas; E85=85% etl urban bus; HDO=heavy duty Otto zing catalyst: NAC=NOx adsorpt p oxidizer; HO2S/O2S=heated/or 1 fuel injection; DGI=direct gasoli ust gas recirculation / copled EGF	nanot fuel; MF=mul o; ion catalyst; SCR-t cygen sensor; HAF ne injection; GCAR	ii fuel a.k.a. BF: I / SCR-N=select S/AFS=heated/a B=gaseous cart	=bi fuel; DF=dual fuel; FF=flexible fuel; tive catalytic reduction – urea / – ammonia; sir-fuel-railio sensor (a.k.a., universal or linea buretor: DI/DDI=indirect/driect dlessel injectio	WU (prefix) ≕warm- r oxygen sensor); on: TC/SC≃turbo/				
	9BYTE08.1P ENGINE'S IDLE IS CONTROL N/A) abie; GVWR=gross horsepower; kw=kild G=compressed/inuel DD=light/medium/hea ission control system DPF=diasel particula Ddy fuel injection; S r; GAC=charge air c	BOYTEO8.1P13 8.1 SIZES (L) 9BYTEO8.1P13 8.1 ENGINE'S IDLE IS CONTROL N/A Debie; GWR=gross vehicle weight rating; 13 CO N/A Doorsepower, kw=kilowatt; hr=hour; G=compressed/liquefied natural gas; LPG=lique DD=light/medium/heavy heavy-duty diesel; UB=lission control system; TWC/OC=bree-way/oxidi DPF=diesel particulate filter; PTOX=periodic tra	SIZES (L) 9BYTE08.1P13 8.1 LPG ENGINE'S IDLE IS CONTROL N/A Debie; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code on conceptions, key-key-key-key-key-key-key-key-key-key-	BNGINE FAMILY SIZES (L) 9BYTE08.1P13 8.1 LPG Otto Otto ADDITIONAL IDLE EM N/A N ENGINE MODELS / CODES (ra GM 8.1L / 1 (3) Babie; GVWR-gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Sectors concrepower, kw=kilowatt, hr=hour; G=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanoi fuel; MF=multi DD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto; ission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-L DDF=cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O25=heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HO2S/D25-heated/oxygen sensor; HAF- DDF-cliesel particulate filter; PTOX=periodic trap oxidizer; HD2S/D25/D25-heated/oxygen sensor; HAF- DDF-cliesel particulate filter;	BNGINE FAMILY SIZES (L) 9BYTE08.1P13 8.1 LPG ADDITIONAL IDLE EMISSIONS COMMANDIAL IDLE EMISSIONS COMMAND ADDITIONAL IDLE EMISSIONS COMMANDIAL	ENGINE SIZES (L) 9BYTE08.1P13 8.1 LPG Otto HDO 2TWC, SFI, 2HO2S ADDITIONAL IDLE EMISSIONS CONTROL N/A ENGINE MODELS / CODES (rated power, in hp) GM 8.1L / 1 (332) SERVICE CLASS 2TWC, SFI, 2HO2S ADDITIONAL IDLE EMISSIONS CONTROL N/A ENGINE MODELS / CODES (rated power, in hp) GM 8.1L / 1 (332) Service CLASS 2TWC, SFI, 2HO2S ADDITIONAL IDLE EMISSIONS CONTROL N/A ENGINE MODELS / CODES (rated power, in hp) GM 8.1L / 1 (332) Service CLASS 2TWC, SFI, 2HO2S ADDITIONAL IDLE EMISSIONS CONTROL Service CLASS ADDITIONAL IDLE EMISSIONS CONTROL SERVICE CLASS 4 TEST PROCEDURE CLASS 2TWC, SFI, 2HO2S ADDITIONAL IDLE EMISSIONS CONTROL SERVICE CLASS 4 TEST PROCEDURE CLASS 4 TEST PROCEDURE CLASS 4 TEST PROCEDURE CLASS 4 TEST CLASS 4 TEST PROCEDURE CLASS 4 TEST CLASS 4 TEST CLASS 4 TEST PROCEDURE CLASS 4 TEST CLASS				

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		со		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	*	*	*	*	*	*	14.4	*	0.01	*	0.01	*
FEL	0.15	*	0.32	*	*	*	*	*		*	*	*
CERT	0.13	*	0.27	*	+	*	4.1	*	0.001	*	0.001	+
NTE		* ,		*		*		*		*	•	
									<u> </u>		<u> </u>	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of March 2009.

Annette Hebert, Chief

Mobile Source Operations Division