	Californ	ie Environen	ental Protection	Agency	
フ를	AIR	RESO	URCES	BOAR	D

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL			SINE	FUEL TYPE	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES	DIAGNOSTIC 6
TEAR		3126	3 (L)		PROCEDURE	CLASS 1	DDI, TC, CAC, ECM, EGR,	FMD
2009	9VPTH16.1	H01 16	5.1	Diesel	Diesel	HHDD	OC,PTOX	
PRIMARY	SCONTROL			ADDI	TIONAL IDLE EN	ISSIONS CO	NTROL ⁵	
	30g				N	/A.		
ENGINE (L)			ENGINE MODE	LS / CODES (ra	ted power, in	hp)	
16.1				See attachmen	t for engine m	odels and ra	atings	
* =not appl	cable; GVWR=gros	s vehicle weight ratin	ng; 13 CC	R xyz=Title 13, California Code o	f Regulations, Sect	ion xyz; 40 CF	R 86.abc=Title 40, Code of Federal Regulation	ns, Section 86.abc;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel line(tin); SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct dises I injection; TC/SC=turbof super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr N0x (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD=on-board diagnostic system (13 CCR 1971.1);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in	NN	HC	N	Ox	NMH	C+NOx	C	:0	P	M	н	Ю
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	*	*	*	*
FEL	*	*	1.16	1.16	1.3	1.3	*	*	0.00	0.00	*	*
CERT	0.04	0.03	1.02	1.06	1.06	1.1	*	*	0.002	0.000	*	*
NTE	0.	21	1.	74	2	.0	19	9.4	0.	02		*

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

This Executive Order hereby cancels and replaces Executive Order A-242-0052 dated, December 23, 2008.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

the day of December 2009. Executed at El Monte, California on this

ren Annette Hebert, Chief Mobile Source Operations Division

Altachanent . A-242-0052-1

Engine Model Summary Template

vlime Family	1 Envine Code	2 Envine Model	3.8HP@RPM	4.Fuel Rate: mm/struke 🕲 peak HP //or rissed onb/	5.Fuel Rate: (Iba/In) (2) peak HP (for disents priv)	6.Torque 🕲 RPM (SFA Gross)	7.Fuel Rate: mm/siroke@peak lorgue	8.Fuel Rale; (bs/hr)@peak lorqu	9.Entlasion Control Device Per SAE J1930	د ۱
averties and	A / A	D16F - 600	524 @ 2000	289.8	198.0	2091 @ 1200	400.0	158:5	EM, EC, TC, CAC, DI, EGR, DPF (rac) C C
OVPTH16 1H01	N/A	D16F - 550	524 @ 2000	299.8	198.0	1887 @ 1100	370.3	134.5	EM, EC, TC, CAC, DI, EGR, DPF	4
WPTH16 1H01	N/A	D16F - 535	510 @ 2000	284.7	188.0	1867 @ 1100	370.3	134.5	EM, EC, TC, CAC, DI, EGR, DPF	
9VPTH16,1H01	N/A	D16F - 500	446 @ 2000	261.2	172.5	1887 @ 1100	370.3	134.5	EM.EC.TC.CAC,DI,EGR,DPF	<i>L</i> J
9VPTH16_1H01	N/A	D16F - 500	446 @ 2000	261.2	172.5	1887 @ 1100	370.3	134.5	EM, EC, TC, CAC, DI, EGR, DPF	<u> </u>
9VPTH16,1H01	N/A	D16F - 500	446 @ 2000	261.2	172.5	1785 @ 1100	351.0	127.5	EM,EC,TC,CAC,DI,EGR,DPF	1
9VPTH16 1H01	N/A	D16F - 500	446 @ 2000	261.2	172.5	1683 @ 1100	329.0	119.5	EM, EC, TC, CAC, DI, EGR, DPF	
9VPTH16 1H01	N/A	D16F - 450	408 @ 2000	233.2	154.0	. 1785 @ 1100	351.0	127.5	EM,EC,TC,CAC,DI,EGR,DPF	8
avertife thus	N/A	D16F - 450	408 @ 2000	233.2	154.0	1785 @ 1100	351.0	127.5	EM, EC, TC, CAC, DI, EGR, DPF	
avertification	N/A	D16F - 450	408 @ 2000	233.2	154.0	1683 @ 1100	329.0	119.5	EM.EC.TC.CAC.DI.EGR.DPF	17
10H161H01	N/A	MP10 - 605C	524 @ 2000	299.8	198.0	2091 @ 1200	400.0	158.5	EM.EC.TC.CAC,DI,EGR,DPF	Å
9VPTH16 1H01	N/A	MP10 - 565C	524 @ 2000	299.8	196.0	1887 @ 1100	370.3	134.5	EM.EC.TC,CAC,DI,EGR,DPF	
OVPTH16 1H01	N/A	MP10 - 515C	466 @ 2000	261.2	172.5	1867 @ 1100	370.3	134.5	EM, EC, TC, CAC, DI, EGR, DPF	A