California Environmental Protection Agency		EXECUTIVE ORDER A-021-0578
	CUMMINS INC.	New On-Road Heavy-Duty Engines
CE Air Resources Board		Page 1 of 2 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAM		ENGINE	FUEL TYPE	STANDARDS & TEST	INTENDED SERVICĘ	ECS & SPECIAL FEATURES	DIAGNOSTIC		
		SIZES (L)		PROCEDURE	CLASS	DDI, TC, CAC, ECM, EGR, OC,			
2013	DCEXH0912XA	T 14.9	Diesel	Diesel	HHDD	PTOX, SCR-U			
PRIMARY EMISSIO	RIMARY ENGINE'S IDLE ADDITIONAL IDLE EMISSIONS CONTROL								
	30g N/A								
ENGINE (	ENGINE MODELS / CODES (rated power, in hp)								
14.9	9 See attachment for engine models and ratings								
*				*					
*				*					
*									
and applicable: GWR=arross vehicle weight rating: 13 CCR xyz=Title 13 California Code of Regulations. Section xyz: 40 CFR 86 abc=Title 40. Gode of Federal Regulations. Section 86 abc:									

L=liter; hp=horsepower; kw=kilowatt; hr=hour;

CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

2 L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;

3 ECS-emission control system; TWC/OC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction – urea / – ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburefor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in senies;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS = internal combustion auxiliary power system; ALT=alternative method er 13 CCR 1956.8(a)(6)(D); Exempte-exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system (13 CCR 1971); OBD(F) / (P) / (\$)=full / partial / partial with a fine / on-board diagnostic;);

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in NMHC		NOx		NMHC+NOx		CO		PM		нсно		
g/bhp-hr	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	0.20	0.20	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	0.35	0.35	*	*	*	*	*	*	*	*
CERT	0.01	0.002	0.22	0.12	*	*	1.1	0.6	0.001	0.001	*	*
NTE	0.	21	0	.52		*	19	9.4	0	.02		*

g/bhp-hr=grams per brake horsepower-hour, FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitroge CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde; (Rev.: 2007-02-(Rev.: 2007-02-26) CO=carbon monoxide; PM=particulate matter;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified in accordance with 13 CCR Section 1971.1(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the heavy-duty on-board diagnostic (HD OBD) system of the listed engine models has been determined to have five deficiencies. The listed engine models are approved subject to the manufacturer paying a fine of \$75 per engine for the third through fifth deficiencies in the listed engine family that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of engines produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2013 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all engines covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per engine pursuant to HSC Section 43154.

California Environmental Protection Agency		EXECUTIVE ORDER A-021-0578
<b>OB</b> Air Resources Board	CUMMINS INC.	New On-Road Heavy-Duty Engines Page 2 of 2 Pages

**BE IT FURTHER RESOLVED:** Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Oct. 12, 2011, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

**BE IT FURTHER RESOLVED:** For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of October 2012.

Annette Hebert, Chief

Mobile Source Operations Division

9-27-2012 Fo#: A-021-0578 Attachment: Page log 1

## Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	4.Fuel Rate: 5.Fuel Rate: /stroke @ peak HP (lbs/hr) @ peak HP (for diesel only) (for diesels only)		7.Fuel Rate: mm/st <b>roke@peak</b> torque	8.Fuel Rate: (Ibs/hr)@peak torque	9.Emission Control Device Per SAE J1930
CEXH0912XAT	3937;FR11085	ISX15 450ST	461@1698	264	151	1750@1000	319	108	SCRC, PTOX, P
CEXH0912XAT	3937;FR11084	ISX15 450ST	461@1698	264	151	1650@1000	299	101	SCRC, PTOX, C
CEXH0912XAT	3937;FR11083	ISX15 450	461@1698	264	151	1650@1000	299	101	SCRO PTOX PC
CEXH0912XAT	3937;FR11082	ISX15 450	461@1698	264	151	155 <b>0@</b> 1000	281	95	SCRC, PTOX, PC
CEXH0912XAT	3937;FR11081	ISX15 425ST	436@1698	248	142	1750@1000	319	108	SCRC, POX, PC
CEXH0912XAT	3937;FR11080	ISX15 425ST	436@1698	248	142	1650@1000	299	101	SCRC, PTOX, PC
CEXH0912XAT	3937;FR11079	ISX15 425	436@1698	248	142	1650@1000	299	101	SCRC, PTOX, PC
CEXH0912XAT	3937;FR11078	ISX15 400ST	410@1698	232	133	1750@1000	319	108	SCRC, PTOX, PC
CEXH0912XAT	3937;FR11077	ISX15 400ST	410@1698	232	133	1650@1000	299	101	SCRO, PTOX, P
CEXH0912XAT	3937;FR11076	ISX15 400	410@1698	232	133	1450@1000	261	88	SCRC, PTOX, PC

ECM PIOX EGR SCR-4, OC, TC, DOJ, CA