⊘ Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						ENG	INE DESCRIPT	ION				
MANUFACTURER		EXECUTIVE ORDER YEAR A-344-0039-1 2013		ENGINE FAMILY		ENGINE SIZES (L)	FUEL TYPE 1	STANDAR & TEST PROCEDU	CLASS?	ECS & SPECIAL FEATURES 3 TWC, SFI, 2AFS, HO2S	OBD COMPLIANCE 4	
ROUSH INDUSTRIES INC.	A-344-0			DRIIE06	.8BW5 6.8		LPG	Otto	HDO			
Gasoline, LPG or	Alcohol \	/ehicles	Only	AMA S	Herr	4.184.4	增低 起源	VEHICLE D	ESCRIPTION		Hajaraja Petr	
EVAPORATIVE		FUEL TANK CAPACITY		VEHICLE MODEL	VEHICLE MAKE & MODELS			ENGINE (L)	ENGINE MODELS / CODES			
FAMILY	UL (K)	(galions)		YEAR	V 2.111	OCE MAKE & MODELS		LITORIL (C)	(rated power, in hp)			
ERIIF0265LPG	150	67.5	, 100	2014	BlueBird Vision School Bus			6.8	BlueBird Vision School Bus / DDF618BR500, DDF618BR510, DDF61HBR500, DDF61HBR510 (362 for all codes)			

86.abc; L=liter; K=1000 miles; hp=horsepower; kw=kilowatt;

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	NMHC		NOx		NMHC+NOx		СО		PM		нсно		
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	
STD	0.14	*	0.20	*	*	•	14.4	*	0.01	•	0.01	•	
FEL	T +	•	•	*	•	•	•	*	•	•	•	•	
CERT	0.07	•	0.08	•	•	•	2.2	•	0.000	•	0.000	•	
NTE		•		•		•		•		•		•	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission test cap, FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971 (engine manufacturer diagnostic), 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks]. (The braces { } are for gasoline, LPG or alcohol fueled vehicles only. The brackets [] are for gasoline or alcohol fueled vehicles only.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-344-0041 dated January 10, 2013.

Executed at El Monte, California on this

day of April 2013.

Annette Hébert, Chief

Mobile Source Operations Division

^{| 26} abc; L=liter, K=1000 miles; hp=horsepower, kw=kilowatt; | CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; L/M/H HDD=light/medium/heavy heavy-duty diesei; UB=urban bus; HDO=heavy duty Otto; | ECS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBi=throttle body fuel injection; SFI/MF1sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbouper charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series; | EMD=engine manufacturer diagnostic system; OBD(F) / (P) / (\$)=full / partial / partial with fine / on-board diagnostic; | (2012-08-20)