

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-134
Relating to Certification of New Motor Vehicles

MUSKATEER MFG. CO.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102, and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That Muskateer Mfg. Co. exhaust emission control systems for 1977 model-year light duty trucks are certified for the engine family described below:

Engine Family: Toyota 20R (TC)
Engine: 133.6 CID
Transmission: 4-speed manual
Exhaust Emission Control Systems: Air Injection, Exhaust Gas
Recirculation, Engine Modification,
Oxidation Catalyst

Model: Muskeet

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1977 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
Toyota 20R (TC)	0.3	8	1.4

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 18th day of September, 1977.

G. C. Hass by *D. M. Mack*

G. C. Hass, Chief
Vehicle Emissions Control Division

Passenger Cars

Light-Duty Trucks

Manufacturer Muskateer Mfg. Co. Executive Order No. A-134 Page 1

Engine Family Toyota 20 R(TC) Engine (CID) 133.6 Engine Code

Emission Control System AI-EGR-EM-OC +10%(A/C) Yes No

Vehicle Models (If Coded see attachment)	Trans	Inertia Weight	Distributor	Fuel System	EGR System	Tune-Up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
			Type Mfgr. Part Number	Type Mfgr. Part Number	Part No. Service*	
Muskeet	M-4	3500	Nippondenso 19100- 38011	Aisan Kogyo 21100- 38160	25620- 38120 No Service.	(1) 8°BTDC@800RPM in neutral; vacuum line remain connected to distributor. (2) Lean Drop idle (See attached sheet) (3) 800 RPM in neutral

Comments
Shift speed (1 to 2) 10 mph, (2 to 3) 20 mph, (3 to 4) 30 mph, (4 to 5) 40 mph
Axle ratio: 4.111

Date of Issue 083077.

Abbreviations

Distributor
C-Centrifugal Advance
V-Vacuum Advance
VR-Vacuum Retard
TI - Transistorized Ignition
EI-Electronic Ignition
Fuel System
EFI, FI
nV-nVenturi Carburetor

Exhaust Emission Control System
AI-Air Injection
CAI-Catalyst Air Injection
EFI-Electronic Fuel Injection
EGR-Exhaust Gas Recirculation
EM-Engine Modification
EFE-Early Fuel Evaporation
ESAC-Electronic Spark Advance
Control

OC-Oxidation Catalyst
PAI-Pulse Air Injection
RC-Reduction Catalyst
TR-Thermal Reactor
TWC-Three Way Catalyst
λ-Air Fuel Ratio Sensor
*Service
I-Inspect, repair/replace