

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-17-43
Relating to Certification of New Motor Vehicles

AMERICAN MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That American Motors Corporation exhaust emission control systems are certified as described below for 1979 model-year gasoline-powered passenger cars:

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
I-C	258	Exhaust Gas Recirculation Air Injection Oxidation Catalyst

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
I-C	0.23	5.7	1.5


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 9 day of August, 1978.



G. C. Hass, Chief
Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer American Motors Executive Order No. A-17-43 Page 1

Engine Family I-C Engine (CID) 258

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
EI-Electronic Ignition
ESAC
VA-Vacuum Advance
VR-Vacuum Retard

Fuel System

EFI, MFI
nV-nVenturi Carburetor
VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection
CCAV-Comb. Chamber Air Valve
EFI-Electronic Fuel Injection
EGR-Exhaust Gas Recirculation
EM-Engine Modification

ESAC-Electronic Spark Advance
Control

MFI-Mechanical Fuel Injection

OC-Oxidation Catalyst
PAI-Pulse Air Injection
TC-Turbo Charged
TR-Thermal Reactor
TWC-Three Way Catalyst
(Feedback Control)
WOC-Warm-up Oxidation
Catalyst

Vehicle Model

Concord Sedan
Concord Wagon
Spirit Sedan
Pacer Sedan
Spirit Coupe
Pacer Wagon

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O. #A 17-43

Passenger Cars Light-Duty Trucks Medium-Duty Vehicles

Manufacturer American Motors Corporation

Page 1A

Engine Family I-C Engine (CID) 258

Engine Code KAC-3C-1

Emission Control System EGR, AI, OC, WOC + 10% (A/C)

Yes No

Eng. Code	Vehicle Models (If Coded see attachment)	Trans.	Inertia Weight Class (Axle Ratio)*	Ign. Sys. Control Parameters EI, CA, VA	Fuel System Type: 1-1V	EGR Valve	Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
KAC-3C-1	Concord Sedan Concord Wagon Spirit Sedan Pacer Sedan Spirit Coupe Pacer Wagon	A-3	3500	Motorcraft D8FE- 12127-EA AM Part No. 3232434	Carter 7318 AM Part No. SF3233878	G-61393 AM Part No. 3230261	1) 8 + 20 BTDC @ 700 RPM (D). Disconnect dist. vacuum hose and plug. 2) 25 RPM lean drop. 3) 700 + 100 RPM in drive Make adjustments with engine at normal operating temperature, air cleaner on, air conditioning off.

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class: See AMC 1979 Vol. 1, Sec. 10, Pg. 34 for HP settings.

*Axle ratio is that of medium duty certification vehicle.

Date of Issue -

Pacer Wagon added per running change No. 79-1