

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-40-5  
Relating to Certification of New Motor Vehicles

FERRARI spa SEFAC

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43100, 43102, 43103, and 43835; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That Ferrari spa Sefac exhaust emission control systems are certified as described below for 1979 model-year gasoline-powered passenger cars.

<u>Engine Family</u>	<u>Displacement Cubic Inches</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
F106AE	178.6	Air Injection Insulated Exhaust Manifold Oxidation Catalyst

Vehicle Models, Transmissions, Engine Codes and Evaporative Emission Control Families as listed on attachments.

The following are the certification emission values to be listed on the window decal required by California Assembly-Line Test Procedures for 1979 model-year vehicles:

<u>Engine Family</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
F106AE	0.35	3.0	1.1

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles except Motorcycles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Moto Vehicles and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 26<sup>th</sup> day of March, 1979.

*G. C. Hass by [Signature]*

G. C. Hass, Chief  
Vehicle Emissions Control Division

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Ferrari Executive Order No. A-40-5 Page 1

Engine Family F 106 AE Engine (CID) 178.61

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance  
 EI-Electronic Ignition  
 ESAC  
 VA-Vacuum Advance  
 VR-Vacuum Retard

Fuel System

EFI, MFI  
 nV-nVenturi Carburetor  
 VV-Variable Venturi

Exhaust Emissions Control System

AI-Air Injection  
 CCAV-Comb. Chamber Air Valve  
 EFI-Electronic Fuel Injection  
 EGR-Exhaust Gas Recirculation  
 EM-Engine Modification

ESAC-Electronic Spark Advance  
 Control  
 MFI-Mechanical Fuel Injection

OC-Oxidation Catalyst  
 PAI-Pulse Air Injection  
 TC-Turbo Charged  
 TR-Thermal Reactor  
 TWC-Three Way Catalyst  
 (Feedback Control)  
 WOC-Warm-up Oxidation  
 Catalyst

Engine Family

F 106 AE

Vehicle Model

Ferrari 308GTB  
 Ferrari 308GTS  
 Dino 308GT4

1979 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O. #A 40-5

Passenger Cars

Light-Duty Trucks

Medium-Duty Vehicles

Manufacturer Ferrari

Page 2

Engine Family F 106 AE Engine (CID) 178.61

Engine Code \_\_\_\_\_

Emission Control System AI, Insulated Exhaust Manifold + 10% (A/C)

Yes  No \_\_\_\_\_

Eng. Code	Vehicle Models (If Coded see attachment)	Trans.	Inertia Weight Class (Axle Ratio)*	Ign. Sys. Type 2-C Mfgr. Part Number	Fuel System Type 4-2V Mfgr. Part Number	EGR Valve Part No. Service	Tune-up Specification (1) Basic Timing (2) Idle Mixture (3) Idle Speed
K02 M	1C16.ACL Ferrari 308GTB Ferrari 308GTS Dino 308GT4	5M	3500	Marelli S159B Dual-points	Weber 40DCNF 72/73/74/75	None	1) 3° + 2° ATDC @ 1000 RPM 2) 1% CO w/air injection (MAXIMUM) 3) 1000 ± 200 RPM

Comments. See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model, equipment and inertia weight class.

\*Axle ratio is that of medium duty certification vehicle.

Date of Issue -