

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-17-104
Relating to Certification of New Motor Vehicles

AMERICAN MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year American Motors Corporation emission control systems are certified as described below for gasoline-powered passenger cars:

<u>Engine Family</u>	<u>Displacement Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
JAM3.OV5LYEX	3.0 (182)	Exhaust Gas Recirculation Heated Oxygen Sensor Three-Way Catalyst (Electronic Port Fuel Injection)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per mile</u>
0.39	7.0	0.7

The following are the certification emission values for this engine family:

<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0.21	1.2	0.3

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 11th day of August, 1987.


K. D. Drachand, Chief
Mobile Source Division

1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer American Motors Corporation Engine Family JAM 3.0 V5 LY EX
 Evaporative Family JV-3.0J-1P Engine Type V6
 Engine Liters (CID) 3.0 (182)

ABBREVIATIONS:

Ignition System

CA - Centrifugal Advance
 ECU - Electronic Control Unit
 EI - Electronic Ignition
 ESAC - Electronic Spark Advance Control
 VA - Vacuum Advance
 VR - Vacuum Retard

Fuel System

CFI, CL, DID, DIP, EFI, MFI
 nV - nVenturi Carburetor

Exhaust Emissions Control System

AIP - Air Injection-Pump
 AIV - Air Injection-Valve
 DBC - Dual Bed Catalyst
 EGR - Exhaust Gas Recirculation
 EIC - Electronic Injection Control
 EM - Engine Modification
 OC - Oxidation Catalyst
 OS - Oxygen Sensor
 HOS - Heated Oxygen Sensor
 SPL - Smoke Puff Limiter or
 Throttle Delay
 TOC - Trap Oxidizer, Continual
 TOP - Trap Oxidizer, Periodical
 TWC - Three-Way Catalyst
 WUOC - Warm-Up Oxidation Catalyst
 WUTWC - Warm-Up Three-Way Catalyst

VEHICLE MODELS:

55 = Premier 4-Door Sedan

Special Features

CCV - Combustion Chamber Valve
 CFI - Central Fuel Injection
 DID - Diesel Injection-Direct
 DIP - Diesel Injection-Prechamber
 EFI - Electronic Fuel Injection
 IC - Intercooler or Aftercooler
 MFI - Mechanical Fuel Injection
 OBD - On-Board Diagnostics
 TC - Turbocharged

ENGINE: FRONT X MID _____ REAR _____

DRIVE: FWD X RWD _____ 4WD FULL TIME _____ 4WD PART TIME _____

1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars X Light-Duty Trucks Medium-Duty Vehicles Gas X Diesel
 Manufacturer American Motors Corporation Engine Family JAM3.OV5LYEX
 Liter (CID) 182 (3.0) Engine Type V6
 Emission Control System
 (Special Features) EGR + HDS + TWC (EFI)

Engine Code	Vehicle Models (If Coded See Attachment)(Hp)	Trans Type	Equiv. Test Weight	Ign. System/ECU Part No.	Fuel System CL, EFI Part No.	EGR Valve Part No.	Catalyst Part No.
5A1	55	A4	3250	*8933004582	280.150.126	8933004082	25104419 25101460 949932
5A2	55		3250	* 5234321			
				**5234633			
				+5234641			
				++4605001			
				+++5234751			
				+++5234642			

Comments: _____

(See Page 1 for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.)

Date of Issue: _____
 +-REVISED 06-19-89: FF30. SERVICE REPLACEMENT ECU.
 +++REVISED 11-27-89: FF34. SERVICE REPLACEMENT ECU.

Revisions: 6-13-88: FIELD FIX 16. PARTS CONSOLIDATION. 5356g/2
 **9-08-88: FIELD FIX 24. PARTS CONSOLIDATION.
 +9-19-88: Field Fix 25. Release for Service a New ECU for Improved Fil Radio Reception.

1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEETPassenger Cars X Light-Duty Trucks Medium-Duty Vehicles Gas X Diesel Manufacturer American Motors Corporation Engine Family JAM3.0V5LYEXLiter (CID) 182 (3.0) Engine Type V6Emission Control System
(Special Features) EGR + HOS + TWC (EFI)

Engine Code	Vehicle Models (If Coded See Attachment) (Hp)	Trans Type	Equiv. Test Weight	Ign. System/ECU ECU, ESAC Part No.	Fuel System CL, EFI Part No.	EGR Valve Part No.	Catalyst Part No.
5A1	55	A4	3250	8933004582	280.150.126	8933004082	25104419 25101460 949932
5A2	55		3250				
5A3	55		3250	8933004641			
5A4	55		3250				
5A5	55		3250	8933004686			
5A6	55		3250				

Comments: Codes 5A3 and 5A4 added by Running Change 88BV3.0-01. Codes 5A5 and 5A6 added by Running Change 88BV3.0-02.

(See Page 1 for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.)

Date of Issue: _____

Revisions: _____

5356g/6

Engine
Family: JAM 3.0 V5 LY EX

1988 VEHICLE WEIGHTS AND ROADLOAD HORSEPOWER
APRIL 29, 1987

VEHICLE	VEHMT3.8					TIRES SHOWN Standard tire listed 1st Optional tires also listed						ROADLOAD HORSEPOWER & COASTDOWN TIMES			
	TOTAL WT.	AXLE WT.	TEST WT.	ENG	TRANS	SIZE MODEL		PRESSURE		(%) USAGE	A/C (SEC.)	HP.	NON A/C (SEC.)	HP.	
								FR	RR						
PREMIER SS 4-DOOR	3883	1953	3258	3.0L	A4	P185/75R14	XA4	38	38	18%	16.36	6.2			
						P185/75R14	INVECTA			5%	16.81	6.3			
						P195/78R14	XA4			55%	17.25	5.9			
						P195/78R14	INVECTA			5%	16.54	6.3			
						P285/78R14	GT4			28%	15.29	5.2			
						P285/78R14	EPX			5%	15.39	5.1			
	2963	1987					P185/75R14	XA4	38	38	18%			17.24	5.6
							P185/75R14	INVECTA			5%			17.71	5.7
							P195/78R14	XA4			55%			18.87	5.4
							P195/78R14	INVECTA			5%			17.45	5.7
						P285/78R14	GT4			28%			15.93	4.7	
						P285/78R14	EPX			5%			16.84	4.6	