## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-22-40 Relating to Certification of New Motor Vehicles

## SAAB-SCANIA AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Saab-Scania AB exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

Engine Family		placement (Cubic Inches)	Exhaust Emission Control Systems (Special Features)
JSA2.OV5FTB3	2.0	(121.1)	Heated Oxygen Sensor Three-Way Catalyst (Electronic Port Fuel Injection) (Turbocharger) (Intercooler)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per mile
0.41	7.0	0.7

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per Mile
0.22	2.1	0.5

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seg.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 27th day of August, 1987.

K. D. Drachand, Chief Mobile Source Division

## 1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Р	ane	1

, <u>34</u>		_Page 1
nufacturer Saab-Scania AB	Engine Family JSA2.0V5F	Page 17-21
Evaporative Family <u>J-900-4</u>	Engine Type S.I. 16-valve	
	Liters (CID) 2.0L (121.1 C	(10)
ABBREVIATIONS		
Ignition System	Exhaust Emissions Control System	Special Features
CA-Centrifugal Advance ECU-Electronic Control Unit EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard	AIP-Air Injection-Pump AIV-Air Injection-Valve DBC-Dual Bed Catalyst EGR-Exhaust Gas Recirculation EIC-Electronic Injection Control EM-Engine Modification OC-Oxidation Catalyst OS-Oxygen Sensor HOS-Heated Oxygen Sensor SPL-Smoke Puff Limiter or Throttle Delay TOC-Trap Oxidizer, Continual TOP-Trap Oxidizer, Periodical	CCV-Combustion Chamber Valve CFI-Central Fuel Injection or Throttle Body Injection DID-Diesel Injection- Direct DIP-Diesel Injection- Prechamber EFI-Electronic Fuel
21 System  CFI, CL, DID, DIP, EFI, MFI  nV-nVenturi Carburetor	TWC-Three-Way Catalyst WUOC-Warm-Up Oxidation Catalyst WUTWC-Warm-Up Three-Way Catalyt	Injection IC-Intercooler or Aftercooler MFI-Mechanical Fuel Injection OBD-On-8oard Diagnostics TC-Turbocharger
VEHICLE MODELS: Saab 900 Turbo Saab 900 Turbo SPG		
Saab 900 Turbo Convertible		
	•	-
you Frank X	·	
And the Front X and Aid	,	
_ Drive: FWDX RWD	4WD Full Time 4WD Part	Time

19\_88 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O. # A-22-40		E.O.	#	A -	2.2	_	4	C
----------------	--	------	---	-----	-----	---	---	---

· E.	s <u>xx</u> Light-Du						
anufacturer	Saab-Scania AB			Engine Fa	amily USAZ.OV	3F1B3	-
iter (CID) _	2.0 (121.1)		<del>-</del>	Eng.	Type S.I. 16-\	/alve 4-Cyl.	In-Line
mission Cont	rol Sys. (Specia	al Featu	res)	rwc, HOS (EFI,	TC, IC)		
Engine Code	Vehicle Models (If Coded see Attachment) (HP)	Trans. Type	Equiv. Test Weight	(ECU)	Fuel System Part No.	EGR Valve	Catalyst Part No.
202TM5AC	900T-3CKL 900T-SPG-3CKL 900T Convertible  900T-3CKL 900T Convertible	M5 M5 M5	3250 3250 3250		Air Mass Meter Saab Pt. No93 75 643 Bosch Pt. No.	Not Applicable	75 33 540 75 33 805 (Alternat

Please refer to Managed and the limit for correct dyno test HP settings based on model at ipment. If two test weights are listed, the lower weight will be used for testing.

Add 10% to dyno test Hp for air conditioning usage.

Date of Issue PART NUMBER UPDATE