(Page 1 of 2)

## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-259-9 Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Suzuki Motor Co., Ltd. exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

Engine Family		splacement (Cubic Inches)	Exhaust Emission Control System (Special Features)		
JSK1.3T2FFC7	1.3	(81)	Exhaust Gas Recirculation Oxygen Sensor Three-Way Catalyst		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per mile
0.41	9.0	1.0

The following are the certification emission values for this engine family:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides
Grams per Mile	Grams per Mile	Grams per Mile
0.13	2.4	0.3

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

day of August, 1987.

K. D. Drachand, Chief Mobile Source Division

## 1988 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Page 1

Manufacturer SUZUKI M	OTOR CO., LTD	Engine Family_	JSK1.3T2FFC7
Evaporative Family	EV2	Engine Type	L4
		Liters (CID)	1.3 (81)
ABBREVIATIONS			
Tanihina Guahan			
Ignition System	Exhaust Emission	s Control System	Special Features
CA-Centrifugal Advance ECU-Electronic Control Unit EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard	EM-Engine Modifi OC-Oxidation Cat OS-Oxygen Sensor HOS-Heated Oxyge SPL-Smoke Puff L Throttle Delay TOC-Trap Oxidize TOP-Trap Oxidize	n-Valve alyst Recirculation njection Control cation alyst n Sensor imiter or r, Continual r, Periodical	CCV-Combustion Chamber Valve CFI-Central Fuel Injection or Throttle Body Injection DID-Diesel Injection- Direct DIP-Diesel Injection- Prechamber EFI-Electronic
Euel System	TWC-Three-Way Ca WUOC-Warm-Up Oxi WUTWC-Warm-Up Th	dation Catalyst	Fuel Injection IC-Intercooler
OFI, CL, DID, DIP, EFI, MFI	worke harm op in	ree may eachtige	or Aftercooler MFI-Mednanical Fuel Injection OBD-On-Board Diagnostics TC-Turbocharger
VEHICLE MODELS:			
SAMURAI CO			
SAMURAI HA	RDTOP		

Engine:	Front_	<u> </u>	Mid	Rear					
Drive:	FWD		RWD	4WD Full Time	4WD	Part	Time	Х	

EOF .. K

E.O.# A-259-9

## 1988 AIR RESOURCES BOARD SUPPLIMENTAL DATA SHEET

Page Passenger cars\_\_\_ Light Duty Trucks\_\_\_ Medium Duty Trucks\_\_\_ Gas\_x Diesel\_

Manufacturer SUZUKI MOTOR CO., LTD Engine Family <u>JSK1.3T2FFC7</u>

Liter (CID) \_\_\_\_1.3 (81)\_

Eng.Type L3

Emission Control Sys. (Special Features) <u>CL+TWC+EGR</u>

Engine Code	Vehicle Models (If Coded see	Trans.	Equiv. Test	Ign.System	Fuel System	EGR Valve	Label Ident.
	attachment) (HP)		Weight	Part No.	Part No.	Part No.	Part No.
FA	SAMURAI CONVERTIBLE (13.0) SAMURAI HARD TOP (13.0)	м5	2,375	Spark plugs: 09482-00155 09482-00167 Distributor: 33100-83031 (33100-83021)	Fuel pump: 15100-83010 (83010) Carburetor: 13200-83150 (DFB306-832B)	EGR valve: 18111-83000 (K5T54775)	83351
(# on s	             		(	ECM: 33920-83021 33920-83021) 33920-83022 b 33920-83022)	y 88LDT-RC1		

Comments: See page one for abbreviations and evaporative emission family identification

> Please refer to manufacturer's HP list for correct dyno test HP settings based on model and quipment. If two weights are listed, the lower weight will be used for testing.

\*Add 10% to dyno test HP for air conditioning usage.

Date of issue - 03AUG87

revised: 12AUG87, 22OCT87(88LDT-RC1)