E.O. A-14-124-1

(Page 1 of 2)

EXECUTIVE ORDER A-14-124 Relating to Certification of New Motor Vehicles

## TOYOTA MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Toyota Motors Corporation exhaust emission control systems are certified as described below for qasoline-powered light-duty trucks:

Engine Family	Displacement Exhaust Emission Control Systems Liters (Cubic Inches) (Special Features)
JTY4.OT5FBB3	4.0 (241.3)  Air Injection - Pump  Exhaust Gas Recirculation  Dual Heated Oxygen Sensors  Dual Three-Way Catalysts  (Electronic Port Fuel Injection)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Loaded Vehicle Weight	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per mile	Nitrogen Oxides Grams per Mile	
3751-5750	0.50	9.0	1.0	

The following are the certification emission values for this engine family:

Loaded Vehicle Weight	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile	
3751-5750	0.15	1.7	0.24	

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 26 day of August, 1987.

K. D. Drachand, Chief P Mobile Source Division 17.11.00 Supplemental data sheets

1988 AIR RE	SOURCES BOARD SUPPLEMENTAL DATA SH	EET 8.0. # A-14-124
		Page <u>l</u> .
Manufacturer Toyota Motor Corp	oration Engine FamilyJTY4.	0T5FBB3
Evaporative FamilyEV-M	E Engine Type 6 cyl.	in-line
-	Liters (CID) 4.0	(241.3)
ABBREVIATIONS		
Ignition System	Exhaust Emissions Control System	Special Features
CA-Centrifugal Advance ECU-Electronic Control Unit EI-Electronic Ignition ESAC-Electronic Spark Advance Control VA-Vacuum Advance VR-Vacuum Retard  Fuel System CFI, CL, DID, DIP, EFI, MFI nV-nVenturi Carburetor	AIP-Air Injection-Pump AIV-Air Injection-Valve DBC-Dual Bed Catalyst EGR-Exhaust Gas Recirculation EIC-Electronic Injection Control EM-Engine Modification OC-Oxidation Catalyst OS-Oxygen sensor HOS-Heated Oxygen Sensor SPL-Smoke Puff Limiter or Throttle Delay TOC-Trap Oxidizer, Continual TOP-Trap Oxidizer, Periodical TWC-Three-Way Catalyst WUOC-Warm-Up Oxidation Catalyst WUTWC-Warm-Up Three-Way Catalyst	CCV-Combustion Chamber Valve CFI-Central Fuel Injection DID-Diesel Injection- Direct DIP-Diesel Injection- Prechamber EFI-Electronic Fuel Injection IC-Intercooler or aftercooler MFI-Mechanical Fuel Injection OBD-On-Board Diagnostics TC-Turbocharger
VEHICLE MODELS		
F	ruiser Wagon 4WD J62LG-PNEA J62LV-PNEA	
Engine: Front x Mid.	Rear	

RWD 4WD Full time 4WD Part time x

Page : 17.11-78

Drive:

Issued: 05/26/87 Rev. 1: 06/26/87

	1988 A	IR RESOU	URCES BO	DARD SUPPLEM	ental data si	HEET	•
Passenger	Cars Light-Du	aty Truc	cks <u>x</u>	Medium-Duty	Vehicles	Page Gas x Die	e
Manufactur	er Toyota Mo	tor Cor	poration	n Engin	e family	<i>J</i> TY4.0T	5FBB3
Liter (CII	4.0	(241.3)	<del> </del>	Eng.	Type 6 cyl	. in-line	
Emission (	Control Sys. (Spe	cial Fe	atures)	AIP + EGR	+ HOS + TWC	+ HOS + TWC	(BFI)
Engine	Vehicle Models (If Coded see		Test	EEC, EI, ESAC	CL. EFI		Catalyst
code	attachment) (Dyno Hp: Refer to 08.13.03.00)			Part No. [Computer]	Part No. [Computer] [Air flow meter] [Injector]	Part No.	Part No.
1, 2	FJ62LG-PNEA FJ62LV-PNEA	A4	4,750		89661-60010 22250-61010	1	17400-61010

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

23250-61010

Page : 17.11-79 Issued : 05/26/87

FJ62LV-PNEA