

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-44
Relating to Certification of New Motor Vehicles

SAAB-SCANIA AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Saab-Scania AB exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

| <u>Engine Family</u> | <u>Displacement Liters (Cubic Inches)</u> | <u>Exhaust Emission Control Systems (Special Features)</u> |
|----------------------|---|---|
| KSA2.0V5FTB4 | 2.0 (121.1) | Three-Way Catalyst Heated Oxygen Sensor (Electronic Port Fuel Injection) (Turbocharger (Intercooler) On-Board Diagnostics (Exempted) |

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

| <u>Hydrocarbons (Grams per Mile)</u> | <u>Carbon Monoxide (Grams per Mile)</u> | <u>Nitrogen Oxides (Grams per Mile)</u> |
|--|---|---|
| 0.41 | 7.0 | 0.7 |

The following are the certification emission values for this engine family:

| <u>Hydrocarbons (Grams per Mile)</u> | <u>Carbon Monoxide (Grams per Mile)</u> | <u>Nitrogen Oxides (Grams per Mile)</u> |
|--|---|---|
| 0.26 | 1.8 | 0.5 |

BE IT FURTHER RESOLVED: That the listed models are certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying to the optional NOx standard by providing evidence that there are sufficient projected sales of vehicles certifying to the primary NOx

emission standard, or is allowed a delay in implementation under small volume manufacturer provisions, or is allowed a delay in implementation under the "in lieu" standards, or is certifying passenger cars weighing more than 5250 lbs. loaded vehicle weight.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.), and with the 2 year/24,000 mile warranty provisions of Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 29th day of August, 1988.



K. D. Drachand, Chief
Mobile Source Division

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEETE.O. # A-22-44

Page 1

Manufacturer Saab-Scania ABEngine Family KSA2.OV5FTB4Evaporative Family K-900-5Engine Type S.I., 16-valve, 4-Cyl., In-LineLiters (CID) 2.0L (121.1 CID)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
 ECU-Electronic Control Unit
 EI-Electronic Ignition
 ESAC-Electronic Spark Advance Control
 VA-Vacuum Advance
 VR-Vacuum Retard

Exhaust Emissions Control System

AIP-Air Injection-Pump
 AIV-Air Injection-Valve
 DBC-Dual Bed Catalyst
 EGR-Exhaust Gas Recirculation
 EIC-Electronic Injection Control
 EM-Engine Modification
 OC-Oxidation Catalyst
 OS-Oxygen Sensor
 HOS-Heated Oxygen Sensor
 SPL-Smoke Puff Limiter or Throttle Delay
 TOC-Trap Oxidizer, Continual
 TOP-Trap Oxidizer, Periodical
 TWC-Three-Way Catalyst
 WUOC-Warm-Up Oxidation Catalyst
 WUTWC-Warm-Up Three-Way Catalyt

Special Features

CCV-Combustion Chamber Valve
 CFI-Central Fuel Injection or Throttle Body Injection
 DID-Diesel Injection-Direct
 DIP-Diesel Injection-Prechamber
 EFI-Electronic Fuel Injection
 IC-Intercooler or Aftercooler
 MFI-Mechanical Fuel Injection
 OBD-On-Board Diagnostics
 TC-Turbocharger

Fuel System

CFI, CL, DID, DIP, EFI, MFI
 nV-nVenturi Carburetor

VEHICLE MODELS:

Saab 900 Turbo 3-door
 Saab 900 Turbo 4-door
 Saab 900 Turbo SPG
 Saab 900 Turbo Convertible

Engine: Front X Mid. _____ Rear _____

Drive: FWD X RWD _____ 4WD Full Time _____ 4WD Part Time _____

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars Light Duty Trucks Medium Duty Vehicles Gas Diesel

Manufacturer Saab-Scania AB

Engine Family KSA2.OV5FTB4

ECS and (Special Features) TWC, HOS, (EF1, TC, IC)

CID (liter) - Engine Type 121.1 (2.0) S.I., 16 valve, 4-Cyl., In-Line

| Engine Code | Vehicle Models (If Coded see Attachment) (HP) | Trans. | Equiv. Test Weight | Ign. System Part No. | Fuel System Part No. | EGR Valve Part No. | Catalyst Part No. |
|-------------|---|--------|--------------------|--------------------------------|--|--------------------|-------------------|
| 2022L13M | 900 Turbo 3-door | M5 | 3250 | Distributor Saab #748139 | Electronic Control Unit Saab #8978348 | N/A | 7533540 |
| | 900 Turbo 4-door | M5 | 3250 | Bosch #0 237 | Bosch #0 280 | | |
| | 900 Turbo SPG | M5 | 3250 | 507 008 | 000 570 | | |
| | 900 Turbo Convertible | M5 | 3250 | | | | |
| 2022L13A | 900 Turbo 3-door | A3 | 3250 | Ignition Coil Saab #8573834 | Air Mass Meter Saab #7538655 | | |
| | 900 Turbo 4-door | A3 | 3250 | Bosch #0 227 | Bosch #0 280 | | |
| | 900 Turbo SPG | A3 | 3250 | 100 147 | 212 013 | | |
| | 900 Turbo Convertible | A3 | 3250 | Power Stage Saab #8980534 | Oxygen Sensor Saab #9392762 | | |
| | | | | Bosch #0 227 | Bosch #0 258 | | |
| | | | | 100 147 | 003 028 | | |

NOTE: FOR ADDITIONAL PART NUMBERS - SEE SECTION 20T, PAGE 10

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Add 10% to dyno test Hp for air conditioning usage.