File

(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-314-5 Relating to Certification of New Motor Vehicles

KIA MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Kia Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

<u>Fuel Type</u>: Gasoline

Engine Family: SKM1.6VJG2EA Displacement: 1.6 Liters (97.5 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Warm-Up Three Way Catalytic Converter Three Way Catalytic Converter Heated Oxygen Sensor Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

| <u>Miles</u> | Non-Methane Organic Gas | Carbon <u>Monoxide</u> | <pre>- NitrogenOxides</pre> | <u>Formaldehyde</u> |
|--------------|----------------------------|---------------------------|-----------------------------|---------------------|
| 50,000 | 0.125 | 3.4 | 0.4 | 0.015 |
| 100,000 | 0.156 | 4.2 | 0.6 | 0.018 |

<u>Reactivity Adjustment Factor (RAF) for NMOG Mass Emission</u>: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1995 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

| Miles | Non-Methane <u>Organic Gas</u> | Carbon <u>Monoxide</u> | Nitrogen Oxides | <u>Formaldehyde</u> |
|-------------------|-----------------------------------|---------------------------|--------------------|---------------------|
| 50,000 100,000 | 0.082 0.087 | 0.3 0.3 | 0.2 | 0.002 |

r

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vedicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles." BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles with Three-Way Catalyst Systems and Feedback Control" (Title 13, California Code of Regulations, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models have been exempted from compliance with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-duty Trucks, and Medium-Duty Vehicles and Engines" pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(2.0) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{1}{2}$ day of December, 1994.

R. B. Summerfield Astatant Division Chief Mobile Source Division

E.O.# A-314-5

199_5_ AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1_ of 1_ PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

| Manufacturer: Kia Motors Corporation Exh Engine Family: SKM1.6VJG2EA |
|--|
| Evap Std: 50K_X_Useful Life with R/L Evap Engine Family:SKM1065BYM02 |
| Exh Std: Tier-0 Tier-1 TLEV_X_LEV ULEV ZEV; EPA Tier-0 Tier-1_X |
| Vehicle Class(es): PC_X_LDT1LDT2MDV1MDV2MDV3MDV4MDV5 |
| Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) |
| Exh Cert Fuel(s): Indo Ph2_X Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or -94 |
| M85 CNG LPG Other (Specify) |
| Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Gasoline X Diesel M85 |
| CNGLNGLPGOther (specify) |
| Hybrid: Type ABC, APU Cycle (e.g., Otto, Diesel, Turbine) |
| Engine Configuration: <u>I-4</u> Displacement: <u>1.6</u> Liters <u>97.5</u> Cubic Inches |
| Engine: Front X Mid Rear Drive: FWD X RWD 4WD-FT 4WD-PT |
| Exhaust ECS (e.g., EGR, MFI, TC, CAC):SFI, WU-TWC. TWC. HO2S. EGR OBD I Exempt |
| (use abbreviations per SAE J1930 SEP91) |

| Engine Code | Vehicle Models | Trans. Type | ETW | DPA | | | |
|----------------------------|----------------|-------------------------|---------------|------------|-----------------------------------|-------------------------------|---|
| (also list CA/49ST/50ST | (if coded see | A-automatic M-manual | ar Test Wt | or RLHP | Ignition (ECM/PCM) Part No. | EGR System Part No. | Catalyst Converter |
| B6DC-MN | Kia Sephia | M-5 | 2750 | 5.8 | Distributor | EGR M Control C Valve : | Part No. Monolith Converter : B6CK(Pre.) B6DE(Main) |
| B6DC-MC | | | 2750 | 6.4 | : B6BF ECU: ZV16 | | |
| B6DC-AN | | L-4 | 2750 | 5.4 | Distributor | | |
| B6DC-AC | | | 2875 | 5.9 | : B6BF ECU: ZV17 | | |

Certification Standards:

. .

| | NMOG | CO | NOx | НСНО | EVAP. |
|---------------------------------|-----------------|--------------------------|--------------------------|--------------------------|------------|
| 50,000 mile : 100.000 mile : | | 3.4 g/mile 4.2 g/mile | 0.4 g/mile 0.6 g/mile | 15 mg/mile 18 mg/mile | 2.0 g/test |
| | at 2500 rpm N/L | at id | le | | |
| Idle HC : | 220 | 100 | | | |
| Idle CO : | 1.2 | 1.0 | | | |
| , _ | | | | | |

Issue Date : August 30, 1994 Revised : Sec.17.02.00.00-2