State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-210 Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TTK2.3VJGFEK <u>Displacement</u>: 2.3 Liters (138 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Warm Up Three-Way Catalytic Converters
Three Way Catalytic Converter
Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection
Supercharger

Dual Charge Air Coolers

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	Hydrocarbons	<u>Monoxide</u>	Oxides	Monoxide (20°F)
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100.000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>
50,000	0.16	1.4	0.1	6.5
100,000	0.18	1.6	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{16}{2}$

day of August 1995.

R. B. Summerfield

Assistant Division Chief Mobile Source Division

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

E.O.# A-16-210 page 2 of 2

		ntion	Engine Fa	mily		C2.3VJGFEK	
Manufacturer N	lazda Motor Corpor	auon	Evap Fami		TT	C1078BYPA1	
		400	EAC V	•			
All Eng Codes in E	ng Fam: CA_	498	_500 <u></u>	- !!! F	v ZEV	US EP	A Tier 1 <u>X</u>
All Eng Codes in E Stds. Type: CA Ti	er-1 <u>X</u> AB96	5ILEV_	LEV _	Evh Std:	VZLV _	Alt In	Use
Evap Std: Veh. Calss:	50K	-	Single	Cert Std for	Multi-Class En	g Fam: N/A	
Veh. Calss:	PC		Single	on Tact Fill	el(s):	Indole	ne
Fuel Type(s): Service Accum: _	Gasoline		Emissi	Olf Lear i ni	31(0)		
Service Accum:	Std AMA			December	ıro.	N/A	
NMOG Test Proce	edure: N/A				re:	-0.40	
Hybrid:	N/A		APU C	ycle:	a 2 Liters		Cu. inches
Engine Config :	V-6		Displa	cement	2.3 Liters	5300 RI	_
Valves/Cly.	4		Rated	HP	210 @ RWD	100 III	4WD-PT
Engine : Front	X Mid.	Rear	Drive:	FWD X	HMD '	444D-L1	
Linguis Tracks _					<i>(3)</i> 2		1505
Exhaust ECS & S	necial Ecoture (inc	CARB, MEL	etc.)	2 H	O2S/SFI/WU-TV	VC/TWC/EGR/	SC/CAC
Exhaust ECS & S	pecial realule (III	n MAY91)	-				
(Use abbreviati	ons per SAE J193			DPA	Ignition	EGR	
	Vehicle Model	Trans. Type		or	(ECM/PCM)	System	Catalyst
Engine Code	(if coded see	A-autonatic	ETW	RLHP	Part No.	Part No.	Part No.
(Cert, Std.)	attachment)	M-manual				 	Monolith
FKJSTAAT	Millenia	A4	3750	5.7	Distributor:	EGR	
INJOINT		ļ			•••	Control	Converter:
	ļ					Valve:	KJ13
		•				KJ01	KJ02
		Ĺ			ECU:	}	KJ02
1							· ·
		•		<u> </u>	KJ13		
					1		1
				1			
	}			1		1	ļ
		ļ					
				}			
						1	
		1					
				1		1	
		}			1	1	
	Ì	1	1			*	1
-	1		1				·
							-
			1	1	1		
Revisions:							

Revisions: 1290

Issue date:	June 30, 1995	
Rev. No.		
Date		