

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-292  
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TTY4.0VJGKHK Displacement: 4.0 Liters (242.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Sequential Multiport Fuel Injection
- Exhaust Gas Recirculation
- Dual Heated Oxygen Sensors (two)
- Dual Three Way Catalytic Converters
- Three Way Catalytic Converter

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.12	0.8	0.1	6.5
100,000	0.13	0.8	0.1	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 9<sup>th</sup> day of August 1995.



R. B. Summerfield  
Assistant Division Chief  
Mobile Source Division

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: TTY4.0VJGKHK Evap Fam: TTY1115AYME0  
 All Eng Codes in Eng Fam: CA 49S 50S x AB965  
 Exh Std: CA Tier-1 x TLEV LEV ULEV ZEV; US EPA Tier-1 x  
 Evap std: 50K Useful Life with R/L x In-Use Exh Std: Full In Use x Alt In Use  
 Veh Class(es): PC x LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5  
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Fuel Type(s): Dedicated x Flex-Fuel Dual-Fuel Bi-Fuel Gasoline x Diesel  
CNG LNG LPG M85 Other(specify) \_\_\_\_\_  
 Emiss Test Fuel(s): Indo x Ph2 CNG LPG M85 Other(specify) \_\_\_\_\_  
Diesel: 13CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94  
 Service Accum: Std AMA Mod AMA x Mfr ADP Other(specify) \_\_\_\_\_  
 NMOG Test Procedure: N/A x Std Equiv R/L Test Proc: SHED x Pt Source  
 Hybrid: Type A B C, APU Cycle(e.g., Otto, Diesel, Turbine): \_\_\_\_\_  
 Engine Configuration: V-8 Displacement: 4.0 / \_\_\_\_\_ Liters 242.2 / \_\_\_\_\_ Cubic Inches  
 Valves per Cylinder: 4 Rated HP: \_\_\_\_\_ 260 @ \_\_\_\_\_ 5,300 RPM  
 Engine: Front x Mid Rear Drive: FWD RWD x 4WD-FT 4WD-PT  
 Exhaust ECS(e.g., MFI, EGR, TC, CAC): SFI, EGR, 2HO2S(2), 2TWC, TWC  
 (use abbreviations per SAE J1930 SEP91)

Engine Code/ (also list CA/ 49S/ 50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic converter part No.
1, 1R1 & 1R2	UCF20L-AEPGKA	L4	4000	7.7	89661-50300*1 89661-50302*2 89661-50303*3	25620-50030	Front:A01 Rear:D01

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

- Note \*1 : Before Running change 96-TR-1.  
 \*2 : After Running change 96-TR-1 and Before Running change 96-TR-4.  
 \*3 : After Running change 96-TR-4.

VEHICLE MODELS:

LS400  
UCF20L-AEPGKA

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

6.2

Manufacturer: TOYOTA Exh Eng Fam: TTY4.0VJGKHK Evap Fam: TTY1115AYME0  
 All Eng Codes in Eng Fam: CA 49S 50S x AB965  
 Exh Std: CA Tier-1 x TLEV LEV ULEV ZEV; US EPA Tier-1 x  
 Evap std: 50K Useful Life with R/L x In-Use Exh Std: Full In Use x Alt In Use  
 Veh Class(es): PC x LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5  
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Fuel Type(s): Dedicated x Flex-Fuel Dual-Fuel Bi-Fuel Gasoline x Diesel  
CNG LNG LPG M85 Other(specify)  
 Emiss Test Fuel(s): Indo x Ph2 CNG LPG M85 Other(specify)  
Diesel: 13CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94  
 Service Accum: Std AMA Mod AMA x Mfr ADP Other(specify)  
 NMOG Test Procedure: N/A x Std Equip R/L Test Proc: SHED x Pt Source  
 Hybrid: Type A B C, APU Cycle(e.g., Otto, Diesel, Turbine):  
 Engine Configuration: V-8 Displacement: 4.0 / Liters 242.2 / Cubic Inches  
 Valves per Cylinder: 4 Rated HP: 260 @ 5,300 RPM  
 Engine: Front x Mid Rear Drive: FWD RWD x 4WD-FT 4WD-PT  
 Exhaust ECS(e.g., MFI, EGR, TC, CAC): SFI, EGR,2HO2S(2),2TWC,TWC  
 (use abbreviations per SAE J1930 SEP91)

	Sect/Page#		Sect/Page #
1 Authorized Representative	01.02.00	21 Gen Std, increase in Emiss,	
2 Fuel Specifications	03.00.00	Safety, Meets all Reqmts	20.03.05
3 Test Equipment	04.00.00	22 Emission Label Durability	07.00.00
4 Test Procedure	05.00.00	23 Driveability Statement	17.01.02
5 Mileage Accumulation Route	02.04.00	24 Adjustable Parameters	08.16.01.00
6 Emission Warranty Statement	17.10.00	25 Tamper Resistance Method(s)	08.16.02.00
7 Maint: Cert/Req'd/Recm'd	06.00.00	26 Fill Pipe Specifications	17.04.00
8 Emiss Label/Vac Hose Diag	07.00.00	27 High Altitude Compliance	17.02.00
9 Evap Control System	19.00.00	28 OBD Sys incl Marked Revisions	02.06.00
10 Engine Parameters	20.01.00	29 I&M Test Procedure & Data	17.11.00
11 Fuel System	08.01.00.00	30 50 Degree F Compliance	N/A
12 Ignition System	08.01.00.00	31 Manufacturer's RAF	N/A
13 Exhaust Control System	20.02.00	32 Phase-In Plans: Exh Cert Stds	N/A
14 Proj Sales(LDT/MDV Split)	17.13.00	Exh In-Use Stds	17.18.00
15 Vehicle Description	20.02.08	Evap Cert Stds	17.19.00
16 Evap Bench Test Procedure	13.02.02	33 NMOG Fleet Average Calculation	17.15.00
17 R/L Temp & Press Profiles	19.05.03&12.01.03	34 AB965 Credits/Withdrawals	N/A
18 EDV Selection	02.03.02	35 EPA Certificate <u>TOYOT-LDV-96-05-00</u>	
19 Prod Veh same as Test Veh	17.01.01	36 Equiv NMOG Proc--ARB Approval	N/A
	Durability	Emission	Emission
20 Test Vehicle Information	Data Vehicle	Data Vehicle	Data Vehicle
C/O or C/A MY & ID	C/O 95-D3	95-UCF2	---
Vehicle Log Page(s)	20.03.04	20.03.04	---
Zero Mile Book Page(s)	17.12.01(95MY)	20-03.06	---
Maint Logs & Engr Eval	17.12.01(95MY)	N/A	---

Continued on next page