

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-755
Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year General Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VGM4.6VJG1EK Displacement: 4.0 Liters (240 Cubic Inches)
4.6 Liters (280 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation
Three Way Catalytic Converter
Dual Heated Oxygen Sensors
Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Hydrocarbons</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Carbon Monoxide (20⁰F)</u> |
|--------------|---------------------------------|------------------------|------------------------|--|
| 50,000 | 0.25 | 3.4 | 0.4 | 10.0 |
| 100,000 | 0.31 | 4.2 | 0.6 | n/a |

The certification exhaust emission values for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Hydrocarbons</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Carbon Monoxide (20⁰F)</u> |
|--------------|---------------------------------|------------------------|------------------------|--|
| 50,000 | 0.15 | 1.9 | 0.2 | 6.5 |
| 100,000 | 0.20 | 2.6 | 0.2 | n/a |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 22nd day of April 1996.



R. B. Summerfield
Assistant Division Chief
Mobile Source Division

**AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
GASOLINE-FUELED PASSENGER CARS**

VEHICLE MODELS: 1 ↓ Q 3 7 (EXAMPLE)

Digit 1 - Selling Division

- 1 - Chevrolet
- 2 - Pontiac
- 3 - Oldsmobile
- 4 - Buick
- 6 - Cadillac
- 8 - Saturn

Digit 2 - Body Designation

- C - Ninety-Eight, Park Avenue
- E - Eldorado
- F - Camaro, Firebird/Formula
- G - Riviera, Aurora
- H - Bonneville, Eighty-Eight, LeSabre
- J - Cavalier, Sunfire
- K - Seville
- Ksp - Deville/Concours
- N - Grand Am, Achieva, Skylark, Malibu, Cutlass Supreme
- V - Catera
- W - Grand Prix, Regal, Century, Lumina, Monte Carlo
- Y - Corvette
- Z - Saturn SC, SL, SW

Digit 3 - Trim Level

B, C, D, E, F, G, H, J, K, L, M, N, P, R, S, T, U, V, W, X, Y, Z

Digits 4 & 5 - Body Style

- | | |
|----------------------------|----------------------------|
| 07 - 2Dr Sport Coupe | 37 - 2Dr Hardtop Coupe |
| 08 - 2Dr Hatchback Coupe | 47 - 2Dr Hardtop Coupe |
| 11 - 2Dr Notchback | 57 - 2Dr Hardtop Coupe |
| 15 - 2Dr Station Wagon | 67 - 2Dr Convertible Coupe |
| 19 - 4Dr Sedan | 68 - 4Dr Hatchback Sedan |
| 23 - 4Dr Aux. Seat Sedan | 69 - 4Dr (Notchback) Sedan |
| 27 - 2Dr (Notchback) Coupe | 77 - 2Dr Hatchback Coupe |
| 29 - 4Dr Sedan | 87 - 2Dr Hatchback Coupe |
| 35 - 4Dr Station Wagon | 90 - Commercial Chassis |

ISSUED: ML-VP045

REVISED:

17-VGM4.6VJG1EK-1
(1997)

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

MFR: GENERAL MOTORS CORP. ENGINE FAMILY: VGM4.6VJG1EK EVAP FAMILY: VGM1095AYPAA
 ALL ENGINE CODES IN ENGINE FAMILY: CA (X) 49S () 50S () AB965 ()
 EXH STD: CA TIER-1 (X) TLEV () LEV () ULEV () ZEV (); U.S. EPA TIER-1 ()
 EVAP STD: 50K (X) USEFUL LIFE WITH R/L (); IN-USE EXH STD: FULL (X) ALTERNATIVE ()
 VEH CLASS(ES): PC (X) LDT1 () LDT2 () MDV1 () MDV2 () MDV3 () MDV4 () MDV5 ()
 SINGLE CERT STANDARD FOR MULTI-CLASS ENGINE FAMILY: NA
 FUEL TYPE(S): DEDICATED (X) GASOLINE (X); EMISSION TEST FUEL(S): INDOLENE () PHASE 2 (X)
 SERVICE ACCUMULATION: STD AMA () MFR ADP (X); NMOG TEST PROCEDURE: NA (X) EQUIV ()
 R/L TEST PROCEDURE: NA (X) PT SOURCE (); HYBRID TYPE: NA APU CYCLE: NA
 ENGINE CONFIGURATION: I4 () V6 () V8 (X) DISPLACEMENT: 4.6 LITERS / 280 CU. IN.
 VALVES / CYLINDER: 2 () 4 (X) RATED HP: 300 @ 6000 RPM
 ENGINE LOCATION: FRONT (X) DRIVE: FWD (X) RWD () 4WD-FT () 4WD-PT ()
 EXHAUST EMISSION CONTROL SYSTEM: EGR-TWC-SFI-2HO2S-(HO2S(2))
 RLHP / DPA VALUES: SECTION 08.13.02.00

| ENG CODE (LOC) (C) | VEH MODELS (SEE PAGE 1) | TRANS (M5,A4,ETC.) | EQUIV. TEST WEIGHT | IGNITION (PCM/CALIB PART NO.) | EGR SYSTEM PART NO. | CATALYTIC CONVERTER PART NO. |
|-----------------------------|----------------------------------|-----------------------|--------------------------|----------------------------------|---------------------------|------------------------------------|
| 11 | 6KY69 6ET57 | A4 | 4250 | 16214848/16244156 | 17096310 | 25161562, 25314806 |
| 11A | | | | 16214848/16244756 | | |
| 11B | | | | 16214848/16256616 | | |
| 12 | 6ET57 6KY69 6KF69 | | | 16214848/16244166 | | |
| 12A | | | | 16214848/16244766 | | |
| 12B | | | | 16214848/16256626 | | |
| 13 | 6EL57 6KS69 6KD69 6KE69 | | 4000 4250 | 16214848/16235316 | | |
| 13A | | | | 16214848/16244126 | | |
| 13B | | | | 16214848/16256586 | | |

| CARLINE NAME | CARLINE CODE |
|--------------|--------------|
| SEVILLE | 10005 |
| ELDORADO | 10020 |
| DEVILLE | 10010 |

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

FR: GENERAL MOTORS CORP. ENGINE FAMILY: VGM4.6VJG1EK EVAP FAMILY: VGM1070AYPAA
 ALL ENGINE CODES IN ENGINE FAMILY: CA (X) 49S () 50S () AB965 ()
 EXH STD: CA TIER-1 (X) TLEV () LEV () ULEV () ZEV (); U.S. EPA TIER-1 ()
 EVAP STD: 50K (X) USEFUL LIFE WITH R/L (); IN-USE EXH STD: FULL (X) ALTERNATIVE ()
 VEH CLASS(ES): PC (X) LDT1 () LDT2 () MDV1 () MDV2 () MDV3 () MDV4 () MDV5 ()
 SINGLE CERT STANDARD FOR MULTI-CLASS ENGINE FAMILY: NA
 FUEL TYPE(S): DEDICATED (X) GASOLINE (X); EMISSION TEST FUEL(S): INDOLINE () PHASE 2 (X)
 SERVICE ACCUMULATION: STD AMA () MFR ADP (X); NMOG TEST PROCEDURE: NA (X) EQUIV ()
 R/L TEST PROCEDURE: NA (X) PT SOURCE (); HYBRID TYPE: NA APU CYCLE: NA
 ENGINE CONFIGURATION: I4 () V6 () V8 (X) DISPLACEMENT: 4.0 LITERS / 240 CU. IN.
 VALVES / CYLINDER: 2 () 4 (X) RATED HP: 250 @ 5600 RPM
 ENGINE LOCATION: FRONT (X) DRIVE: FWD (X) RWD () 4WD-FT () 4WD-PT ()
 EXHAUST EMISSION CONTROL SYSTEM: EGR-TWC-SFI-2HO2S-(HO2S(2))
 RLHP / DPA VALUES: SECTION 08.13.02.00

| ENG CODE (C) | VEH MODELS (SEE PAGE 1) | TRANS (M5,A4,ETC.) | EQUIV. TEST WEIGHT | IGNITION (PCM/CALIB PART NO.) | EGR SYSTEM PART NO. | CATALYTIC CONVERTER PART NO. |
|--------------|-------------------------|--------------------|--------------------|-------------------------------|---------------------|------------------------------|
| 14 | 3GR29 | | | 16214848/16235426 | 17096310 | 25161938 |
| 14A | | | | 16214848/16244736 | | |
| 14B | | | | 16214858/16256666 | | |
| 15 | 3GR29 | | | 16214848/16235436 | | |
| 15A | | | | 16214848/16244746 | | |
| 15B | | | | 16214848/16256676 | | |

CARLINE NAME
 AURORA

CARLINE CODE
 29045

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

MFR: GENERAL MOTORS CORP. ENGINE FAMILY: VGM4.6VJG1EK EVAP FAMILY: VGM1070AYPAA
 ALL ENGINE CODES IN ENGINE FAMILY: CA (X) 49S () 50S () AB965 ()
 EXH STD: CA TIER-1 (X) TLEV () LEV () ULEV () ZEV (); U.S. EPA TIER-1 ()
 EVAP STD: 50K (X) USEFUL LIFE WITH R/L (); IN-USE EXH STD: FULL (X) ALTERNATIVE ()
 VEH CLASS(ES): PC (X) LDT1 () LDT2 () MDV1 () MDV2 () MDV3 () MDV4 () MDV5 ()
 SINGLE CERT STANDARD FOR MULTI-CLASS ENGINE FAMILY: NA
 FUEL TYPE(S): DEDICATED (X) GASOLINE (X); EMISSION TEST FUEL(S): INDOLENE () PHASE 2 (X)
 SERVICE ACCUMULATION: STD AMA () MFR ADP (X); NMOG TEST PROCEDURE: NA (X) EQUIV ()
 R/L TEST PROCEDURE: NA (X) PT SOURCE (); HYBRID TYPE: NA APU CYCLE: NA
 ENGINE CONFIGURATION: I4 () V6 () V8 (X) DISPLACEMENT: 4.0 LITERS / 240 CU. IN.
 VALVES / CYLINDER: 2 () 4 (X) RATED HP: 250 @ 5600 RPM
 ENGINE LOCATION: FRONT (X) DRIVE: FWD (X) RWD () 4WD-FT () 4WD-PT ()
 EXHAUST EMISSION CONTROL SYSTEM: EGR-TWC-SFI-2HO2S-(HO2S(2))
 RLHP / DPA VALUES: SECTION 08.13.02.00

| ENG CODE (OC) | VEH MODELS (SEE PAGE 1) | TRANS (M5,A4,ETC.) | EQUIV. TEST WEIGHT | IGNITION (PCM/CALIB PART NO.) | EGR SYSTEM PART NO. | CATALYTIC CONVERTER PART NO. |
|------------------|----------------------------|-----------------------|-----------------------|----------------------------------|------------------------|------------------------------------|
| (NW) | | | | | | |
| 30 | 6KH69+V4U | A4 | 5500 | 16214848/16251976 | 17096310 | 25161938 |

| CARLINE NAME | CARLINE CODE |
|--------------|--------------|
| LIMOUSINE | 10015 |
| HEARST | 10035 |

SUED: ML-VR107

REVISED:

17-VGM4.6VJG1EK-4
(1997)