

File

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-828  
Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year General Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: WGMXV03.1044 Displacement: 3.1 Liters (191 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

- Three Way Catalytic Converter
- Heated Oxygen Sensors (two)
- Exhaust Gas Recirculation
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Organic Gases</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Formaldehyde</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|----------------------------------|------------------------|------------------------|---------------------|-------------------------------|
| 50,000       | 0.125                            | 3.4                    | 0.4                    | 0.015               | 10.0                          |
| 100,000      | 0.156                            | 4.2                    | 0.6                    | 0.018               | n/a                           |

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.98 RAF for 1998 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane<br/>Organic Gases</u> | <u>Carbon<br/>Monoxide</u> | <u>Nitrogen<br/>Oxides</u> | <u>Formaldehyde</u> | <u>Carbon<br/>Monoxide (20°F)</u> |
|--------------|--------------------------------------|----------------------------|----------------------------|---------------------|-----------------------------------|
| 50,000       | 0.071                                | 0.6                        | 0.1                        | 0.001               | 6.6                               |
| 100,000      | 0.081                                | 0.7                        | 0.1                        | 0.002               | n/a                               |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).


BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 21 day of August 1997.

  
R. B. Summerfield, Chief  
Mobile Source Operations Division

(FOR CARB USE ONLY)

E.O. #A-6-828

**AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
GASOLINE-FUELED PASSENGER CARS**

VEHICLE MODELS: 1 J C 3 7 (EXAMPLE)

Digit 1 - Selling Division

- 1 - Chevrolet
- 2 - Pontiac
- 3 - Oldsmobile
- 4 - Buick
- 6 - Cadillac
- 8 - Saturn

Digit 2 - Body Designation

- C - Park Avenue
- E - Eldorado
- F - Camaro, Firebird/Formula
- G - Riviera, Aurora
- H - Bonneville, Eighty-Eight/Regency, LeSabre
- J - Cavalier, Sunfire
- K - Seville
- Ksp - Deville, Limousine, Funeral Coach/Hearse
- N - Grand Am, Achieva, Skylark, Malibu, Cutlass
- V - Catera
- W - Grand Prix, Regal, Century, Lumina, Monte Carlo, Intrigue
- Y - Corvette
- Z - Saturn SC, SL, SW, EV1

Digit 3 - Trim Level (Examples)

B, C, D, E, F, G, H, J, K, L, M, N, P, R, S, T, U, V, W, X, Y, Z

Digits 4 & 5 - Body Style (Examples)

- |                            |                            |
|----------------------------|----------------------------|
| 07 - 2Dr Sport Coupe       | 37 - 2Dr Hardtop Coupe     |
| 08 - 2Dr Hatchback Coupe   | 47 - 2Dr Hardtop Coupe     |
| 11 - 2Dr Notchback         | 57 - 2Dr Hardtop Coupe     |
| 15 - 2Dr Station Wagon     | 67 - 2Dr Convertible Coupe |
| 19 - 4Dr Sedan             | 68 - 4Dr Hatchback Sedan   |
| 23 - 4Dr Aux. Seat Sedan   | 69 - 4Dr (Notchback) Sedan |
| 27 - 2Dr (Notchback) Coupe | 77 - 2Dr Hatchback Coupe   |
| 29 - 4Dr Sedan             | 87 - 2Dr Hatchback Coupe   |
| 35 - 4Dr Station Wagon     | 90 - Commercial Chassis    |

ISSUED: ML-WP138

REVISED:

17-WGMXV03.1044-1  
(1998)

1998 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

MFR: GENERAL MOTORS CORP. ENGINE FAMILY: WGMXV03.1044 EVAP FAMILY: WGMXE0095904  
 ALL ENGINE CODES IN ENGINE FAMILY: CA (X) 49S ( ) 50S ( ) AB965 ( ) ORVR: YES ( ) NO (X)  
 EXH STD: CA TIER-1 ( ) TLEV (X) LEV ( ) ULEV ( ) SULEV ( ); U.S. EPA TIER-1 ( )  
 VEH CLASS(ES): PC (X) LDT1 ( ) LDT2 ( ) MDV1 ( ) MDV2 ( ) MDV3 ( ) MDV4 ( ) MDV5 ( )  
 EVAP STD USEFUL LIFE (X)  
 SINGLE CERT STANDARD FOR MULTI-CLASS ENGINE FAMILY: NA  
 FUEL TYPE(S): DEDICATED (X) GASOLINE (X); EXH EMIS TEST FUEL(S): INDOLINE ( ) PHASE 2 (X)  
 EVAP EMIS TEST PROCEDURE: CALIF ( ) FED (X)  
 SERVICE ACCUMULATION: STD AMA ( ) MFR ADP (X); NMOG TEST PROCEDURE: NA ( ) EQUIV (X)  
 R/L TEST PROCEDURE: PT SOURCE (X)  
 ENGINE CONFIGURATION: I4 ( ) V6 (X) V8 ( ) DISPLACEMENT: 3.1 LITERS / 191 CU. IN.  
 VALVES / CYLINDER: 2 (X) 4 ( ) RATED HP: 160 @ 5200 RPM  
 ENGINE LOCATION: FRONT (X) DRIVE: FWD (X) RWD ( ) 4WD-FT ( ) 4WD-PT ( )  
 EXHAUST EMISSION CONTROL SYSTEM: EGR-TWC-H02S (2) - SFI  
 RLHP / DPA VALUES: SECTION 08.13.02.00

| ENGINE CODE<br>& LETTER<br>DERIVATIVES*1 | LOC<br>(C/F/NW) | VEH MODELS<br>(SEE PAGE 1) | TRANS<br>(M5,A4,ETC.) | EQUIV.<br>TEST<br>WEIGHT | EGR<br>SYSTEM<br>PART NO. | CATALYTIC<br>CONVERTER<br>PART NO. |
|--|-----------------|----------------------------|-----------------------|--------------------------|---------------------------|------------------------------------|
| 1  | C               | 1WL69<br>1WN69<br>1WW27    | A4/A                  | 3625                     | 17096154                  | 24506761,<br>24508105              |

\*1 Base engine codes are the same as letter derivatives unless otherwise noted. Refer to PCM/VCM part number page for additional engine code letter derivative information.

CARLINE NAME  
 CHEVROLET LUMINA/MONTE CARLO

CARLINE CODE  
 03150

(FOR CARB USE ONLY)

E.O. #A-6-828

1998 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

PCM AND CALIBRATION PART NUMBERS

MFR: GENERAL MOTORS CORP.

ENGINE FAMILY: WGMXV03.1044

EVAP FAMILY: WGMXE095904

| <u>ENGINE CODE</u> | <u>PCM/VCM<br/>PART NUMBER</u> | <u>ENGINE CALIB</u> | <u>OPER CALIB</u> | <u>TRANS CALIB</u> |
|--------------------|--------------------------------|---------------------|-------------------|--------------------|
| 1                  | 16200870                       | 09353474            | NA                | NA                 |
| 1A                 |                                | 09352634            |                   |                    |

ISSUED: ML-WP138

REVISED: ML-WR049

17-WGMXV03.1044-5  
(1998)

**EMISSION DATA RATIOS**  
**TO BE USED FOR ASSEMBLY LINE TESTING**

|              | <u>3116W1024</u><br><u>(Config 008)</u> | <u>3147W127</u><br><u>(Config 003)</u> |
|--------------|---|--|
| NMHC* (G/MI) | 0.0609                                  | 0.0979                                 |
| NMOG (G/MI)  | 0.0631                                  | 0.1003                                 |
| HCHO (G/MI)  | 0.0012                                  | 0.0013                                 |
| NMOG:NMHC    | 1.0361                                  | 1.0245                                 |
| HCHO:NMHC    | 0.0197                                  | 0.0133                                 |

\* NMHC includes methane response factor.

Average NMOG:NMHC = 1.030

Average HCHO:NMHC = 0.016

Ratio established using Phase 2 emission certification fuel.

ISSUED: ML-WP138

REVISED: ML-WP161, ML-WP177

17-WGMXV03.1044-20  
(1998)