

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-322  
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: WTYXV03.0GXB Displacement: 3.0 Liters (182.7 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Sequential Multiport Fuel Injection
- Exhaust Gas Recirculation
- Dual Air Fuel Ratio Sensors
- Dual Warm Up Three Way Catalytic Converters
- Three Way Catalytic Converter
- Heated Oxygen Sensor

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Organic Gas</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Formaldehyde</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|--------------------------------|------------------------|------------------------|---------------------|-------------------------------|
| 50,000       | 0.075                          | 3.4                    | 0.2                    | 0.015               | 10.0                          |
| 100,000      | 0.090                          | 4.2                    | 0.3                    | 0.018               | n/a                           |

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 1998 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Organic Gas</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Formaldehyde</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|--------------------------------|------------------------|------------------------|---------------------|-------------------------------|
| 50,000       | 0.055                          | 0.3                    | 0.1                    | 0.002               | 4.8                           |
| 100,000      | 0.078                          | 0.4                    | 0.2                    | 0.002               | n/a                           |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 25<sup>th</sup> day of July 1997.



*for* R. B. Summerfield, Chief  
Mobile Source Operations Division

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXV03.0GXB Evap Fam: WTYXE0095AE1  
 All Eng Codes in Eng Fam: CA  49S  50S  AB965  , ORVR: YES  NO   
 Exh Std: CA Tier-1  TLEV  LEV  ULEV  SULEV  US EPA Tier-1   
 Veh Class(es): PC  LDT1  LDT2  MDV1  MDV2  MDV3  MDV4  MDV5   
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Fuel Type(s): Dedicated  Flex-Fuel  Dual-Fuel  Bi-Fuel  Gasoline  Diesel   
 CNG  LNG  LPG  M85  Other (specify) \_\_\_\_\_  
 Exh Emiss Test Fuel(s): Indo  CBG  CNG  LPG  M85  Other (specify) \_\_\_\_\_  
 Diesel: 13 CCR 2282  40 CFR 86.113-90  40 CFR 86.113-94   
 Evaporative Emission Test Procedure: California  Federal   
 Service Accum: Std AMA  Mod AMA  Mfr ADP  Other (specify) \_\_\_\_\_  
 NMOG Test Procedure: N/A  Std  Equip  R/L Test Proc: SHED  Pt Source   
 Engine Configuration: V-6 Displacement: 3.0 Liters 182.7 Cubic Inches  
 Valves per Cylinder: 4 Rated HP1: 192@5200 RPM\*1  
 Rated HP2: 198@5200 RPM\*2  
 Engine: Front  Mid  Rear  Drive: FWD  RWD  4WD-FT  4WD-PT   
 Exhaust ECS (e.g., MFI, EGR, TC, CAC): SF1,EGR,2A/F S(\*3),2WU-TWC,TWC,HO2S  
 (use abbreviations per SAE J1930 JUN93)

| Engine Code<br>(also list CA/49S/50ST) | Vehicle Models<br>(if coded see attachment) | Trans.<br>(M5, A4, etc.) | ETW<br>or<br>Test<br>Wt | DPA or<br>RLHP | Ignition<br>(ECM/PCM)<br>Part No. | EGR system<br>Part No. | Catalytic<br>Converter<br>Part No. |
|--|---|--------------------------|-------------------------|----------------|-----------------------------------|------------------------|------------------------------------|
| 2<br>&2R1                              | MCV20L-AEPGKA                               | L4                       | 3625                    | 6.7            | 89661-3T340*7                     | 25620-20020            | U13*4                              |
|  | MCV20L-AEPNKA                               |                          |                         |                | 89661-3T330*7                     |                        | U92*5                              |
|  | MCV20L-BTPGKA                               |                          | 3750                    | 7.4/7.3        | 89661-06600*7                     |                        | U99*5                              |
|  | MCV20L-CEPGKA                               |                          | 3625                    | 6.7            | 89661-06610*7                     |                        | V01*6                              |
|  | MCV20L-CEPNKA                               |                          |                         |                | 89661-3T341*8                     |                        | V02*6                              |
| 3<br>&3R1                              | MCX10L-AEPGKA                               | L4                       | 3750                    | 5.7            | 89661-07130*9                     |                        |                                    |
|  | MCX10L-AEPNKA                               |                          |                         |                | 89661-07131*10                    |                        |                                    |
|  | MCX10L-AESGKA                               |                          |                         |                | 89661-07140*9                     |                        |                                    |
|  | MCX10L-AESNKA                               |                          |                         |                | 89661-07141*10                    |                        |                                    |

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

- Note
- \*1: Applied to Carline CAMRY.
  - \*2: Applied to Carline ES 300 and AVALON
  - \*3: A/F S means Air-fuel ratio sensor.
  - \*4: Maker; TOYOTA MOTOR CORPORATION
  - \*5: Maker; TABC, INC.
  - \*6: Maker; CATALER INDUSTRIAL CO., LTD
  - \*7: Before Job#1 Running Change 98-TR-01
  - \*8: After Job#1 Running Change 98-TR-01
  - \*9: Before Running Change 98-TR-01
  - \*10: After Running Change 98-TR-01

17.11.00

E.O.# A-14-322

Page 2 of 2

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXV03.0GXB Evap.Fam: WTYXE0095AE1

VEHICLE MODELS:

| <u>CAMRY</u>  | <u>ES 300</u> | <u>AVALON</u> |
|---------------|---------------|---------------|
| MCV20L-AEPGKA | MCV20L-BTPGKA | MCX10L-AEPGKA |
| MCV20L-AEPNKA |               | MCX10L-AEPNKA |
| MCV20L-CEPGKA |               | MCX10L-AESGKA |
| MCV20L-CEPNKA |               | MCX10L-AESNKA |