

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-325
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: WTYXV04.0DBB Displacement: 4.0 Liters (242.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection
Dual Heated Oxygen Sensors (two)
Dual Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.14	1.0	0.4	3.1
100,000	0.18	1.5	0.5	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 4th day of September 1997.


R. B. Summerfield, Chief
Mobile Source Operations Division

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fan WTYXV04.0DBB Evap Fam: WTYXE0115AE1
 Eng Codes in Eng Fam: CA ___ 49S ___ 50S x AB965 ___ , ORVR: YES ___ NO x
 Exh Std: CA Tier-1 x TLEV ___ LEV ___ ULEV ___ SULEV ___ , US EPA Tier-1 x
 Veh Class(es): PC x LDT1 ___ LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
 Single Cert Std for Multi-Class Eng Far N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s): Dedicated x Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline x Diesel ___
 CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) _____
 Exh Emiss Test Fuel(s): Indo x CBG ___ CNG ___ LPG ___ M85 ___ Other (specify) _____
 Diesel: 13 CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
 Evaporative Emission Test Procedure: California ___ Federal x
 Service Accum: Std AMA ___ Mod AMA ___ Mfr ADP x Other (specify) _____
 NMOG Test Procedure: N/A x Std ___ Equip ___ R/L Test Proc: SHED x Pt Source ___
 Engine Configuration: V-8 Displacement: 4.0 Liters 242.2 Cubic Inches
 Valves per Cylinder: 4 Rated HP1: 290@6000 RPM
 Engine: Front x Mid ___ Rear ___ Drive: FWD ___ RWD x 4WD-FT ___ 4WD-PT ___
 Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,2HO2S(2),2TWC
 (use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49S/50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4, etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR system Part No.	Catalytic Converter Part No.
1,4,4R1, 4R2,4R3,	UCF20L-AEAGKA	L5	4250	7.7	89661-50430*1 89661-50431*2 89661-50432*3 89661-50433*4 89661-50434*5 89662-50010*6 89661-50560*7	N/A	LH:Q04, RH:Q03
3,6,6R1, 6R2,6R3,	UZZ30L-ACAZKA	L5	4000	9.0	89661-24530*1 89661-24531*2 89661-24532*3 89661-24533*4 89661-24534*5 89662-24010*6 89661-24610*7	N/A	LH:Q08, RH:Q07

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.
 Note *1 : Before running change 98-TR-4.
 *2 : After running change 98-TR-4 and before running change 98-TR-8.
 *3 : After running change 98-TR-8 and before running change 98-TR-10 and before field fix 98-TF-1.
 *4 : After running change 98-TR-10 and before running change 98-TR-15.
 *5 : After running change 98-TR-15.
 *6 : After field fix 98-TF-1 and before field fix 98-TF-4. *7 : After field fix 98-TF-4.

VEHICLE MODELS: LS 400 SC 300/SC 400
UCF20L-AEAGKA UZZ30L-ACAZKA

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXV04.0DBB Evap Fam: WTYXE0135AE1
 All Eng Codes in Eng Fam: CA ___ 49S ___ 50S x AB965 ___ , ORVR: YES ___ NO x
 Exh Std: CA Tier-1 x TLEV ___ LEV ___ ULEV ___ SULEV ___ , US EPA Tier-1 x
 Veh Class(es): PC x LDT1 ___ LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s): Dedicated x Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline x Diesel ___
 CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) _____
 Exh Emiss Test Fuel(s): Indo x CBG ___ CNG ___ LPG ___ M85 ___ Other (specify) _____
 Diesel: 13 CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
 Evaporative Emission Test Procedure: California ___ Federal x
 Service Accum: Std AMA ___ Mod AMA ___ Mfr ADP x Other (specify) _____
 NMOG Test Procedure: N/A x Std ___ Equip ___ R/L Test Proc: SHED x Pt Source ___
 Engine Configuration: V-8 Displacement: ___ 4.0 Liters ___ 242.2 Cubic Inches ___
 Valves per Cylinder: 4 Rated HP1: 300@6000 _____ RPM
 Engine: Front x Mid ___ Rear ___ Drive: FWD ___ RWD x 4WD-FT ___ 4WD-PT ___
 Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,2HO2S(2),2TWC

(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49S/50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4, etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR system Part No.	Catalytic Converter Part No.
2, 5,5R1, 5R2,5R3,	UZS160L-BEAQKA	L5	4000	8.9/9.4	89661-3A460*1 89661-3A461*2 89661-3A462*3 89661-3A463*4 89661-3A464*5 89662-30010*6 89661-30050*7	N/A	Q09

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

- Note *1 : Before running change 98-TR-4.
- *2 : After running change 98-TR-4 and before running change 98-TR-8.
- *3 : After running change 98-TR-8 and before running change 98-TR-10 and before field fix 98-TF-1.
- *4 : After running change 98-TR-10 and before running change 98-TR-15.
- *5 : After running change 98-TR-15.
- *6 : After field fix 98-TF-1 and before field fix 98-TF-4.
- *7 : After field fix 98-TF-4.

VEHICLE MODELS:

~~GS 400~~/GS 400
UZS160L-BEAQKA