Deli

(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-8-111-A Relating to Certification of New Motor Vehicles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: XBMXV02.8M52 <u>Displacement</u>: 2.8 Liters (170.4 Cubic Inches)

3.2 Liters (192.3 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1999 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000 100,000	0.083 0.093	1.1	0.2 0.2	0.002	2.5 n/a

- BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."
- BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.
- BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.
- BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).
- BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."
- BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).
- BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.
- BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).
- BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

R. B. Summerfield, Chief

Mobile Source Operations Division

1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

All Eng Codes in Eng Fam: CA 408 Exh. Engine Family: XBMXV02.8M52 Evap. Fam: XBMXE0156E36
493 508 X AB965 ORVE: VES NO
LEV X LEV ULEV SULEV 118 EPA Tigs 1
Veh Class: PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi - Class Eng Fam: N/A
Fuel Type (s): Dedicated Flex-Fuel Dual Fuel Bi - Fuel Diggel
CNG LNG LPG M85 Other (specify)
Diesel: 13 CCR 2282 40 CFR86.113-90
Evaporative Test Procedure: California X Federal
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)
NMOG Test Procedure: N/A Std Equiv _X R/L Test Proc: SHED _X Pt Source
Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Configuration: inline-6 Displacement: 2.8 Liters 170.4 Cubic Inches 3.2 Liters 192.3 Cubic Inches
Valves per Cylinder: 4 Rated HP: 190 @ 5 300 RPM (2.8 L) 240 @ 6 000 RPM (3.2 L)
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT Exhaust ECS: 2TWC, 2HO2S(2), SFI, AIR

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
2.8/3 M5 2.8/3 A5 2.8/3/C M5 2.8/3/C A5 3.2 MS 3.2 MS 3.2 MS 3.2 MS 3.2 MS A 3.2 MS A	328is 328isA 328iConv 328iAConv M3 M Coupe M 3 Conv. M3 A M3 A Conv.	ſ	3 375 3 500 3 625 3 750 3 500 3 375 3 750 3 500 3 875	6.2 6.8 6.8 6.2 7.8 7.0 6.2 7.0	1 433 685 1 430 251 1 405 548 1 405 968 1 406 680	n.a.	1 744 164 left 1 744 163 right 1 432 455 left 1 432 456 right