HYUNDAI MOTOR COMPANY

EXECUTIVE ORDER A-254-0077 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE YEAI				VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE						
2002	2HYX	2HYXV02.7FLS		Passenger Car	Low E	Emission Vehicle (LEV)	Gasoline (Indolene)						
No.		EVAPORATIVE FAMILY (EVAP)		SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC OC = oxidation catalytic converter O2S						
1	2HYXR015	R0150PEE		TWC, 2WUTWC, 2H		oxygen sensor AFS/HAFS = air/fuel sensor (aka. Universal O2S)/ heated AFS HO2S = heated O2S EGR = exhaust gas recirculation							
2	*	*			•								
3	*		3		•		AIR = secondary air injection PAIR = pulsed AIR MFI = multiport fuel injection SFI = sequential MFI						
4	*		4		•	TC/SC = turbo/super charger CAC = charge air coole OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie							
EVAF No.	P ECS No.	ENGINE SIZE (L	- 1			ECT TO SFTP	ABBREVIATIONS:						
1	1	2.7		Hyundai Sonata									
*	*	*				*							
*	*	* *		7.1.		*							
*	*	*				*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

AVER	NMOG FLEET AVERAGE [g/mi] CERT STD		NMOG [g/mi] @RAF = 1.00		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor												
CERT			CH4 RAF = *			CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		F	PM [g/mi]		Hwy NOx [g/mi]	
0.058	0.0	68	С	CERT STD		CERT	STD	С	ERT	STD	CERT	STD	CER	T S	TD	CERT ST	
K = 1000 miles	@	50K 0		.036	0.075	0.5	3.4	0.01		0.2	0.4	15	*		•	0.01	0.3
	@	@ 100K		.046	0.090	0.7	4.2	0.0	0.02	0.3	1	18	*		•	0.01	0.4
	@ 50°	F, 4K	0	.096	0.150	0.8	3.4	0.	0.01	0.2	0.1	30	*	***	*	*	*
	O [g/mi] 20°F, 50K			g = gram mg = milligram mi = mile		NMHC+NOx [g/mi] (composite)		N/	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	ST	STD				CERT	STD	С	ERT	STD	CERT	CERT STD	CER	CERT S		CERT	STD
8.7	8.7 10.0			@ 4K		*	*	0	0.04	0.14	2.8	8.0	0.01	0	.20	0.3	2.7
F = degre	e Fahrenh	eit			@ 100K	*	*		*	*	*	•	*		*	*	*
@ 100K	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				APORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
	3-D	2-0)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.6	1.8		0.02	0.05	*	*	*		*		*	•	*		*	*
STD	2.0	2.0 2.5		0.05	0.20	*	*	*	•	*	*	*	*	*	*	*	
2-D, 3-D [g	g/test] = 2-	day, 3-	day d	liurnal aı	nd hot-soak		RL [g/mi]	= runni	ng loss		ORVR [g/ga	allon of fue	dispense	d] = on-b	oard refu	ueling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

day of August 2001

R. B. Summerfield, Chief Mobile Source Operations Division w