

## LAND ROVER GROUP LTD.

EXECUTIVE ORDER A-277-0024 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE YEAR		T GROUF	•	VEHICLE TYPE		AUST EMISSION DARD CATEGORY	FUEL TYPE  Gasoline						
2002	2LR	XT04.6003	3	3,751 - 5,750 Pounds Adjusted Loaded Vehicle W Medium Duty Vehicle	eight Low E	Emission Vehicle (LEV)							
No.	EVAPOR FAMILY (		No.	SPECIAL FEAT EMISSION CONTROL	TURES & SYSTEMS (ECS)	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation							
1	2LRXE01	24001	1		02S(2), AIR, SFI, OB	D (P)	catalytic converter O2S = ovygen sensor						
2	*	•			*	HO2S = heated O2S							
3	*		3		*	MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air coole							
4	*		4		*	OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = series							
EVAF No.	ECS No.			VEHICLE MAKES & MODELS	VEHICLES SUB. STANDARDS AF		ABBREVIATIONS:						
1	1	4.0		Land Rover Discovery Series II									
*	*	* *		*									
*	*	* *		•									
*	*					*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]		NMOG [g/mi] @RAF = 0.94		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor													
CERT	ST	D	CH4 RAF = *		СО		NOx [g		HCHO [mg/mi]			PM [g/mi]			Hwy NOx [g/mi]		
* *			CERT		STD	CERT STD		CE	RT	STD	CERT	STD	CER		TD	CERT	STD
15 1000	@	50K	0	.054 0.160		0.9	4.4	0.	0.1		0.4	18	*		*	0.02	0.8
K = 1000 miles	@	@ 120K		.061	0.230	0.9	6.4	0.1	.1	0.6	0.4	27	*	_	*	0.02	1.2
	@ 50°	F, 4K	0	.091	0.320	1.4	4.4	0.	.1	0.4	0.0	36	*		*	*	*
	[g/mi] 0°F, 50K			g = gram mg = milligram mi = mile		NMHC+NOx [g/mi] (composite)		NMI	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]			NMHC+NOx [g/mi]		CO [g/mi] [SC03]	
CERT	CERT STD		N.			CERT	STD	CE	CERT		CERT	STD	CER			CERT	STD
4.8	12.5		Á	@ 4		*	*	*		*	*	*	*	* *		*	*
F = degree	Fahrenh	renheit		@ 120K		*	*	*		*	*	*	*	_	*	*	*
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
120K	3-D	2-D	П	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D		ORVR
CERT	0.6	0.6		0.00	*	*	*	*	*	*	•	*	*	*	*	*	*
STD	2.0	2.5	T	0.05		*	•	*	* *		*	*	*	•	*	*	+
2-D, 3-D [g/	(test] = 2-c	lay, 3-c	lay d	liurnal a	nd hot-soak		RL [g/mi] =	running	loss		ORVR [g/ga	llon of fue	l dispense	d] = on-b	oard refi	ueling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this of

day of September 2001

B. B. Summerfield, Chief Mobile Source Operations Division