

NISSAN MOTOR CO., LTD

EXECUTIVE ORDER A-015-0366 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP 2NSXV02.5C5A			VEHICLE TYPE		HAUST EMISSION NDARD CATEGORY	FUEL TYPE Gasoline						
200	2				Passenger Car	Lov	w Emission Vehicle (LEV)							
No.		EVAPORATIVE FAMILY (EVAP)		No.	SPECIAL FEAT EMISSION CONTROL		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2NSX	NSXR0085RCA			2TWC, 2	HO2S(2), SFI, OB	catalytic converter O2S = oxygen sensor HO2S = heated O2S							
2		•				*	AiR = secondary air injection PAIR = pulsed AIR							
3		•		3		•	MFI = multiport fuel Injection SFI = sequential MFi TC/SC = turbo/super charger CAC = charge air cooler							
4		•		4		*	OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie							
EVAF No.			ENGINI SIZE (L		VEHICLE MAKES & MODELS		IBJECT TO SFTP ARE UNDERLINED							
1	1		2.5		NISSAN SENTRA									
*	•		•		•									
•		* *												
* -	• •		•		•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]			NMOG [g/mi] @RAF = 0.94			CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor											
CERT	ERT STD		CH4 RAF = 1			CO [g/mi]			NOx [g/mi]		HCHO [mg/ml]		PM [g/mi]			Hwy NOx [g/mi]	
0.061	0.0	0.068		ERT	STD	CERT	STD	C	ERT	STD	CERT 0.3	STD	CER	T S	ΓD	0.03	STD 0,3
K = 1000 miles	@ 50K @ 100K @ 50°F, 4K		C	0.033	0.075	1.0	3.4	1).1	0.2		15	•		•		
			0.035		0.090	1.0	4.2	0.1	.1	0.3	0.4	18	•		•	0.04	0.4
			C	0.066	0.150	1.8	3.4	0.	0.1	0.2	1	30	•		•	•	1
	[g/mi] 0°F, 50K			g = gram mg = milligram mi = mile		NMHC+NOx [g/mi] (composite)] NA	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US08]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	ST					CERT	STD	CI	ERT	STD	CERT	STD	CER	T S	TD	CERT	STD
3.3	10.	10.0		@ 4K		*	•	0	.10	0.14	3.3	8.0	0.16	0.	20	0.4	2.7
F≖ degree	elt	@ 100K		•	•		*		•	•	•	•		*	•		
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2			ΕV	EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
100K	3-D	-D 2-D		RL	ORVR	3-D	2-D	RL	ORVE	R 3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.5	0.5		0.00	0.05	*	•	*	•	•	*	•	•	*	•	•	•
STD	2.0	2.0 2.5		0.05	0.20	•	•	+	-	•	*		*	•	•	•	•
2-D, 3-D [g.	/test] = 2-	day, 3-d	lay e	diumal a	nd hot-soak	recovery	RL	[g/mi] =	running	loss	ORVR (g/g	allon of fue	dispense	d] = on-be	pard ref	ueling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order

Executed at El Monte, California on this ______day of August 2001.

R. B. Summerfield, Chief Mobile Source Operations Division