

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1092 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROUP			P	MC	VEHICLE TYPE =passenger car; LDT=light-duty truck; V=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle;	EMISSION STAND Y (LEV=low emi TLEV= transitional LE LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200			V03.8VI	A		PC LEV				100K / 100K Gasoline (Tier 2 Unleaded)					
No.			ORATIVE Y (EVAF)				lo.	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heated			
1	3FMX	R010	R0105BAE			2TWC(2), 2HO2S(2),	EGR, SFI, O	AF	S/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhaust					
2		*	•			•		ga Ali	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		•			3					TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4		*			4			dia	gnostic prefix 2=para	liel (2) suffix=series					
EVAI No.		CS lo.			ABBREVIATIONS:										
1		1	3,8			Ford Mustang									
*		* *				•									
*		*	*												
*	*		*				#								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

				NMOG @ RAF= * CH4 RAF = *		CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D NMHC diurnal+hot-soak RL [g/mi]=running loss ORVR [g/g/allon dispensed]=on-board refuelling vapor re										1=2/3 day	
CER			NMOG	NMHC CERT [g/mi]	NMHC	diurnal+ho mg=milligi	t-soak Ri	. [g/mi]=rui	nning loss 000 miles	ORV	R [g/gallor	n dispensed ahrenheit	=on-board	refueling vap piemental fe	or recovery	g=gram	
0.053		0.062	CERT				[g/mi]		x [g/mi]			[mg/mi]		g/mi]		x [g/mi]	
500 000 000 000 000 000 000 000 000 000			[g/mi]	[g/iii]	1.0	CERT	STD	CERT	ST	<u> </u>	CERT	STD	CERT	STD	CERT	STD	
1	1. 整身课		0.030	* .	0.075	0.2	3.4	0.05	0.2	2	1	15	*	*	0.1	0.3	
	原療	@ UL	0.045	*	0.090	0.3	4.2	0.1	0.3	3	1	18	*	*	0.1	0.4	
401	@ 50	°F & 4K	•	*	*	*	*	*	*		•	*	*	*	*	*	
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+NO [g/mi] [US0			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50			SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	D CE	RT ST	D CER	T STD	CERT	STD	
CERT	2.3	1 2 3	2.6	SFTP 1	*	*	*	*	*	*		• •	*		*		
STD	10.0	多重	$h_{i,j,j,l,l}$	SFTP 2	*	*	*	*	*	*		• •	*	*	*	*	
@ UL	E	VAPOR	ATIVE FAN	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
<u> </u>	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.0	0.8	0.01	0.07	*	*	*	•	*	*	*	*	-	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	•	1	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of July 2002

Allen Lyons, Chief

Mobile Source Operations Division