

## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1096 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=llght-duty MDV=medium-duty vehicle; LVW=lovehicle weight; ALVW=adjusted L	truck; CATEGOR	EMISSION STANDA Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super UL	Sion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3	3FMXV04.6VG5			PC	1) USEPA I 2) Counted	Bin 7 I as ARB LEV I ULEV	, 100K / 100K	Gasoline (Tier 2 Unleaded)				
No.		EVAPORATIVE FAMILY (EVAF)		N	o. SPECIAL FEATO EMISSION CONTROL S		* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	3FM	3FMXR0115BAE			2TWC(2), 2HC	02S(2), EGR, SFI, O	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust						
2	*					*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*				*	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4						*							
EVAI No.		Table   Tabl		VEHICLES SUB. STANDARDS AF		ABBREVIATIONS:	BBREVIATIONS:						
1		1	4.6		Ford: Crown	Victoria, Crown Vic	ictoria Police; Lincoln Town Car; Mercury Grand Marquis						
•		*	*										
*	* *												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]			MOG @ CH4 R	RAF= * AF = *	NMOG or nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test										1=2/3 day			
CER	T	STD		NMOG NMHC		NMHC	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
0.05	3	0.062		ERT	CERT [g/mi]	[g/mi]		[g/mi]	NO	x [g/mi]		НСНО	[mg/mi]		g/mi]	Hwy NO			
			L9	/mi]		[9]	CERT	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD		
	@ 50K @ UL		0.	051	*	0.075	0.8	3.4	0.02	0.1	1	*	15	*	*	0.02	0.15		
			UL 0.066		*	0.090	0.9	4.2	0.03	0.15		*	18	*	*	0.03	0.20		
Ť	@ 50		K *		*	*	•	*	*	•		*	*	*	*	*	*		
	CO [g/mi] @ 20°F & 50K					NMHC+NC (compo	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]				HC+NOx ni] [SC03]	CO [g/mi] [SC03]					
50			SFTP 2 = @ UL (Tier		1, TLEV)	CERT	STD	CERT	STD	CERT	S	TD CE	RT ST			CERT	STD		
CERT	5.6	6		SF.	TP @ 4K	*	*	*	•	0.09	0	.14 0.	.05 8.0	0.01	0.20	0.2	2.7		
STD	10.0		1,5	5-460	rp@UL	0.09	0.68	*	*	*		* 0	.3 11.	.1 *	*	0.4	3.7		
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVA	POR	ATIVE F	AMILY 3	E	EVAPORATIVE FAMILY 4				
<u> </u>	3-D	2.	D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-	D R	L ORV	R 3-D	2-D	RL	ORVR		
CERT	1.4	1	.0	0.003	0.15	*	*	•	*	*	*	*	•	*	*	•	*		
STD	2.0	2	.5	0.05	0.20	*	*	*	*	*	*	•	•	*	+	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That NMOG and HCHO certification compliance has been conditionally demonstrated based on the amended test procedures adopted by the Board on November 15, 2001. In the event the amended procedures do not become effective, the manufacturer shall be required to submit NMOG and HCHO compliance test data within 30 days after notification by the ARB or this Executive Order may be revoked and voided *ab initio*.

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2

le L

Allen Lyons, Chief

New Vehicle/Engine Programs Branch

day of May 2002.