

MAZDA MOTOR CORPORATION

EXECUTIVE ORDER A-016-0278 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR		TEST GROUP		IP	ME	VEHICLE TYPE =passenger car; LDT=light-duty truck; V=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGOR'	EMISSION STAND Y (LEV=low emis LEV= transitional LEV LEV; SULEV=super U	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		3TKXV02.3CJM		M		PC		LEV		100K / 100K				
No.	FAM	ILY (E	ATIVE EVAF)	N	о.	SPECIAL FEATURES EMISSION CONTROL SYSTEI	& * = not applicable			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC				
1	3TK)	CXR0150PPC			1	TWC, HO2S(2), E		- W	J= warm-up cat. O2S/H S/HAFS=air-fuel ratio s	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust				
2		*			2	*		gas	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFi/SFI= multiport fuel injection/sequential MFi TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
3		*			3	*		— ∄тв						
4		*			1	*		⊪∪∧						
EVAI No.		ECS ENGINE No. SIZE (L				VEHICLE VEH MAKES & MODELS STA	IICLES SUBJ	ECT TO SFTP E UNDERLINED	E4	REVIATIONS:				
1_		1												
		*	*					Mazda 6						
*		*	*					*						
*		* *						*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET AVERAGE [g/mi] CERT STD		NMOG @ RAF=0.94 CH4 RAF = *		NMOG or							on-CH4 hydro									
CER			NMOG CERT	NMHC	NMHC STD	mg=millig	am mi=	- [g/////i]-i u	nning loss 1000 mile:	S UKV	rk (g/gano	n dispensed] Fahrenheit	=on-board r	efueling var plemental f	or recovery	o≂oram					
0.05	1 (0.062 CERT CERT [g/mi]		[g/mi]	CERT	[g/mi]		Ox [g/mi]		НСНО	[mg/mi]	PM [g/mi]	Hwy NC							
					+	CERT	STD	CER	T ST	D	CERT	STD	CERT	STD	CERT	STD					
41.2	434	@ 50K	0.024	*	0.075	0.5	3.4	0.1	0.2		0.3	15	*	*	0.02	0.3					
2010 500		@ UL	0.028	*	0.090	0.6	4.2	0.1	0.	3	0.3	18	*	*	0.03	0.4					
jie rej	@ 50°F		*	*	*	*	*	*	+			*	*	*	*	*					
@ 20	°F&	. LE	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)			NMHC+NO				NMHC+NOx [g/mi] [SC03]		CO [g/mi]						
50		SFTP 2 = @ UL (Tier 1, TLEV)		1, TLEV)	CERT	STD	CERT	STD	CERT	SI		RT ST			CERT	STD					
CERT	2.2	3 360		SFTP 1	. *	*	*	*	0.04	0.	14 0	.2 8.0	0.01	0.20	0.04	2.7					
STD	10.0		137		13.1			PP C	SFTP 2	*	*	*	*	*	1	•	* *	*	*	*	*
@ UL		VAPOR	ATIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				F	EVAPORATIVE FAMILY 4							
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D											
CERT	0.9	1.0	0.001	0.03	•	*	*	*	3-0		, KI	- ORVI		2-D	RL	ORVR					
STD	2.0	2.5		0.20	+ +	-	-						*	*		*					
0.0	2.0	2.0	0.05	0.20				*	*	*	*	*	*	*	•						

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Allen Lyons, Chief

Mobile Source Operations Division