

## **FUJ! HEAVY INDUSTRIES, LTD.**

EXECUTIVE ORDER A-002-0119-3 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			MI	VEHICLE TYPE  =passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARE CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3 31	3FJXX02.5JHM				PC	LEV			100K / 100K	Gasoline				
No.	FAMIL'	APORATIVE MILY (EVAF)			No.	SPECIAL FEATURES ( EMISSION CONTROL SYSTEM		* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing T WU= warm-up cat. O2S/HO2S=oxygen sensor/heated					
1	3FJXR	012	5188		1	TWC(2), HO2S(2	), SFI, OBD (F	AF	S/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhaust					
2		•			2	TWC(2), HO2S(2), S		gas	gas recirculation AIR/PAIR=secondary air injection/pulser AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		ў . 3.			3					TITBI= throttle body injection TC/SC=turbo (super charge)					
4					4	*		dia	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.	EC: No							ECT TO SFTP	ABB	BBREVIATIONS:					
1	1	[	2.5	_		SUBARU: IMPREZA RS, IMPREZA WAGON (TS, OUTBACK), FORESTER (2.5X, 2.5XS)									
1	2		2.5		SUBARU: LEGACY AWD (L, GT, OUTBACK LIMITED), LEGACY WAGON AWD (L, GT, OUTBACK), BAJA										
•			*		*										
•	*	* *		1	*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG F	LEET [g/mi]		RAF=0.94 AF = *	NMOG or	TOT THE OUB	n mumus	nrmainenv	/ON INEN:	articulate	o matter	DAETRASAL	carbons Co lvity adjustm	onet faataa	2/2 D [~ !!	1-0/0
CER	T	STD NMOG NMHC		NMHC STD	mg=millig	ot soak K	∟ լցտույ≕ru	nning loss 1000 miles	URVR	[g/gallon	dispensed) hrenheit	=on-board r  SFTP=sup	efueling vap	or recovery	g=gram	
0.07			CERT CERT		[g/mi]		[g/mi]		Ox [g/mi]		нсно [		PM [g			x (g/mi)
			[Aura]	[8,1111]		CERT	STD	CER	T ST		CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.050	•	0.075	1.4	3.4	0.1	0.2	2	1	15	*	*	0.01	0.3
-47	47.00	@ UL	0.053	•	0.090	1.7	4.2	0.1	0.3	3	1	18	*		0.01	0.4
Va. Wes	@ 50	0°F & 4K	0.085	*	0.150	1.5	3.4	0.04	0.2	2	0.5	30	•		*	*
@ 20		네 티	= @ 4K (SUL EV) or 50K (T	ler 1, TLEV)	NMHC+NC (compo				NMHC+NC [g/mi] [USC				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	50K		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CEI	RT ST		<del></del>	CERT	STD
CERT	4.4			SFTP 1	*	•	*	•	0.05	0.14	5.	1 8.0	0.06	0.20	1.3	2.7
STD	10.0			SFTP 2	•		•	•	*	*	•	•	*	•	*	•
@ UL			ATIVE FAN	ILY I	EVAPORATIVE FAMILY 2 EVAPOR					PORAT	IVE FA	MILY 3	E'	EVAPORATIVE FAMILY 4		
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR
CERT	1.1	1.1	0.00	0.02	· [	*	*	*		*	•	•	*	*	*	
STD	2.0	2.5	0.05	0.20	<b>-</b>	•	•	•	*	*	+	+	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-002-0119-2 dated June 4, 2002.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division