

## **TOYOTA MOTOR CORPORATION**

EXECUTIVE ORDER A-014-0448
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD! YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truc MDV=medium-duty vehicle; LVW=loade vehicle weight; ALVW=adjusted LVW)	k; CATEGOR d vehicle:	EMISSION STANDA Y (LEV=low emiss TLEV= transitional LEV; LEV; SULEV=super ULI	ION EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ ilquefled natural gas; LPG=llquefled petroleum gas)			
200	3	3TYXV03.0FFF			PC		LEV	100K / 100K	Gasoline			
No.		EVAPORATIVE FAMILY (EVAF)			SPECIAL FEATURI EMISSION CONTROL SYS		* = not applicable	WU= warm-up cat. O2S/	y cat. ADSTWC=adsorbing TWC HO2S=oxygen sensor/heated O2S			
1	3TY)	3TYXR0150AK1			2TWC, TWC, 21	O2S(2), SFI, OB	AFS/HAFS=air-fuel ratio	sensor/heated AFS EGR=exhaust				
2		*				*	gas recirculation AIR/PAIR=secondary air injection/pulsed   AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC≖turbo /super charger □CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
3		* * * * * * * * * * * * * * * * * * * *				*						
4		•				*	diagnostic prefix 2=par	allel (2) suffix=series				
EVAI No.		ECS ENGINE VEHICLE VEHICLES SUBJECT TO SFTP No. SIZE (L) MAKES & MODELS STANDARDS ARE UNDERLINE			ABBREVIATIONS:							
1	1 3.0			Lexus: GS 300, IS 300								
*	* * *						•					
*		*										
*		*   *										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF = 0.94 CH4 RAF = *			of nitroger	n HCHO=	formaldehy	de PM≖p	articulate i	matter	RAF=react	livity adjus	O≖carbon m tment factor refueling vap	2/3 D [g/te	st]=2/3 day
CER	RT STD		NMOG	NMHC	NMHC	mg=millig	ram ml=	mile K≖	1000 miles	F≖deg	rees Fa	hrenheit	SFTP=sup	plemental fe	deral test p	rocedure
0.05	5 1	0.062	CERT [g/mi]	CERT [g/ml]	[g/ml]		[g/ml]		x [g/mi]		CHO [m		PM [		Hwy NO	
0.00		J.UUL			[8]	CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	0.054	•	0.075	0.7	3.4	0.1	0.2	. 1		15	*	*	0.1	0.3
		@ UL	0.066	•	0.090	1.1	4.2	0.1	0.3	1	ı T	18	*		0.1	0.4
	@ 50	°F & 4K	*	*	•	•	•	•	*	•		•		*		*
	CO [g/mi] @ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					g/mi] posite)	NMHC+NOx (g/mi] [U\$06]		C	0 [g/mi] [US06]		IHC+NOx ni] [SC03]		[g/mi] C03]
50			= @ UL (Tier		CERT	STD	CERT	STD	CERT	STD	CER	T STC	CER	T STD	CERT	STD
CERT	3.5			SFTP 1	*		*	•	0.09	0.14	6.6	8.0	0.13	0.20	0.2	2.7
STD	10.0			SFTP 2	•	*	•	•	*	•	*	•	•	•	*	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVA				APORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
الله الله	3-D	2-	D RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR
CERT	0.4	0.	5 0.01	0.01	*	•	*	*	*	*	*	•	*	*	*	*
STD	2.0	2.	5 0.05	0.20		*	*	*	•	*		*	*	. *	*	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of August 2002.

Allen Jons, Chief Mobile Source Operations Division