

## KIA MOTORS CORPORATION

EXECUTIVE ORDER A-315-0041 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)		STANDA (LEV=low em transitional I SULE	JST EMISSION RD CATEGORY Ission vehicle; TLEV= LEV; ULEV=uitra LEV; V=super ULEV)		EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=ilquefied petroleum gas)		
200		4KMXT03.5G02			2	LDT: 3,751-5,750 Pounds LVW 1) USEPA 2) Counte			n 9 s ARB LEV I ULEV	.	100K/100K Gasoline (Tie Unleaded)			
No.		APORATIVE SPECIAL FEATURES & *= MILY (EVAF) No. EMISSION CONTROL SYSTEMS (ECS) *=					* = not applicable	• 10	OC/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC				
1	1 4KMXR0160G02				1	2HO2S(2), 2WU			<b>B</b> /	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust				
2		*			2		•		<del></del> #9	gas recirculation AIR/PAIR=secondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		* 4			3		*	'		TITBI= throttle body injection TC/SC=turbo /super charges				
4		*			4	*					CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series			
EVAI No.		ECS No.	ENGINE SIZE (L)			VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED				AB	ABBREVIATIONS:			
1		1	3.5			Kia Sorento 2WD/4WD								
	i													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RA AVERAGE [g/mi] CH4 RAF					NMOG or	Introgen	nunu≕ton	maidenvde	PM=bat	Ticulate r	matter	RAFEreactiv	rbon CO=c	ant factor	2/3 D [a/tan	11-2/2 44-4	
CERT STD			NMOG NMHC		NMHC	mg=millig	X-SOAK KL	. [g/mı]≖rur	nning loss 000 miles	ORVR	[g/gallon	dispensed] ahrenheit	=on-board r SFTP=supp	efueling var	or recovery	σ≖gram		
0.050		0.085	CERT [g/mi]		CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]		HCHO	[mg/mi]	PM [c		Hwy NC		
170-0		**			[9/11/1]		CERT	STD	CERT	ST	D   C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.05	0.054 *		0.075	0.5	3.4	0.1	0.2	0.2 1		15	*	•	0.02	0.27	
4		@ UL	0.06	2 *		0.090	0.6	4.2	0.1	0.3	1		18	*	* *		0.40	
5245	@ 50	0°F & 4K	F & 4K *		*	*	* *		*	*		•	*	*	*	*	*	
CO [ @ 20	°F&	₽ L	1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NC (compo	osite)	i] CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	3Ft 2	≈ @ UL (Tier 1, TLEV		1, ILEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CERT	T STD	CERT	STD	
CERT	7.5	.5		SFTP @ 4K		•	*	*	•	0.03	0.25	7.	4 10.	5 0.10	0.27	0.2	3.5	
STD	12.5	SFTP @ UL		0.15	1.03	3.11	5.04	*	*	*		*	*	- *	•			
@ UL		EVAPOR	***************************************	FAM	ILY 1	EVAPORATIVE FAMILY 2				EVA	PORAT	IVE FA	MILY 3	E	EVAPORATIVE FAMILY 4			
	3-D	2-[	)	RL	ORVR	3-D	2-D	RL (	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR	
CERT	1.2	1.3	3	0.04	0.01	*	*	*	*	*	*	*		*	•	*	*	
STD	2.0	2.	5 (	0.05	0.20	*	*	*	*	*	*	*	•	*	+	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_27<sup>2f</sup> day of August 2003.

Allen Lyons, Chief

Mobile Source Operations Division