## **SUZUKI MOTOR CORPORATION**

EXECUTIVE ORDER A-259-0091 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty true MDV=medium-duty vehicle; LVW=loade vehicle weight; ALVW=adjusted LVW	ck; CATEGOR	EMISSION STANDA Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super UL	sion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2004		4SKXV2.295D1			PC		3in 8   as ARB LEV I ULE\	,	100K / 100K	Gasoline				
No.		IPORA IILY (E		No	SPECIAL FEATURE EMISSION CONTROL SYS	ES & STEMS (ECS)	* = not applicable	OC/	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC YU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	4SKXR0120164			1	SFI, WUTWC, TWO	, HO2S(2), EGR,	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust							
2	*			2		•	Gas AIR	— gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (F)=full /partial on-board						
3		*				*	TBI							
4		*				*	diag	;≖charge air cooler  (  nostic  prefix 2≈para	JBD (F) / (F)=tuil /partial on-board illel (2) suffix=series					
EVAF No.		ECS No.	ENGINI SIZE (L			VEHICLES SUB.	JECT TO SFTP	ABBR	EVIATIONS: *					
1	1 2.3				SUZUKI: AERIO, AERIO AWD, AERIO SX, AERIO SX AWD									
		*	*			*								
*	* *													
*		* *				·	•							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methene NMCG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram													
CER	ERT STD		NMOG	NMHC	NMHC	mg=milligr	K-BORK KL	. [g/mi]=run	ning loss 300 miles	ORVR [g	/gailon	dispensed] threnheit	≖on-board :	refueling vap plemental fe	or recovery	g≈gram	
0.040		.075	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/ml]	Н	CHO [	mg/mi]	PM [		Hwy NO		
			[Aum]	[Runl]		CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD	
		@ 50K	0.041	•	0.100	0.4	3.4	0.01	0.14	. 0	0.1	15	*	*	0.01	0.19	
		@ UL	0.050	*	0.125	0.7	4.2	0.02	0.20	0	.2	18	*	•	0.02	0.27	
12	@ 50°	F & 4K	*	•	•	*	*	*	•		•	*	*	*	*	*	
@ 20	@ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			(composite) (c		[g/mi] NMHC- posite) [g/mi] [					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50K		SFTP 2 = @ UL (Tier		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEI	RT ST	CER	T STD	CERT	STD	
CERT	1.5			SFTP 1	*	*	*	*	0.06	0.14	1.:	3 8.0	0.09	0.20	0.4	2.7	
STD	10.0			SFTP 2	0.09	0.71	*	٠		*	3.	5 11.	1 *	*	1.1	3.7	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPO					PORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR	
CERT	0.8	0.8	0.01	0.08	•	*	*	*	*	*	•	- ·	*	•	•	•	
STD	2.0	2.5	0.05	0.20	•	•	*	*	•	•	•	•	<del>  •</del>	*	•	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of June 2003.

Allen Lyons, Chief

Mobile Source Operations Division