HYUNDAI MOTOR COMPANY

EXECUTIVE ORDER A-254-0116 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medlum-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	CATEGOR' vehicle; 1 ULEV=ultra	LEV= transitional LEV LEV; SULEV=super U	sion /;	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	-	5HYXT02.0JV9				LDT: 3751-5750 pounds LVW	1) USEPA Bin 9 2) Counted as ARB LEV I ULEV			100K / 150K	Gasoline (Tier 2 Unleaded)				
No.		EVAPORATIVE FAMILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYST		* = not applicable	oc	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	5HY	5HYXR0125PDJ			1	WU-TWC, TWC, H	02S(2), SFI, OE	AF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
2		*			2		*								
3		*			3		*								
4		*			4		*		agnostic prefix 2=para						
EVAI No.		ECS No.	ENGINE SIZE (L)					ECT TO SFTP E UNDERLINED	ABBI	ABBREVIATIONS:					
1		1	2.0		T	TUCSON									
*	* *		*					*							
*		* *			•										
*	* *		*	*		*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]) RAF= * !AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG CERT	NMHC	NMHC STD [g/mi]	mg=millig	ram mi	=mile K=	1000 mile	s F≃d	iegrees F	ahrenheit	SFTP=supp	lemental fe	deral test p	rocedure	
0.07	3 0.076			CERT [g/mi]			[g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
			[g/mi]			CERT	STD	CER	T S	TD (CERT	STD	CERT	STD	CERT	STD	
\$ 1		@ 50K	0.022	*	0.075	0.2	3.4	0.05	5 0	.2	0.2	15	*	*	0.01	0.27	
4.0	2	@ UL	0.023	*	0.090	0.2	4.2	0.1	0	.3	0.2	18	•	*	0.01	0.40	
	@ 50°	F & 4K		*	*	*	*	*		*	*	*	*	*	*	*	
	CO [g/mi] SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					Ox [g/mi] osite)				NMHC+NOx [g/mi] [US06]				IC+NOx i] [SC03]		CO [g/mi] [SC03]	
50	50K SFTP 2			= @ UL (Tier 1, TLEV)		STD	CERT	STD	CERT	STD	CE	RT STI	CERT	STD	CERT	STD	
CERT	0.8		SFTP @4	000 miles	*	*	*	*	0.03	0.25	5 5	7 10.	5 0.01	0.27	1.3	3.5	
STD	12.5		SFTP (0 100,000 @ miles	0.05	1.03	1.03	5.0	•	*			*	*	*	*	
@ UL	E	VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E/	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	. ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	0.39	0,5	0.02	0.10	*	*	*	*	*	*	*	*	*	*	*	*	
STD.	0.65	0.8	5 0.05	0.20	*	*	*	*	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of June 2004.

Allen Lyons, Chief Mobile Source Operations Division