

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			STANDA (LEV=low em transitional L	ST EMISSION RD CATEGORY Ission vehicle; TLEV EV; ULEV=ultra LEV /=super ULEV)	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200		6MBXV03.5U2A				PC		V II ULEV	EXH: 120K EVAF2/ORVR: 100K EVAF1& 3/ORVR: Unleaded) 150K/120K						
No.		NO NO			Э.	SPECIAL FEATU EMISSION CONTROL S			* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust					
1	6MB	BXR0174LNC				SFI, AIR, 21	1O2S(2), 2TWC, OBC	AFS/HAR-S=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR-secondary air injection/pulsed AIR						
2	6MB	MBXR0160LNY				SFI, AIR, 2HO2S(2), 2W	U-TWC, 2TWC							
3		BXR0168LNC					*								
EVA No.		ECS No.				VEHICLE MAKES & MODELS			CT TO SFTP UNDERLINED	ABBREVIATIONS:					
1		1	3.0												
1		1	3.5												
2		1	3.5			-									
2		1	3.0						Mercedes-Benz: C	enz: C280					
2		2	3.5	\perp		Mercedes-Benz: C350 4MATIC									
2		2	3.0			Mercedes-Benz: C280 4MATIC									
3		1	3.5			Mercedes-Benz: E350, E350 (WAGON)									
3		2	3.5	i_	Mercedes-Benz: E350 4MATIC, E350 4MATIC (WAGON)										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				D RAF=* AF = *	NMOG or NMHC=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxide NMOG or nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 NMHC diurnal+hot-soak RL [g/ml]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gi										1=2/3 day		
CERT STD		TD	NMOG	NMHC	NMHC	mg=milli	ot-soak k gram mi:	:∟ [g/mi]≕ru =mile K≕	inning los 1000 mile	s ORV	R [g/gallo =degrees	n dispensed] Fahrenheit	on-board r= SFTP≖sup	efueling vap piemental fe	or recovery derai test pi	g=gram ocedure	
0.039	0.0	046	CERT	CERT	[g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
OLD STREET, ST	No.		[g/mi]	[g/mi]		CERT	STD	CER	T S	TD	CERT	STD	CERT	STD	CERT	STD	
1.09	@ 50K		0.008	*	0.040	0.2	1.7	0.02	0.	05	0.2	8	*	*	0.01	0.07	
	@ UL		0.012	*	0.055	0.3	2.1	0.02	0.	.07	0.3	11	*	*	0.01	0.09	
1.1	@ 50°F	& 4K	0.014	*	0.080	0.2	1.7	0.01	0.	05	0.4	16	*	*	*	*	
CO [@ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/mi] (composite) (composite				NMHC+NOx CO [g/mi] [g/mi] [US06] [US06]				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2 = @ UL (Tie		1, TLEV)	CERT	STD	CERT	STD	CERT	ST	D C	ERT STI	CER	T STD	CERT	STD	
CERT	3.5	e Sira P	s	FTP @ 4K	*	*	* .	*	0.02	0.1	14 (0.3 8.0	0.001	0.20	0.02	2.7	
STD	10.0		S S	FTP @ UL	*	*	*	*	*	*	,	* *	*	*	*	+	
@ UL	EV	APORA	TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EV	APOR/	ATIVE F	AMILY 3	E	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L ORV	R 3-D	2-D	RL	ORVR	
CERT	0.22	0.47	0.01	0.002	0.3	0.5	0.01	0.12	0.36	0.29	9 0.	0.05	*	*	*	•	
STD	0.50	0.65	0.05	0.20	2.0	2.5	0.05	0.20	0.50	0.65	5 0.0	0.20	*	*	*	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

BE IT FURTHER RESOLVED: That certification to the evaporative emission standards in 13 CCR 1976(b)(1)(B)-(C) listed above has been permitted pursuant to 13 CCR 1976(b)(1)(F)-Endnote 3(b).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

day of January 2005.

Allen Lyons, Chief Mobile Source Operations Division