Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

VIIICII	CEI	uncau	1011 15	9.4		٠.				FUEL TYPE					
MODE		TEST GROUP			MD	VEHICLE TYPE =passenger car; LDT=light-duty truck; V=medium-duty vehicle; LVW=loaded shicle weight; ALVW=adjusted LVW)	STAND (LEV=low e transitions	LUST EMISSION ARD CATEGORY emission vehicle; TLEV= I LEV; ULEV=ultra LEV; EV=super ULEV)	(miles)	(CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
2000	в	6MBXV06.0LBI				PC	1) USEPA E 2) Counted	Bin 8 as ARB LEV I ULEV	EXH/ORVR: 100K EVAF1,3&4: 100K EVAF 2: 150K	Gasoline (Tier 2 Unleaded)					
No.		EVAPORATIVE AMILY (EVAF)			lo.	SPECIAL FEATURES EMISSION CONTROL SYST	EMS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust						
1	6MBXR0160LNY				1	SFI, AIR, TC, CAC, 21	102S(2), 2TWC	gas recirculation AIR/PAIR=secondary air Injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
2	6M	6MBXR0218LNC			2		*								
3	6M	6MBXR0160LNZ			3		-								
4	6M	MBXR0218LNZ			4		EHICLES SUB								
EVA		ECS ENGINE			VEHICLE V MAKES & MODELS ST	ANDARDS A	RE UNDERLINED	ABBREVIATIONS:	REVIATIONS:						
No.		No.	SIZE		├-	Mercedes-Benz: SL 600									
1	1 5.5			-	Mercedes-Benz; S 800, CL 600										
2		1 5.5			├	Mercedes-Benz: SL65 AMG									
3		11	6.0		╄	Mercedes-Benz: Maybach 57, Maybach 62									
4	1 5.5				↓_	Mercedes-Benz: CL65 AMG, S65 AMG, Maybach 57S									
4		1 6.0					Mai Caries-Dell	Z. OLOU AMO, GUUT.							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet on the manufacturer's "NMOG Fleet on the manufacturer's submitted compliance plan in lieu of testing). Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF=* CH4 RAF = *		NMOG or	nitrogen diurnal+ho	HCHO≕for⊓ t-soak RL	naldenyde [g/mi]=run	PM=parti ning loss	ORVR ig	gallon di	spensed]=	oon CO=car ty adjustment on-board res SFTP=suppl	fueling vap	or recovery	g=gram	
CERT	STD			NMHC	STD				1000 miles <u>r=ue</u>		=degrees Fahrenheit HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.039	0.046		ERT	CERT [g/ml]	[g/mi]	CERT	g/mij STD	CERT			RT	STD	CERT	STD	CERT	STD	
0.039		4-	g/mi)	[g/iiii]			3.4	0.02	0.14		*	15	*	•	0.05	0.19	
	@ 50	K C	.015		0.100	0.4						18	*	•	0.06	0.27	
1.7	@	JL (0.015	*	0.125	0.4	4.2	0.03	0.20			10		- + 	•		
	@ 50°F &		*	*	*	*	.	*				[g/mi]	NMI	IC+NOx	CO	[g/mi]	
CO [g		P1=6	1 = @ 4K (SULEV, ULEV, NMHC			Ox [g/mi] CO [g/mi] posite) (composite)			NMHC+NOx [g/mi] [US06]			US06]		[g/mi] [SC03]		[SC03]	
@ 20°	E 9 🖼	LEV) or 50K (Tier 1, SFTP 2 = @ UL (Tier 1, TL		ler 1, TLEV) [(comp	STD	CERT	STD	CERT	STD	CER	r str	CERT	STD	CERT	STD	
50F	(SF				CERT	*	- OLKI	*	0.03	0.14	0.4	8.0	0.003	0.20	0.005	2.7	
CERT	2.4	en.	S S	FTP @ 4K					0.00	-		11.	4 *	-	0.005	3.7	
STD	10.0		SFTP @ UL		0.03	0.71	*	*			0.4			FVADODAT			
	EVAPORATIVE FAMILY 1				EV.	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EVAPORATIVE FAM				
@ UL -			RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D		ORVR 0.01	
	3-D	2-D			0.34	0.50	0.01	0.01	1.2	1.6	0.004	0.01	0.5	1.6	0.000		
CERT	0.3	0.5 2.5	0.01		0.50	0.65	0.05	0.20	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

BE IT FURTHER RESOLVED: That certification to the evaporative emission standards in 13 CCR 1976(b)(1)(B)-(C) listed above has been permitted pursuant to 13 CCR 1976(b)(1)(F)-Endnote 3(b).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby superseedes Executive Order A-003-0307 dated January 19, 2005.

day of December 2005. Executed at El Monte, California on this

Allen Kyons, Chief

Mobile Source Operations Division