DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0715

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	FX	HAUST EMISSION NDARD CATEGORY	USEFU (mil		INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		FUEL TYPE	
2006			USEPA Bin 4		EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2 Unleaded)	
	6CRXV05.7MD1	Passenger Car	Co	unted as ARB LEV2 ULEV	120K	150K	* E		Omeaueu)	
No.		SPECIAL FEATURES		EVAPORATIVE		AF)		DISPLAC	EMENT (L)	
1	2TWC, 2HO2S(2), SFI, EGR, OBD(P)			6CRXR0150GHA						
*	•			•				5.7		
•										
		*								

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

day of March 2006.

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ AVERAGE [g/mi] CH4 RA		AF = *	NMOG or NMHC	HCHO=for	maldehyde; P	M=particula	ate matter,	Ilon disper	sed)=on-b	nard refue	ling vapor r	monoxide; N est]=2/3 day o ecovery; g=gra	diurnal+ am; mg= milli	gram	
CERT	STD	NMOG	NMHC STD			not-soak; RL [g/m]=running loss, over [g/gains in species] mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemen CO [g/mi] NOx [g/mi] HCHO [mg					na/mil P		g/mi]	Hwy NOx [g/mi]	
0.057	0.046	CERT	CERT	[g/mi]		[g/mi] STD	CERT	STD			STD	CERT	STD	CERT	STD
0.057	0.040	[g/mi]	[g/mi]		CERT	1 310	CERT	+ ::	- -		•	*		*	*
41.44	@ 50K	*	*	<u> </u>	· -						11.	*	-	0.01	0.05
	@ UL	0.028	*	0.070	0.5	2.1	0.02	0.04			''' 			*	•
1444	50°F & 4K	*	*	*	•	· _	•	*			<u></u> _				
		1.25		NMHC+NO		CO [g		NMHC [g/mi]			[g/mi] S06]		HC+NOx ij [SC03]		[g/mi] C03]
CO [g/mi] @ 20°F & 50K		$\label{eq:constraint} \mathbf{r}_{i} = \mathbf{r}_{i}, \mathbf{r}_{i} = \frac{\mathbf{p}_{i}}{2}$	(comp	STD	CERT	STD	CERT	STD	CERT	STD	CER	r STD	CERT	STD	
			200 11-		*	+	•	0.08	0.14	1.1	8.0	0.03	0.20	0.1	2.7
STD	10.0		000 miles @ 120000 miles	0.07	0.63	*	*	*	*	1.2	11.1	*	*	0.4	3.7
3-Days Di			iurnai + Ho ns/test) @		2-Days Diu (grams	urnal + Hot Soak is/test) @ UL		Running Loss (grams/mile) @ UL			1	On-Board Recovery (g	Refueling rams/gallo	ueling Vapor s/gallon) @ UL	
Evaporative Family					CERT		STD (CERT S			CERT		STD	
		CERT		TD		<u> </u>		0.0		0.05		0.10	0.20		
6CRXR0150GHA 0.34		0.34	0	.50	0.33	'	0.65	*	+	*	-+-	•		*	
*		*		*	*			-				*		*	
		*		*	•		*							+	
		•		•	*	*		*							

^{*=} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. Intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
	MAGNUM	6CRXR0150GHA	1	5.7	*	E	SFTP	Partial
DODGE		6CRXR0150GHA	1	5.7		E	SFTP	Partia
CHRYSLER	300C/SRT-8	OCKARO 1300 IIA			 		CETE	Partia
DODGE	CHARGER	6CRXR0150GHA	1	5.7		E	SFTP	Faite
DODGE	MAGNUM AWD	6CRXR0150GHA	1	5.7	*	E	SFTP	Partia
DODGE			1	5.7	*	E	SFTP	Partia
CHRYSLER	300C AWD	6CRXR0150GHA	1	5.1		<u> </u>		L