New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mi	L LIFE les)	IN COMI (*=N/A o A/E=e	MEDIATE -USE PLIANCE r full in-use; xh. / evap. diate in-use)	FUEL TYPE	
			USEPA Bin 9a (opt)	EXH / ORVR	EVAP	EXH EVAP * E		Gasoline (Tier 2 Unleaded)	
2006	6GMXT03.5187	LDT: 3751-5750 Pounds LVW	Counted as ARB ULÉV	100K	150K				
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE	FAMILY (EV	DISPLACEMENT (L)				
1	WU-TWC,T	WC, HO2S(2), SFI, OBD(F)	6GMXR	0170957					
*		*				3.5			
*		*							
*		*	1						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

day of January 2005.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lygns, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE [g/mi] CH4		@ RAF=* RAF = *	NMOG or		thane; NMOG=r ormaldehyde; P												
CERT STD NMOG			NMHC	NMHC STD	mi=mile;	K=1000 miles:	mid ioss: t	URVRIOO	สแกก สเรก	ensedi=	on-board re	fuolinava			am; mg ≃mill	igram	
0.058 0.062		[g/mi]	CERT [g/mi]	[g/mi]	CO [g/mi]		NOx [g/mi]		ŀ	HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
76	@ 50K	0.071	*	0.400	CERT	_	CERT			ERT	STD	CEF	₹T	STD	CERT	STD	
grant and			*	0.100	0.5	3.4	0.2	0.2		*	15.	*		*	0.08	0.27	
e e	@ UL	0.071	<u> </u>	0.130	0.5	4.2	0.2	0.3		*	. 18.	*		*	0.08	0.40	
100	@ 50°F & 4K	•	*	*	*	*	*	*		*	*	*		* .	*	*	
CO [g/mi] @ 20°F & 50K		Productive grants		NMHC+NC (compo									NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
				CERT	STD	CERT	STD	CERT	STD	CE	RT S1		ERT	STD	CERT	STD	
CERT	3.7		000 miles	*	*	*	*	0.19	0.25	7.	7 10	.5 (0.08	0.27	0.4	3.5	
STD	12.5	SFTP	@ 100000 miles	0.28	1.04	*	*	*	*	7.	7 14	.6		*	0.8	4.9	
				ırnal + Hot s/test) @ U				nal + Hot Soak test) @ UL		Running Loss (grams/mile) @ UL			On-Board Refue Recovery (grams/			ueling Vapor s/gallon) @ UL	
			CERT	ST	D CERT		STD		CEI	CERT				CERT		STD	
6GMXR0170957		0.49	0.6	5	0.79	0.	.85	0.0	0	0.0	5	0.04		0.20			
Ŕ		*	*		*		*	*		•				*			
*			*	*		*	1	*	*		*	7		•		*	
*		*	*		*		*	*:		*	_		*	+-			

^{* =} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORA TIV E FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
CHEVROLET	COLORADO 2WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
CHEVROLET	COLORADO 4WD	6GMX R01 70957	1	3.5	*	E	SFTP	Full
CHEVROLET	COLORADO CAB CHASSIS INCOMPLETÉ 2WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
CHEVROLET	COLORADO CREW CAB 2WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
CHEVROLET	COLORADO CREW CAB 4WD	6G M XR0170957	1	3.5	*	E	SFTP	Full
GMC	CANYON 2WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
GMC	CANYON 4WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
GMC	CANYON CAB CHASSIS INCOMPLETE 2WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
GMC	CANYON CREW CAB 2WD	6GMXR0170957	1	3.5	*	E	SFTP	Full
GMC	CANYON CREW CAB 4WD	6GMXR0170957	1 .	3.5	*	E	SFTP	Full
HUMMER	H3 4WD	6GMXR0170957	1	3.5	*	E	SFTP	Full